

e-ISSN: 2319-8753 | p-ISSN: 2347-6710

DIA

International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 5, May 2024

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

🖂 ijirset@gmail.com



e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Refereed Journal |

Volume 13, Issue 5, May 2024

[DOI:10.15680/IJIRSET.2024.1305285]

Plastic Brick Made from Waste Plastic

A. Taranath¹, Madhusudan A V², Venkatesh Naik³, Harikrishna B⁴, Husen Basha⁵

Assistant Professor, Dept. Mechanical Engg., Ballari Institute of Technology and Management, Ballari, Karnataka, India¹

U.G. Students, Dept. Mechanical Engg, Ballari Institute of Technology and Management, Ballari, Karnataka, India^{2,3,4,5}

ABSTRACT: Plastic is a very common material that is now widely used by everybody in the world. Plastic plays a predominant role in reusable in this era, as it is compact and light in weight. Common plastic items that are used are covers, bottles, and food packages. The great problem with plastic is its decomposition. Plastic is made of polymer chemicals and they are non-biodegradable. This means that plastic will not decompose when it is placed in earth. Though plastic is a very useful material that is flexible, robust and rigid they become waste after their use and they pollute the air and land. Recycling is processing use waste materials into new products to prevent waste of potentially useful materials. The increase in the popularity of using eco-friendly, low cost and lightweight construction materials in building industry has brought about the need to investigate how this can be achieved by benefiting to the environment as well as maintaining the material requirements and their standards.So, our project is to prepare plastic bricks to replace normal clay brick

KEYWORDS: Plastic, Bricks, chemicals, non Bio-degradable,eco friendly.

I. INTRODUCTION

Plastic is a very common material that is now widely used by everybody in the world. Plastic plays a predominant role in reusable in this era, as it is compact and light in weight. Common plastic items that are used are covers, bottles, and food packages. The great problem with plastic is its decomposition. Plastic is made of polymer chemicals and they are non-biodegradable. This means that plastic will not decompose when it is placed in earth. Though plastic is a very useful material that is flexible, robust and rigid they become waste after their use and they pollute the air and land. Recycling is processing use waste materials into new products to prevent waste of potentially useful materials. The increase in the popularity of using eco-friendly, low cost and lightweight construction materials in building industry has brought about the need to investigate how this can be achieved by benefiting to the environment as well as maintaining the material requirements and their standards. From the advantages of plastic recycling procedure is used. For the production of plastic bricks is an optimal method for controlling the problem by decomposition of plastic waste and also it costs economical for the production of building materials. In this study, plastic waste from factories will be used to incorporate with cement and sand to produce sand bricks. The bricks will then be tested to study the compressive strength, efflorescence and water absorption. In the recent past research, the replacement and addition have been done with the direct inclusion of polyethylene, polyethylene terephthalate (PET) bottles in shredded form, chemically treated polyethylene-fiber, PET in small particles form by replacing natural coarse aggregate. Most of replacements have been done by volume calculation, and showed the decreased in compressive strength as the increased plastic waste. In this study, recycled plastic waste have been introduced in the form of crushed. The replacement of plastic waste material has been done by weight.

II. RELATED WORK

Muyen Z, Barna TN, Hoque MN (2016). Strength properties of plastic bottle bricks and their suitability as construction materials in Bangladesh. Progressive Agriculture 27(3): 362-368.

"Study of plastic dust brick made from waste plastic" by **Ronak Shah, Himanshu Garg, Parth Gandhi, Rashmi Patil, Anand Daftardar (2017).** They used plastic dust as the main component of waste product which is the by – product of many industrial products such as PVC pipes and they have heated plastic dust at 220°C. The final product from plastic dust was tested for the compressive strength and it was observed as 6.66 N/mm2 which is higher than conventional bricks (3-5 N/mm^2).

"Plastic in Brick Application." By Siti Nabilah Amir & Nur Zulaikha Yusof (2018). The studies showed the possibility of using plastic as binder with the aid of catalyst through depolymerisation of PET to replace cement. It was observed that a significant decrease in compressive strength is observed for more than 50% replacement of binder with



e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Refereed Journal |

Volume 13, Issue 5, May 2024

DOI:10.15680/IJIRSET.2024.1305285

PET waste. With increased amount of PET, the softening point of the bricks produced was also increased. They used the different size of moulds like (150*150*150) mm, (200*100*100) mm etc.

Hiremath PM, Shetty S (2014). utilization of waste plastic in manufacturing of plastic-soil bricks. international journal of technology enhancement and emerging engineering research 2(4): 2347-4289

III. METHODOLOGY

- > To Prepare plastic bricks
- > To vary the percentage of plastic in bricks to determine the strength performance
- > To compare strength of plastic bricks with normal clay bricks
- Cost Compare in between plastic bricks and normal clay bricks





(b)





Figure a and b are moulds for making the plastic bricks Figure c shows the preparation of moltenin open hearth furnace



e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |

||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305285

Figure d, e and f shows the compression test of rectangular plastic brick, normal clay cement brick and hexagonal plastic brick respectivel

IV. EXPERIMENTAL RESULTS

nt View Data Delete Record Superin	poor Selad. Madulus Data: Graph Scale: Additional Results: Time Graphs: Dop. Modulus	
FIE PVT LTD. Salect Graph C Load Vs Displacement Stress Vs Disp. Sterss Vs Strain Sandarg Moment Dig.	Graph: Load Vs Displacement	
Results Internet liente per per		
Hamun Force Fml 204 520 kM	121000-	
Dags at Fm 2.700 mm	290.000	
Mac Dog 2700 mm	340.000	
Concerning Strength Company	200.000-	
	40.000	
	10-0.000 0.000 0.900 1.200 1.900 1.900 2.100 2.400 2.700	
	Normal Part Zoom Print Graph Close	
	FIE Make Universal Testing Machine, UTE-40	
	De	

Figure (a) is normal clay cement brick graph

FIE FVT LLTD. Select Graph O Load Vs Displacement Stress Vs Disp. Stress Vs Disp. Stress Vs Disp. Bending Moment Dig. Results Driv Texed Riends gets proted Maximum Face (Fm) 213140 MI Output of Fm 27700 mm Max. Disp. 27700 mm 10000-	
Select Graph Superimpose select	
Connect Stress Vs Disp. Connect Stress Vs Disp. Connect Superimpose select Connect Con	
Stress Vs Strain Strain Stress Vs	
Bending Reash Up; Logit Results Driv Toked Results gets protect 20000- Maximum Force (Fm) 219,140 kH Drips at Fin 27,700 mm Has: 27,700 mm 1000- 10000-	
ResultsDriv Technol Results gets prited 240.000- Maximum Force (Fin) 219.140 kN 240.000- Disp. at Fin 27.700 mm 210.000- Max. Disp. 27.700 mm 180.000-	
New mann Force (Fin) 219,140 kN 240,000 - Disp. at Fin 227,700 mm 218,000 - Mass. Disp. 227,700 mm 180,000 -	
Disp. at Fin 27.700 mm 210.000- Max. Disp. 27.700 mm 180.000-	
Max. Disp. 27.700 mm 180.000-	
(c/s Acea (So) 7.750.000 mm ²	
compressive Shength 0.028 kH/mm ² 150.000-	
121000-	
5000	
60.000 -	
10 000 1500 1500 1500 1500 1800 2000 2000 27000	
Tolectore 3000 b.000 3000 15000 15000 16000 21000 21000 21000	
Since Normal Graph Part Zoom Print Graph Close Print	
FIE Make Universal Testing Machine, UTE-40	

Figure (b)is rectangular plastic brick graph



|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |

Volume 13, Issue 5, May 2024

DOI:10.15680/IJIRSET.2024.1305285



Figure (c) is hexagonal plastic brick graph

Fig a is normal clay cement brick graph

Fig b is rectangular plastic brick graph

Fig c is hexagonal plastic brick graph

From the experiment conducted we come to know that the ultimate compressive strength of the plastic brick is 19MPa, the ultimate compressive strength of the plastic rectangular brick is 28MPa and the ultimate compressive strength of the hexagonal plastic brick is 15 MP. From these results we come to know that rectangular plastic brick has maximum compressive strength.

V.CONCLUSION

The Plastic sand bricks possess more advantages which include Cost efficiency, Removal of waste products thus abolishing the land requirement problem for dumping plastic, Reduction in the emission of greenhouse gases by the conversion of flue gases in to synthetic Oil etc., This method is suitable for the countries which has the difficult to dispose/recycle the plastic waste. The natural resources consumed for the manufacturing Of Plastic sand bricks are very much less when compared to its counterparts. Plastic sand brick possesses more advantages which includes cost efficiency, resource efficiency, reduction in emission of greenhouse gases, etc. Plastic sand brick is also known as "Eco-Bricks" made of plastic waste which is otherwise harmful to all living organisms can be used for construction purposes. It increases the compressive strength when compared to fly ash bricks & clay bricks. By use of plastic sand bricks, the water absorption presence of alkalis was highly reduced.

- ▶ Waste plastic, which is available everywhere, may be put to an effective use in brick.
- Plastic bricks can help reduce the environmental pollution, thereby making the environment clean and healthy.
- Plastic sand bricks reduce the usage of clay in making of bricks.
- > Plastic sand bricks give an alternative option of bricks to the customers on affordable rates.
- ➤ Water absorption of plastic sand brick is zero percent.
- Compressive strength of plastic sand brick is 5.6 N/mm2 at the compressive load of 96KN.
- We conclude that the plastic sand bricks are useful for the construction industry when we compare with Fly Ash bricks and 3rd class clay bricks.



e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Refereed Journal |

||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305285

REFERENCES

- [1] Ghernouti, Bahia Rabehiucef, Brahim Safi and RabahChaid, "UseOfRecycledPlasticBagWasteIn The Concrete" Journal of International YoScientific Publications:Materials,MethodsandTechnologies Volume 8, ISSN 1314-7269 (Online), Published at http://www.scientific-publications.net
- [2] Ghernouti, Bahia Rabehiucef, Brahim Safi and RabahChaid, "UseOfRecycledPlasticBagWasteIn The Concrete" Journal of International YoScientific Publications:Materials,MethodsandTechnologies Volume 8, ISSN 1314-7269 (Online), Published at http://www.scientific-publications.net
- [3] Khilesh Sarwe, "Study of Strength Property of Concrete Using Waste Plastics and Steel Fibers" Department of Civil Engineering, Jabalpur Engineering College, Jabalpur, India. International Journal of Engineering and Science (IJES)/vol 3/Issue/5/Pages/09-11/2014/.
- [4] Bhogayata, K. D. Shah, B. A. Vyas, "Performance of concrete was using Non-Recyclable plastic wastes as concrete constituent", International Journal of EngineeringResearch&Technology(IJERT)vol.1 issue 4, june-2012.
- [5] Mojtaba ValinejadShoubi, Azin Shakiba Barough (2013) Investigating the Application of Plastic Bottle as a Sustainable Material in the Building Construction. International Journal of Science, Engineering and Technology Research (IJSETR) 2(1): 2278 -7798.
- [6] Shilpi Saxena, Monika Singh (2013) Eco- Architecture: PET Bottle Houses. International Journal of Scientific Engineering and Technology 2(12): 1243-1246.
- [7] K Ramadevi Experimental Investigation on the Properties of Concrete with Plastic PET (Bottle) FibersasFine Aggregates'InternationalJournalof Emerging Technology and Advanced Engineering 2(6):1-5.Samarpan foundation, House construction withplasticbottles,NewDelhi,India.How-ToMake a Bottle Brick.
- [8] Puttaraj Mallikarjun Hiremath, Shanmukha shettya(2014) Utilization of Waste Plastic in Manufacturing of Plastic-Soil Bricks, International journaloftechnologyenhancementsandemerging engineering research 2(4): 2347-4289.
- [9] Pratima Patel, Akash Shah, (2014) Sub stainable development using waste PET bottles as construction eleme

INTERNATIONAL Standard Serial Number India







INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com