

e-ISSN: 2319-8753 | p-ISSN: 2347-6710

DIA

International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 5, May 2024

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

🖂 ijirset@gmail.com

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |



||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305290

Investigations on the Hard X-ray Reflectivity of Speculum and OtherMetal Mirrors Using Computational Techniques

Nazimudeen E. A, Girish T. E, Sunila Abraham

Department of Physics, Christian College, Chengannur, Kerala, India Department of Physics, University College, Thiruvananthapuram, Kerala, India Department of Physics, Christian College, Chengannur, Kerala, India

ABSTRACT: Recent technological developments in mirror-based grazing incidence X-ray optics have stimulated the need for basic research in high-quality metallic mirror materials for novel applications. Among different metallic mirror materials, a binary alloy of copper and tin called speculum metal was used to make vital optical components in early studies of experimental astronomy and X-ray optics. It is highly reflective and suitable to make brilliant polishing surfaces with excellent resistance to tarnishing. In this context, we have studied for the first time the reflectivity of the speculum and other mirror materials in the hard X-ray region based on theoretical calculations. Furthermore, theoretical calculationsareverified well with the X-ray database program of computer simulation. The results obtained reveal that the reflectivity of speculum metal in the hard X-ray region at grazing anglesbelow 10 arc minutes is higher than that for commonly used high-density mirror materials. This hard X-ray reflectivity of speculum metal will open up promising possibilities for it to useas a vital optical component in various technological applications including X-ray astronomy, X-ray microscopy, X-ray imaging, synchrotron beamlines, X-ray lasers, X-ray reflection spectroscopy and other areas of high energy physics.

KEYWORDS: Compton Effect, X-ray reflectivity, Speculum metal, Metal mirror X-ray astronomy.

I.INTRODUCTION

The total reflection of X-raysfrom solid samples with smooth surfacesfirst reported by A. H. Compton in 1923 can be assumed to mark the birth of grazing incidence X-ray optics [1-4]. With this technique, the field of X-ray astronomy became a major scientific discipline in astrophysics and cosmology [5, 6]. It has made great progress in the past several years with technological advances in X-ray observations and instrumentations. The remarkable scientific observations in that field have enriched and guided new views of the universe. They have also shed light on dark matter and dark energy [7, 8]. However, future space missions in X-ray astronomy require the integration of highly reflective thin mirror segments into a lightweight, high-resolution telescope housing without distortion [9].Mirror materials like nickel, gold, platinum and Iridium are good reflectors and are commonly used for making X-ray mirrors in space missions[10]. However, recent advances in grazing incidence X-ray opticshave stimulated the need for basic research in high-qualityoptically active mirror materials for novel applications. In this context, a detailed study of the reflectivity of speculum metal in the X-ray region, especially in the hard X-ray region will be highly useful and it forms the theme of the present paper.

Speculum metal is a typical binary alloy of copper and tin in the proportion of about 2:1. It is suitable to make brilliant polishing surfaces and ithas a pleasing silvery white colour withexcellent resistance to tarnishing. The antiquity of this particular alloy dates back to the Bronze Age [11-13]. It regained its prominence for a short period from the time of Isaac Newton in the 17th century to the early decades of the 20th century as mirrors, gratings, etc. for making large reflecting telescopes and other optical precision instruments [14, 15]. Speculum metal is not only a material of the past but also is relevant today because of its excellent applications in diverse fields of science and technology apart from its archaeometallurgical importance. In recent years, it finds several engineering applications in various fields such as slit material in transmission electron microscopy, an alternative to nickel undercoating for gold or chromium electroplating, anode material for lithium-ion batteries, etc. [16-18]. It can also be used in several scientific observations and discoveries

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |

(1)

Volume 13, Issue 5, May 2024

DOI:10.15680/IJIRSET.2024.1305290

covering different areas including experimental astronomy, optical and nuclear instrumentations, spectroscopic and other studies in modern physics [19-21].

II.BASIC CONCEPTS OF X-RAY REFLECTION

The interaction of X-rays with matter can be described by an index of refraction less than unity, and is given by,

$$n = 1 - \delta - i\beta$$

With real part δ , a decrement of the refractive index describing the reflection, given by

$$\delta = \frac{N_A}{2\pi} r_{e_A} z_{A}^2 + C_m \lambda^2$$
(2)

and β determining the absorption properties of the material, given by $\beta = \frac{\lambda \mu}{4\pi}$, where N_A is the Avogadro number, r_eis the

classical electron radius, Z is the atomic number, A is the atomic mass, ρ is the mass density, λ is the wavelength of X-ray photon, C_m is the material constant and μ is the linear absorption coefficient. X-rays undergo total external reflection only

for the grazing angle of incidence (θ) less than the critical angle,

$$\theta_{\rm c} = (2\delta)^{1/2} = \frac{1.651}{\rm E} \left(\frac{\rm Z}{\rm A}\rho\right)^{1/2}$$
(3)

Where E is the photon energy.

The reflection of X-rays is described by the Fresnel equations, which are derived by Compton and Allison. Reflectivity is calculated by three approximation relations, given by

(i)
$$R = 1 - \sqrt{\frac{2}{\delta}} \cdot \frac{\beta}{\delta} \theta \text{ when } \theta = \theta_{c} (4. a)$$

(ii)
$$R = \frac{\delta + \beta - \sqrt{2\beta\delta}}{\delta + \beta + \sqrt{2\beta\delta}} \text{ when } \theta < \theta_{c} (. b) \text{ and}$$

(iii)
$$R = \frac{\delta^{2}}{4\theta^{4}} \text{ when } \theta > \theta_{c} (4. c)$$

Where θ is the grazing angle of incidence [22-25].

2. Materials and methods

Experimental investigations are carried out by using a highly reflecting speculum metal mirror, cast and polished using traditional techniques from Aranmula, a village in Kerala, Southern India [26-28]. The purchased mirror (Aditi Handicrafts Centre, Aranmula) with an aperture of 0.05m, separated from the brass base is cleaned and sectioned into several fragments of different dimensions using a diamond cutter, which is used for experimental characterization. X-ray reflection parameters are calculated theoretically by using the above basic equations and verifications of these calculations are carried out by using computer simulation programmesbased on Henke- Gullikson-Davis database at Lawrence Berkeley Laboratoryand Sergey's X-raylibrary database at Argonne National Laboratory [29, 30].

III.EXPERIMENTAL EVIDENCE FOR HIGH X-RAY REFLECTIVITY OF SPECULUM METAL

A unique X-ray reflection property of speculum metal is observed from early experiments related to X-ray optics carried out by A. H. Compton and R. L. Doan. Compton pointed out in his literary article that considerable X-ray reflection does occur from a speculum surface when it strikes the surface at small glancing angles, within the critical angle for total reflection. Later, Doan confirmed this fascinating experimental investigation results in collaboration with Compton and they obtained the spectra of ordinary X-rays by reflection at very small glancing angles from a grating ruled on speculum metal [31, 32]. Some of these spectra are used to measure X-ray wavelengths with considerable precision. Spectra of K – K-series radiations both from copper and molybdenum obtained by reflection at a small glancing angle from a grating ruled on speculum metal are shown in Fig. 1 (a) and (b). In connection with these experimental results, the X-ray reflectivity of speculum metal in comparison with a variety of other mirror materials as functions of different photon energies at different grazing angles of incidence have been studied.

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |



||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305290



Fig. 1. (a) Reflection on speculum using Cu Ka X- rays (b) Reflection on speculum using Mo Ka X- rays

D – Image of a direct beam, O - Directly reflected beam [38, 39]

III. RESULTS AND DISCUSSION

Based on the fundamental theory of X-ray reflection, we have calculated the total external reflection critical angle for speculum metal with other mirror materials for photon energies from 8.05 keV to 300 keV, which is shown graphically in Fig. 2. It is observed from our study that the critical angle reduces as the x-ray photon energy increases from 8.05 keV to 300 keV and is high for iridium and low for aluminium. These observations led us to the conclusion that the critical angle for total external reflection reduces inversely as the photon energy increases and also high-density materials with higher atomic numbers have a larger critical angle at any photon energy. Theoretically, the estimated total external reflection critical angle of Cu K_{α} and Mo K_{α} X-rays for different substances like Al, Ni, Cu, Pt and Au is similar to that reported by N. V. Alov and Klockenkämper in their literary work [23, 33].

In the next step, a theoretical study of the critical angle reflectivity of the speculum and other materials for different photon energies from 8.05 keV to 300 keV is made and is graphically represented in Fig. 3. Critical angle reflectivity of the speculum is found to be gradually increased from 54.2 to 88.3 for photon energies from 8 keV to 300 KeV, compared with other materials. It is also found that the critical angle reflectivity of the speculum is higher than that of high-density common X-ray mirror materials such as iridium, platinum, and gold and comparable with that of lighter elements such as silver, nickel and copper.

Theoretical reflectivity of speculum metal with other mirror materials for various grazing angles of 1- 10 arc minutes using Cu K α and Mo K α X-rays with energies 8.05 keV and 17.5 keV are given in Tables 1 and 2. In the X-ray region of Cu K α , the speculum shows higher reflectivity, which is comparable with that of commonly used high-density X-ray mirror materials, but slightly less than that of lighter elements. The reflectivity in the region of Mo K α X-ray is found to be higher than that of commonly used high-density X-ray mirror materials and comparable with that of light elements. But aluminium shows poor reflection in this hard X-ray region, which is about 1-2% only. Henke-Gullikson-based computer simulated reflectivity of speculum with various mirror materials at different grazing angles for Cu K α and Mo K α X-rays are given in Tables 3 and 4, which are broadly in good agreement with theoretical calculations. The simulated spectral reflecting power of perfectly smooth speculum metal surface for Mo K α compared with other mirror materials are shown in Fig. 4 and 5. Reflectivities of more than 80 % are observed for X-ray energies up to 17.5 keV at all grazing angles, but a reduction in reflectivity is observed in all cases at higher X-ray energies.

ijirset

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |

||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305290

Moreover, the simulated reflectivity plot of speculum metal for Cu K α and Mo K α X-rays as functions of different photon energies up to 30 keV at various grazing angles of incidence using a computer simulation program based on Henke-Gullikson database and Sergey's X-ray library database are graphically shown in Fig. 6 and 7. The reflectivity is decreased at all grazing angles of incidence but more reduction in reflectivity is observed at grazing angles of 10 and 7 arc minutes. Early literary work proposed by Henke et al. also reported the reflectivity of Al, Ni, Cu and Pt at various grazing angles for different energies, which has a close resemblance to our estimation [35]. It also suggested that the reflectivity of gold, copper and nickel in the soft X-ray region (using Copper K α , particularly for energy 8 keV at a grazing angle of 5 mrad) are above 88 to 96%, but aluminium shows a reflectivity of 7.6%. However in the hard X-ray region using Molybdenum Ka with energy 17.479 keV at a grazing angle of 5 mrad, all these materials show poor reflectivity. Theoretical reflectivity at the perfectly smooth surface of speculum metal for Mo K α X-ray is plotted as functions of different photon energies and various grazing angles of incidence and is shown in Fig. 8. The reflectivity plot shows that speculum reflects with high efficiency at energies 8.05 keV and 17.5 keV and it decreases very rapidly at higher photon energies at a grazing angle of 10 arc minute. However, it reflects with high efficiency and gives a finite value up to 300 keV at a grazing angle of one arc minute. This implies that the efficiency of reflection is high as the grazing angle within the critical angle regime reduces to its lower value. In brief, theoretical studies of the X-ray reflectivity of speculum metal in comparison with a variety of other mirror materials and its verification based on the Henke- Gullikson- Davis database and Sergey's X-ray library database confirm the results of Compton and Deon experiments (1923) on the X-ray reflectivity of speculum metal using Cu Ka and Mo K α X-rays, that is about above 80%. Thus the reflectivity of speculum metal in the X-ray region, particularly in the hard X-ray region is highly interesting and it will find excellent applications for this typical alloy as mirrors, gratings, filters, light pipes, etc. in various fields of astrophysics, especially in X-ray astronomy, X-ray optics, X-ray microscopy, Xray reflection spectroscopy and other areas of high energy physics.

IV.CONCLUSIONS

X-ray reflectivity of various mirror materials including speculum metal is studied in detail for different photon energies ranging from 8.05 keV to 300 keV at various grazing angles of incidence. Speculum metal shows a gradual increase in critical angle reflectivity with the increase of photon energy. Low-density materials generally show high reflectivity at small grazing angles compared to high-density materials. The reflectivity of speculum metal in the hard X-ray region at various grazing incidence angles of 1–10 arc minutes is found to be high in comparison with commonly used high-density mirror materials such as gold, platinum and iridium. This also confirms the results of Compton and Deon experiments (1923) on the X-ray reflectivity of speculum metal using Cu K α and Mo K α X-rays that is about above 80%. The high reflectivity may be due to the presence of a thin transparent layer of a well-polished smooth surface containing nanoscale crystalline particles. The high reflectivity of speculum metal in the hard X-ray region may open up promising possibilities for this alloy to be used as mirrors, gratings, filters, light pipes, etc. in various fields of astrophysics, especially in X-ray astronomy, X-ray microscopy, X-ray imaging including medicine and industry, X-ray lithography, X-ray reflection spectroscopy and other areas of high energy physics.

ACKNOWLEDGEMENTS

Authors are extremely grateful to Dr. S. NarayanaKalkura, Dr. K. MuraleedharaVarier, Mr.Midhun, Dr.Gopchandran, Dr. Abdul Kalam, for their constructive comments, valuable suggestions, continuing support and contributions during the entire work, the director of NCESS, the staffs of SICC, University of Kerala, for providing useful reference materials and laboratory facilities to conduct experimental analyses.

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |



||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305290



Fig. 2 Critical angle for various materials calculated for different photon energies



Fig. 4 Henke- Gullikson data based simulated reflectivity of perfectly smooth speculum metal for different photon energies up to 30keV at various grazing angles of incidence



Fig. 3 Critical angle reflectivity of various materials as a function of different photon energies



Fig. 5 Henke- Gullikson data-based simulated reflectivity of speculum metal as functions of photon energies up to 30 keV at various grazing angles of incidence

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |



||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305290



Fig. 6Sergey's X-ray librarydata-based simulated reflectivity of pspeculum metal for different photon energiesup to 30 keV at various grazing angle



Fig. 7Sergey's X-ray library data-based simulated reflectivity of perfectly smooth speculum metal for different photon energies up to 30 keV at various grazing angle



Fig. 8 Theoretical reflectivity of perfectly smooth surface of speculum metal for Mo K_{α} X-rays as functions of different photon energies and various grazing angle of incidence

Table 1 Theorem	retical reflectivity	of various	mirror	materials	for N	Mo K	a X-rays
-----------------	----------------------	------------	--------	-----------	-------	------	----------

Matarial	Reflectivity of various materials calculated for Cu K_α X-rays at different grazing angles						
Material	1 arc min	3 arc min	5 arc min	7 arc min	10 arc min		
Speculum	99.60	98.79	98.0	97.19	95.98		
Gold	99.43	98.34	97.25	96.13	94.48		
Platinum	99.45	98.48	97.45	96.47	94.95		
Iridium	99.53	98.58	97.63	96.68	95.26		
Silver	99.30	97.90	96.50	95.12	93.10		
Copper	99.83	99.45	99.16	98.82	98.32		

よう は IJIRSET |e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |

||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305290

Nickel	99.85	99.55	99.26	98.96	98.52
Aluminum	99.72	99.17	98.62	98.10	97.24

Material	Reflectivity of various materials calculated for Mo K_{α} X-rays at different grazing angles						
Wateria	1 arc min	3 arc min	5 arc min	7 arc min	10 arc min		
Speculum	99.29	97.89	96.48	95.04	92.92		
Gold	98.58	95.74	92.90	90.02	85.77		
Platinum	98.70	96.10	93.49	90.85	86.95		
Iridium	98.77	96.32	93.86	91.37	87.68		
Silver	99.61	98.82	98.04	97.24	96.06		
Copper	99.24	97.71	96.18	94.64	92.35		
Nickel	99.31	97.95	96.59	95.20	93.15		
Aluminum	99.87	99.61	99.36	4.50	1.09		

Table 2 Theoretical reflectivity of various mirror materials for Mo Ka X-rays

Table 3 Reflectivity of various mirror materials for Cu K_{α} X-rays using Computer simulation based on the Henke-Gullikson-Davis database

	Reflectivity of va	rious materials for	Cu K_{α} X-rays at different grazing angles			
Material	1 arc min	3 arc min	5 arc min	7 arc min	10 arc min	
Speculum	99.56	98.70	97.82	96.88	95.33	
Gold	99.39	98.17	96.95	95.71	93.78	
Platinum	99.44	98.33	97.22	96.09	94.34	
Iridium	99.48	98.44	97.40	96.35	94.72	
Silver	99.31	97.96	96.59	95.17	92.89	
Copper	99.81	99.43	99.05	98.64	97.96	
Nickel	99.82	99.47	99.11	98.73	98.09	
Aluminum	99.74	99.21	98.62	97.94	96.40	

Table 4Reflectivity of various mirror materials for Mo K_{α} X-rays using Computer simulation based on
Henke-Gullikson- Davis database

Material	Reflectivity of various materials calculated for Mo K_{α} X-rays at different grazing angles						
	1 arc min	3 arc min	5 arc min	7 arc min	10 arc min		
Speculum	99.29	97.82	96.12	93.84	85.20		
Gold	98.55	95.64	92.59	89.21	82.75		
Platinum	98.65	95.95	93.14	90.06	84.36		
Iridium	98.77	96.29	93.72	90.91	85.76		
Silver	99.60	98.78	97.84	96.64	93.09		
Copper	99.24	97.67	95.87	93.52	85.88		
Nickel	99.32	97.93	96.35	94.30	88.00		
Aluminum	99.87	99.58	99.02	20.30	1.82		

Ì Ì Ì ⅔ IJIRSET

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |

||Volume 13, Issue 5, May 2024||

DOI:10.15680/IJIRSET.2024.1305290

REFERENCES

- [1] A. H. Compton, X-rays as a branch of optics, Nobel lecture, (1927) 174 190.
- [2] A. H. Compton, The total reflection of X-rays, Phil. Mag. S. 6. 45 (1923) 1121-1131
- [3] A.H. Compton, X-rays and Electron: An Outline of Recent X-ray Theory, I st Ed., D. Van Nostrand Company, New York, 1926.
- [4] K. P. Singh, Techniques in X-ray astronomy, Resonance (2005) 15-23.
- [5] Paul Gorenstein, Grazing incidence telescopes for x-ray astronomy, Opt. Eng. 51(2012) 011010: 1-14.
- [6] A. Vikhlinin et al., Chandra cluster cosmology project iii: cosmological parameter constraints, Astrophys. J. 692 (2009) 1060.
- [7] S. W. Allen et al., Improved constraints on dark energy from Chandra x-ray observations of the largest relaxed galaxy clusters, Mon. Not. R. Astron. Soc. 383, 3 (2008), 879–896.
- [8] A. M. Soderberg, E. Berger, K. L. Page et al., An extremely luminous x-ray outburst at the birth of a supernova, Nature. 453, 7194 (2008) 469–474.
- [9] K. W. Chan, et al., Reflective coating for lightweight X-ray optics, Proc. SPIE 8443, 84433S (2012)
- [10] A.. C. Probs et al., Iridium coatings for space-based x-ray optics, Proc. of SPIE Vol. 10562, 105621E 1-9.
- [11] A. A. Mills, R. Hall, The production of a plane surface: As illustrated by specula from some early Newtonian telescopes, Notes Rec. Roy. Soc. London. 37 (1983) 147-166.
- [12] D. Tolansky, W. K. Donaldson, The reflectivity of speculum metal. J. Sci. Instrum. 24 (1947) 248 249.
- [13] William F Collins, The mirror- black and quicksilver patinas of certain Chinese bronzes. J. R. Anthropol. Inst. G. 64 (1934) 69-79.
- [14] A. A. Mills, P. J. Turvey, Newton's telescope, An examination of the reflecting telescope attributed to Sir Isaac Newton in the possession of the Royal Society. Notes Rec. R. Soc. London. 33 (1979) 133-155.
- [15] John Strong, The Johns Hopkins University, J. Opt. Soc. Am. 50 (1960) 1148-1152.
- [16] A.V. Crewe, M. Isaacson, D. Johnson, A high-resolution electron microscopy for use in transmission scanning electron microscopy, Rev. Sci. Instrum. 42 (1971) 411- 420.
- [17] Akira Ito et al., Cu- Sn alloy metallization of polymer through reduction diffusion method using ionic liquid bath at medium- low temperature, ECS transactions.16 ((2009) 677- 679.
- [18] Jianguo Ren et al., Nanometer copper-tin alloy anode materials for lithium-ion batteries, Electrochimica. Acta. 52 (2007) 2447- 2452.
- [19] https://imagine.gsfc.nasa.gov/science/toolbox/xray_telescope.html
- [20] https://universe.gsfc.nasa.gov/xrays/MirrorLab/xoptics.html.
- [21] David Attwood, Soft X-rays and Extreme Ultraviolet Radiations; Principles and Applications, Ist Ed., Cambridge University Press, New York, 1999.
- [22] A. H. Compton, S. K. Allison, X-rays in Theory and Experiment, second ed., D. Van Nostrand Company, Inc., New York, 1935.
- [23] R. Klockenkämper, Total-Reflection X-Ray Fluorescence Analysis, II nd ed., John Wiley & Sons, Inc., New York 2015.
- [24] Krassimir Stoev, Kenji Sakurai, Recent Theoretical Models in Grazing Incidence X-ray Reflectometry, The Rigaku Journal, 14, 2 (1997) 22- 37.
- [25] Yoshikazu Fujii, Recent Developments in the X-ray Reflectivity Analysis, J.AJPA. 4, 2 (2016) 27-49
- [26] S. Srinivasan, I. Glover, Skilled mirror craft of intermetallic delta high-tin bronze (Cu_31 Sn_8, 32.6 % tin) from Aranmula, Kerala, Current Sc. 93 (2007) 35-40.
- [27] E.A. Nazimudeen, T. E. Girih, Sunila Abraham, On the nature of thin films of speculum metal, Mtcomm. 16 (2018) 314- 319
- [28] T. Nagee et al., Thermographical analysis of continuing tradition of mirror casting in Kerala, ISIJ International. 54 (2014) 1172 – 1176.
- [29] http://henke.lbl.gov/optical_constants/.
- [30] http://x-server.gmca.aps.anl.gov.
- [31] A. H. Compton, X-rays as a branch of optics, Nobel lecture, (1927) 174 190.
- [32] A.H. Compton, R.L. Doan, X-ray spectra from a ruled reflection grating. Proc. N.A.S. 11 (1925) 596-601.
- [34] N. V. Alov, Total Reflection X-ray Fluorescence Analysis: Physical Foundations and Analytical Application (A Review), Inorganic Materials, 47, 14 (2011) 1487–1499.



|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Refereed Journal |

||Volume 13, Issue 5, May 2024||

[DOI:10.15680/IJIRSET.2024.1305290]

[35] B. L. Henke, E. M. Gullikson, J. C. Davis, X-ray interactions: Photo absorption, scattering, transmission and reflection at E = 50 – 30000 eV, Z = 1-92, Atom. Data Nucl. Data Tables. 54 (1993) 181-342.

INTERNATIONAL Standard Serial Number India







INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com