

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 4, Special Issue 6, May 2015

Vehicular Tracking and Reporting by Vehicle to Vehicle (V2V) Communication

A.B.Yuvaraj¹, M.Jaganathan²

P.G. Student, Department of CSE, K.S.R. Institute for Engineering and Technology, K.S.R. Kalvinagar, Tamilnadu,

India¹

Assistant Professor, Department of CSE, K.S.R. Institute for Engineering and Technology, K.S.R. Kalvinagar,

Tamilnadu, India²

ABSTRACT: Vehicular networks is attracted a lot of attention recently. The application of vehicular networks is to use video cameras embedded in vehicles to support video surveillance, which we call "surveillance on-the-road". Monitoring and Tracking suspicious vehicles (such as stolen cars) on the road through license plate recognition (LPR). Vehicles can work cooperatively through vehicle-to-vehicle (V2V) communications to achieve this goal. With a tracking and reporting modules, our solution does not rely on infrastructure networks. The tracking module allows handoff of a tracking job to neighboring vehicles as necessary and report of suspicious vehicles to nearby police cars. In the framework can be applied to the developing WAVE/DSRC (Wireless Access in Vehicular Environments/Dedicated Short Range Communications) standards.

KEYWORDS: V2V, LPR, WAVE/DSRC.

I. INTRODUCTION

Video surveillance is the advances of video technologies and embedded computing and communications technologies. Vehicular surveillance applications such as vehicle security[1], brake warning[3], and urban monitoring [8]. Traditional surveillance systems only rely on fixed stations on the roads to monitor road conditions. Embedded on vehicles to help the surveillance job, which we call "surveillance on-the-road". In additionto fixed video cameras, millions of cameras installed onvehicles may help the surveillance job. Mostvehicles nowadays have rear cameras to assist backwarddriving. With vehicular cameras, deeper and richer roadconditions may be tracked. The communication issues to support such "on-the-road" Surveillance scenarios throughvehicle-to-vehicle (V2V) communications.

Tracking and Reporting suspicious vehicles rely on roadside infrastructures [6] toachieve this goal. The proposed work is an infrastructure-less framework for tracking and monitoring suspicious vehicles by vehicles on theroads. Our solution consists of a tracking module and reporting modules. The tracking module allows a vehicle to keep tracking an identified suspicious vehicle and handoff [5]it's tracking job to neighboring vehicles as necessary. It allows a tracking vehicle toreport the intersection passed by the suspicious vehicle tonearby police cars even if it has no digital map informationat hand.

The reporting module helps find the nearest police carat low message cost without relying on costly roadside infrastructures, such as roadside units (RSUs) and wirelesslocal area network access points (WLAN APs) [9]. Itonly relies on V2V communications, that if both thetracking vehicle and the nearest police car have 3G/3.5Gradio interfaces, the discovery for suspicious vehiclesmight be directly reported to the nearest police car via3G/3.5G communications.

Vehicle to Vehicle (V2V) communicationswill be used to report the discovery as proposed in this work. On the other hand, propose to enhance LPR (licenseplate recognition) capability to a vehicular camera, so asuspicious license number which is to be tracked can be be compared locally in a vehicle. The work should be applicable to the developing WAVE/DSRC (Wireless Access in VehicularEnvironments/Dedicated Short Range Communications) [4] standards.



International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 4, Special Issue 6, May 2015

II. SYSTEM MODEL

Vehicular surveillance networksvia V2V communications. Each vehicle is equipped with aGPS receiver and some video cameras. These video cameras can help recognize thelicense plates of the vehicles immediately in front/rear ofit. With license plate recognition (LPR) techniques, transmittinglicense plate images is not always necessary. Foridentifying suspicious vehicles, the police departmentmay publish a list of license plate numbers to be trackedin a particular region. Then vehicles in that region can tryto recognize these plate numbers and keep those videoclips when there is a match.



Vehicles can immediately communicate with each otherupon encountering on the road without having to join aBSS. Vehicles transmit periodical beacons to exchange ID positions with neighboring vehicles indicated in broadcasting messages to limit their ranges.

- 1. **Tracking handoff**: How do we handoff the tracking job to neighboring vehicles as v_s (Suspicious vehicle) changes its lane or direction so that v_s can be continuous tracked on the road?
- 2. Intersection detection: How do we detect an intersection without digital maps at hand so that each intersection passed by v_s can be reported to v_p (Police vehicle) for maintaining the up-to-date location of v_s ?
- 3. **Rebroadcast decision**: How do we report the location of v_s to nearby v_p such that the number of rebroadcasts of m_r can be minimized?
- 4. Message guiding: How do we guide the propagation of m_r to the nearest v_p without flooding the network so that the message overhead for reporting can be reduced?

III.TRACKING AND REPORTING PROTOCOLS

It is an infrastructure-less frameworkfor the vehicle tracking and reporting problem, which consists of a tracking module and a reporting module. First, to keep tracking an identified v_s , and propose a tracking handoff scheme and an



International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 4, Special Issue 6, May 2015

intersection detection scheme. Second, to efficiently deliver reporting messages about v_s to the nearest v_p , and finally rebroadcast decision, an intersection-guiding search, and amemory-based backoff schemes.

IV. EXPERIMENTAL RESULT



Fig 2: Simulation Result

Estinet8.1 is used for the simulation result, here A, C, D is the neighbor vehicle, B is the suspicious vehicle and finally the location of the suspicious vehicle is reported to the police vehicle (v_p) .

V. CONCLUSION

"Surveillance On-the-Road" that integrates surveillance technologies with WAVE/DSRC communications to support vehicle tracking and reporting applications. Vehicles can work cooperatively through V2V communications to achieve this goal. The tracking module can handoff a tracking job to neighboring vehicles as necessary and report suspicious vehicles to nearby police cars. The reporting module can help guide message flows to avoid flooding the network. In the paper, mainly focuson how to design the vehicular tracking and reporting by V2V communications.

REFERENCES

- Lien-Wu Chen, Yu-Chee Tseng, Kun-ZeSyue (2014) 'Surveillance on-the-road: Vehicular tracking and reporting by V2V communications', Computer Networks 67 (2014) 154–163
- Rongxing Lu, Xiaodong Lin and Haojin Zhu(2009) 'SPARK: A New VANET-based Smart Parking Scheme for Large Parking Lots', 978-1-4244-3513-5/09/\$25.00
 ©2009 IEEE
- [3] Thammakaroon, P. Tangamchit, P. (2008) 'Adaptive Brake Warning System for Automobiles', 978-1-4244-2858-8/08/\$25.00 ©2008 IEEE
- [4] Daniel Jiang and Luca Delgrossi (2008) 'Towards an International Standard for Wireless Access in Vehicular Environments', 978-1-4244-1645-5/08/\$25.00 ©2008 IEEE
 [5] O. Traver, N. Wikita needed. E. Dri, D. Madalia, V. Sadakas, Production in VANET, in: Proc. Makita Networks, 678-1-4244-1645-5/08/\$25.00
- [5] O. Tonguz, N. Wisitpongphan, F. Bai, P. Mudalige, V. Sadekar, Broadcasting in VANET, in: Proc. Mobile Networking for Vehicular Environments, May 2007, pp. 7–12.
- [6] L.-W. Chen, Y.-H. Peng, Y.-C. Tseng, An infrastructure-less framework for preventing rear-end collisions by vehicular sensor networks, IEEE Commun. Lett. 15 (3) (2011) 358–360.
- [7] L.-W. Chen, K.-Z. Syue, Y.-C. Tseng, VS3: a vehicular surveillance and sensing system for security applications, in: IEEE International Conference on Mobile Adhoc and Sensor Systems (MASS), October 2009.
- [8] U. Lee, E. Magistretti, M. Gerla, P. Bellavista, A. Corradi, Dissemination and harvesting of urban data using vehicular sensing platforms, IEEE Trans. Vehicular Technol. 58 (2) (2009) 882–901.
- M. Caceres, F. Sottile, M.A. Spirito, WLAN-based real time vehicle locating system, in: IEEE Vehicular Technology Conference (VTCSpring), April 2009, pp. 1– 5.
- [10] O. Tonguz, N. Wisitpongphan, F. Bai, P. Mudalige, V. Sadekar, Broadcasting in VANET, in: Proc. Mobile Networking for Vehicular Environments, May 2007, pp. 7–12.