

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016

Study of Annealing Temperature on Prepared Iron oxide Nanoparticles by Sol-Gel Method

Rusul Adnan Al-Wardy^{1*}, Hanan A.Thjeel AL-Ogaili¹, Sabah Ibrahim Abbas¹

Department of Physics, College of Science, University of Wassit, Wassit, Iraq¹

ABSTRACT: Iron Oxide nanoparticles are synthesized by Sol-gel route from mixed two source materials [0.1] M ferric nitrate (Fe(NO₃)₃.9H₂O) and[0.2]M monohydrated citric acid (C₆H₈O₇) then annealed at different annealing temperature (150,300,500and 700) C. The structural, morphological and the optical properties are studied by XRD, SPM and UV-visible spectrum. It can be noticed from results XRD test that iron oxide has the multiple phases when prepared in this method , where it's found that the crystal structure of sample iron oxide nanoparticle at 150 °C is amorphous while the other samples are polycrystalline cubic (magnetite) , hexagonal and Rhombohedral (hematite). The average size of nanoparticles in the range of (11.2 , 29.48 and 46.2)nm at 300,500 and 700°C respectively , increased annealing temperature of the gel led to increase the average size . The α -Fe₂O₃ nanoparticles strongly depend on the precursors composition, the pH solution and heated treatment . SPM results show that the morphology of samples at 500 ,700 more homogeneous .it can be found from UV-visible analysis that energy gap about 2.6 eV at 700°C , the band gap increasing with increasing temperature , also the absorption spectrum increasing at 700 C more than other samples while low at 150 and 300 , the spectrum near to visible region around 400 nm .

KEYWORDS: a-Fe ₂O₃ Nanoparticles, Iron Oxide, Structural Properties, Sol-Gel

I. INTRODUCTION

In the last few years, Metal oxide nanoparticles (NPs) became extensively investigated for fascinating functional materials, the nanoparticles of iron oxides is one of these transition metal oxides that evoked remarkable interest in all aspects as theoretical fields or the various potential applications in nanodevices . [1][2]The oxides of iron (Ferrous and ferric) is existed in seven crystalline phases, the most famous structures are: Magnetite (Fe_3O_4), the ferrimagnetic \mathbf{F} -Fe₂O₃ (Maghemite)and antiferromagnetic α -Fe₂O₃ (Hematite) where hematite crystallizes in the trigonal system ; while other phases are β - and ϵ -Fe2O3 are the less commonly that belong to their good properties such as optical, electrical and magnetic, [3,4] that extensively investigated by researchers in different specializations like chemists, Physicists and engineers. Iron oxides are used efficaciously in many Applications and in various fields ; the nanoparticles of magnetite that can be used in cancer diagnosis and therapy whereas maghemite is widely used in magnetic recording systems and catalysis [5,6], while hematite is used as an anticorrosive agent, catalytic reactions, red pigments [7] printing ink[8], nano fillers [9] gas sensors [10,11] and dye sensitized solar cells[12] magnetic resonance imaging (MRI), also advantages of Fe₂O₃ nanoparticles have narrow band gap (about 2.2 eV), n-type semiconducting material, abundant, cheap non-toxic, thermally stable.[13] There several techniques are used to synthesis α -Fe₂O₃ nanoparticles such micro-emulsion technique [14], vapor-solid growth technique [15] forced hydrolysis [16]. In this work we use the sol-gel process to prepare iron oxides nanoparticles from ferric nitrate and mono hydrated citric acid, the structural and morphological and optical properties are studied by XRD, AFM and UV-Visible spectrum where it takes better the conditions to prepare the nanoparticles of iron oxides which depended on the dilution solutions, concentrations of the citric acid solutions and time of the annealing temperature after synthesis.



(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016

II. EXPERIMENTAL WORK

The nanoparticles of iron oxides (hematite and magnetite) is prepared via the sol gel route and to identify the parameters that affect on the nanosize of particles . The preparation for these nanosize particles by a slightly modified method for greater simplicity. The mixture consist of two solutions, the first one ,100 ml (0.1M) of iron nitrate Fe $(NO_3)_3$. $9H_2O$ (4.039g) was used as a precursor solution, and was gelated by using 100 ml of mono hydrated citric acid(C ₆H ₈ O₇) solution (0.2M)of (3.842g)as ligand molecules, and singly distilled water as the solvent. The iron solution that gives the yellow solution added to the citric acid solution drop by drop with vigorous stirring that puts into magnetic stirrer at room temperature for 4 hours. Then this solution reached to a temperature of 80 °C, while maintaining vigorous stirring until the gel was formed and the contained water was evaporated, after that the gel put in autoclave in order to annealing at temperatures ranging from (150, 300, 500 and 700)[®]C for 1 hour then the sample mills and collects to purpose of study its properties as shown in Figure (1), the samples appears different colors after the annealing as shown in Figure (2) depending on the annealing temperature ,also to study optical properties used HCl as solvent for samples. We used an X-ray diffractometer is recorded by SHIMADZU XRD-6000 (CuKα radiation λ =0.154nm) in 20 range from (20° to 80°) for the verification of the crystal structure and for the average size of the particles for hematite. The surface studies or Microscope Atomic Force Microscopy studies for samples is investigated , the morphology of the hematite nanoparticles produced is studied using Scanning Probe Microscope (type AA3000), supplied by Angstrom Advanced Inc. to determine the nanoparticles dimensions range of the prepared layer form the samples and their statistical distribution. UV-visible spectrum is studied by SP- 3000NANO spectra made in Japan In rage 200-1100



Figure. 1. Schematic of procedure to prepare iron oxide nanoparticles.



(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016



Figure. 2. The color Samples of the iron oxide nanoparticles at different annealing temperature solvent in HCl.

III. RESULTS AND DISCUSSION

> STRUCTURE PROPERTIES

To study XRD patterns for all samples of iron oxides nanoparticles that prepared by sol-gel route at different annealing temperature (150,300,500and 700) C, in Figure (3 - a, b, c and d) It can be observed the multiple phases of iron oxide crystals when annealed at variation temperature . It can be noticed that no diffraction peaks in sample of the iron oxide at 150° c , as shown in figure (3– a) that is behaves as amorphous structure at low temperature due to the short -range order, while in Figure (3-b) it can be found that four peaks for samples annealing at 300°C, it appears a cubic structure(magnetite type), the intensity strongest peak correspond to reflection plane (311) at $2\theta=35.83^{\circ}$, so the other orientations are (220),(440)and (511) at 30.61°, 63,06° and 57.08° (JCPDS card No. 01-084-0307 where iron oxide in this temperature behaves transfer from amorphous to cubic crystal as magnetite (Fe_3O_4) depended on annealing temperature, long - range order and reaction conditions, in the high temperature at 500 and 700 $^{\circ}$ C the asprepared samples of iron oxide nanoparticles in Figure. (3- c, d) the results showed that α -Fe2O3 nanoparticles at 500 °C have rhombohedral crystal system with a lattice constant of a = 5.0258 °A , b = 5.0248 °A, c = 13.7489 °A (space group=R-3c), these results in good agreement with [4][17]. also, all diffractions peaks orientations in the (012), (104), (110), (113), (024), (116), (018) and (214) directions are in excellent agreement with JCPDS card number 86-0550. The strongest peak appears in (104) orientation at 500 and 700 °C and the absence of any other peaks suggests that α -Fe2O3 nanoparticles give the high purity and the impurities disappeared . X-Ray diffraction data shows that α -Fe₂O₃nanoparticles with a hematite-type structure are crystallized as polycrystalline in hexagonal crystal system with rhombohedral lattice structure at (500 and 700) \mathbb{C} [13]. It can be obviously the clear broadening in the peaks compare with bulk, the broaden affects with the crystallite size and the internal strains.[8] proved that the samples are formed the Nanocrystallines of iron oxide during preparation, also it can be noticed that the structure crystalline of the sample at 700 ℃ enhancement more than the other samples till more than 500 ℃, that gives proof that the increasing annealing temperature enhances the nanostructure of samples , so it can be found that the crystalline size (D) for all samples from results of XRD by applying Scherre's equation(1) as written :[18]

D = 0.9 $\lambda \beta \cos \theta$ (1)

Where D is the average crystallite size, λ (0.154nm) is wave length of X-rays , β is the full width at half maximum(FWHM), and θ is the Bragg diffraction angle, all samples calculated D at the strongest peak .It is observed that the average crystallite size increased from 11nmto 46 nm as the processing temperature increased from 150–700°C, from above eq.(1) found that average crystallite size (D) of the nanoparticles iron oxide in range of (11.2 - 46.2)nm are listed in table (1) that appears the relation between different annealing temperature, structure, color and average of crystal size (D) of four samples in this work.



(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016

Table (1)The relation between the structure, the color and average of crystal size of iron oxide nanoparticle at different annealing temperature .





> SCANNING PROBE MICROSCOPY

Scanning-Force Microscopy (SFM) is one type of scanning probe microscopy (SPM) a very-highresolution , the resolution is demonstrated about (0.1 - 1 nm), its more than 1000 times better than the optical diffraction limit , all the samples of iron oxide nanoparticle is scanned by the SPM in Figure (4 a, b, c and d) shows that results of scanning images of the as prepared samples at variation temperature , so it can be found that the average diameter sizes as shown in table (2) about (86.07-92.65)nm and the average height around between (2-5.5)nm at different annealing temperature respectively , where the size particles of iron oxide depended on the concentrations of the (citric acid) during the preparation also it can be appeared that the grain size in SPM are greater than XRD measurements due to the grain size consist of the crystals group (many small crystal), the SPM is scanned at top surfaces of grains for samples , while the diffraction in XRD test gives miller indices or (crystal planes) of crystals.



(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016



Figure (4) AFM of the iron oxide nanoparticles at different annealing temperature a - at 150 °C , b- at 300 °C c - 500 °C , d-at 700 °C



(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016

Table (2) Average diameter size of iron oxide nanoparticles at different temperature.

The Annealing Temperature (C)	Height of crystal (nm)	Average diameter size (nm)
150	2.4	86.07
300	2	92.45
500	2.9	87.75
700	5.5	92.65

From SPM it is observed that the samples at (500 and 700)°C more homogenies and uniform especially at 700 this proved that at high annealing temperature the clearly improved to properties samples and more roughness from other sample. in the other hand the grains stable on the greatest area of the top surface, so the tip is the sensitive part of SPM moving vertically on surface of sample therefore the size represents the grain size that has the greatest area, while in XRD that rays incident oblique on sample to be on the small face of the grain.

> ABSORPTION SPECTRUM

The absorption spectra of iron oxide nanoparticles at variation temperature illustrates in figure (5) electromagnetic wave incidents on substance and the excited electrons transits from the valence band .the (VB) to the conduction band(CB) where the transitions $n \rightarrow \sigma^*$, $n \rightarrow \pi$ and $n \rightarrow \pi^*$ are the possible electronic transitions between 350-950 nm .The optical absorbance of nanoparticles was investigated using Sp-3000nano optima (UV-Vis spectrophotometer) in the wavelength region of 200 to 1100 nm at room temperature as shown in Figure.5. shows the high absorption at visible region , the peak absorbance at around 400nm, generally the edges bands of absorption spectra is located at between (400-500) nm 486nm at 500°C 476nm at 700°C and 510nm 516nm and corresponding for the optical energies gaps of all samples (150,300,500 and 700)°C which recorded about(2.4, 2.43, 2.55 and 2.6) eV respectively, it can be noticed that the increasing of energy gap of α -Fe₂O₃ nanoparticles compared with bulk , these results similar to another optical absorption spectrum registered by [13], the increasing of energies gaps gradually with increasing temperature also because the strong quantum confinement effect of the reduction particle size that due to the shift in the absorption spectrum of nanoparticles where its sizes become equal or smaller than Bohr radius of exciton [19], The shift to the visible region illustrates that there increasing in the optical band gans of all comple







(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016

with applying the Tauc equation (2) to evaluate the optical energies gaps for these samples [20]as following :

Where, hv is photon energy (eV),C is constant, α is absorption coefficient(cm⁻¹), the average band gap energy is (Eg)and n is depending on the transition type if allowed or non- allowed . the Figure .6 shows the Tauc plot between the linear extrapolation of $(\alpha h\nu)^2$ versus to photon energy(hv) of the iron oxide nanoparticles for all samples where the direct allowed transition of the nanoparticles iron oxide . The average energies gaps have found from the Tauc plot around (2.4,2.43, 2.55and2.6) eV at different annealing temperature respectively which are larger than the energy gaps of bulk for iron oxide the reason belong to the strong quantum confinement effect and re-arrangement the electronic states near to the Fermi level [21,22].



Figure . 6. the graph shows the relation between the photon energy $(h\nu)$ and $(ah\nu)^2$ for the nanoparticle of iron oxide at different temperature.

VI. CONCLUSION

The iron oxide nanoparticles is prepared successfully via sol- gel route, this method has several advantages as low cost, simple equipment and easy operation . it can be observed that there multiple phases of iron oxide nanoparticles as prepared in this method from analyses of XRD patterns and phase transfer to α -fe2O3 nanoparticles at high annealing at(500,700 °C) with polycrystalline is hexagonal structure ,so all properties such as structural ,morphological and optical are improved at 500 and 700°C , also obtains the high absorption in visible region at same temperature and low at 150 , the optical energy gap of nanoparticles is 2.6 at 700°C increasing with respect to the bulk of iron oxide while the other energies gaps of other samples are smaller than annealing at700°C .

ACKNOWLEDGMENT: We would like to grateful to chemistry department in College Science /Wassit University to help us to achieve this work especially Mr. Gassan , Mr, Ali and the head department Dr. Abbas.

REFERENCES



(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 4, April 2016

[2]Nguyen Duc Cuong, Dinh Quang Khieu, Tran Thai Hoa, Duong Tuan Quang, Pham Hung Viet, Tran Dai Lam, Nguyen Duc Hoa and Nguyen Van Hieu, (2015) "Facile synthesis of α-Fe₂O₃ nanoparticles for high-performance CO gas sensor", Materials Research Bulletin, Vol.68, pp302-307

[3]Hongtao Cui , Yan Liu and Wanzhong Ren (2013)"Structure switch between α -Fe₂O₃, γ -Fe₂O₃ and Fe₃O₄ during the large scale and low temperature sol-gel synthesis of nearly monodispersed iron oxide nanoparticles", Advanced Powder Technology, Vol.24, pp 93-97

[4]Marin Tadi, Dragana Markovi', Vojislav Spasojevi', Vladan Kusigerski, Maja Remškar, Janez Pirnat, Zvonko Jagličci' "Synthesis and magnetic properties of concentrated a-Fe₂O₃ nanoparticles in a silica matrix", Journal of Alloys and Compounds ,441 (2007) 291–296.

[5] A.M. Testa, S. Foglia, L. Suber, D. Fiorani, L. Casas, R. Roig, E. Molins, J.M. Gren`eche, J. Tejada, (2001) "Unconventional magnetic behavior of iron-oxide nanoparticles in polymeric matrices issue", Journal Of Applied Physics, issue 3, vol.90, pp: 1534 - 1539.

[6]F. Hong, B.L. Yang, L.H. Schwartz, H.H. Kung, (1984) "Crystallite size effect in the selective oxidation of butene to butadiene on iron oxide. 1. Moessbauer, x-ray and magnetization characterization of the catalysts" Journal of Physics and Chemistry , vol 88, pp.2525-2530.

[7] F. Bondioli, A.M. Ferrari, C. Leonelli and T. Manfredini, (1998) "Synthesis of Fe₂O₃/Silica red inorganic inclusion pigments for chemical application, Mater. Res. Bull, vol.33 ,pp: 723-729.

[8]Maryam Mohammadikish ,(2014)"Hydrothermal synthesis, characterization and optical properties of ellipsoid shape α -Fe₂O₃ nanocrystals" ,Ceramics International ,Vol.40, Ipp: 1351-1358.

[9]Ali Khoshakhlagh, Ali Nazari and Gholamreza Khalaj (2012)"Effects of Fe₂O₃Nanoparticles on Water Permeability and Strength Assessments of High StrengthSelf-Compacting Concrete" Journal of Mater. Science . Technology, vol.28, pp:73-82.

[10] J. Z. Iiang, R. Lin, W. Lin, K. Nielsen, S. Morup, K. Dam Johansen and R. Clasen , (1997) "Gas-Sensitive Properties and Structure of Nanostructured (a-Fe₂O₃)SnO₂)x Materials Prepared by Mechanical Alloying," Journal of Physics D: Applied Physics, Vol. 30, No. 10, pp. 1459-1467. http://dx.doi:10.1088/0022-3727/30/10/012.

[11] X. Chi, C. Liu, L. Liu, S. Li, H. Li, X. Zhang, X. Bo, H. Shan, (2014)" Enhanced formal dehyde-sensing properties of mixed

Fe2O3-In2O3 nanotubes "., Materials Science in Semiconductor Processing, vol.18, pp:160-164. http://dx.doi.org/10.1016/j.mssp.2013.11.016

[12] S.M. Reda, (2010) "Synthesis of ZnO and Fe₂O₃ nanoparticles by sol-gel method and their application in dye-sensitized solar cells", Materials Science in Semiconductor Processing, vol.13, pp:417-425.

[13]K. Raja, M. Mary Jaculine, M. Josec, Sunil Vermad, A.A.M. Prince, K. Ilangovan, K. Sethusankara, S. Jerome Das (2015) "Sol-gel synthesis and characterization of α -Fe₂O₃ nanoparticles" ,Superlattices and Microstructures, Vol. 86 PP: 306-312. http://dx.doi:10.1016/j.ceramint.2013.07.016

[14] V. Chhabra, P. Ayyub, S. Chattonpadhyay, A.N. Maitra, (1996)"Preparation of acicular γ-Fe₂O₃ particles from a micro emulsion-mediated reaction", Materials Letters, vol .26, pp:21-26 <u>http://dx.doi:10.1016/0167-577X(95)00200-6</u> [15] Y.Y. Fu, R.M. Wang, J. Xu, J. Chen, Y. Yan, A.V. Narlikar, H. Zhang,(2003)" Synthesis of large arrays of aligned α-Fe₂O₃ nanowires"

Chemical Physics Letters ,379, pp:373-379. http://dx.doi:10.1016/j.cplett.2003.08.061

[16] T. Sugimoto, K. Sakata, and A. Muramatsu,(1993)" Formation Mechanism of Monodisperse Pseudocubic α-Fe2O3 Particles from Condensed Ferric Hydroxide Gel", Journal of Colloid and Interface Science, vol.159, pp: 372-382. <u>http://dx.doi:10.1006/jcis.1993.1336</u>

[17] Bappi Paul, Bishal Bhuyan, Debraj Dhar Purkayastha, Siddhartha Sankar Dhar(2015)" Facile synthesis of α-Fe₂O₃ nanoparticles and their catalytic activity in oxidation of benzyl alcohols with periodic acid " Catalysis Communications, Vol. 69, Pages 48–54. [18] C. S. Pathak, P. K. Pathak, P.Kumar, M. K. Mandal (2012)"Characterization and Optical Properties Of Ni⁺² Doped ZnS Nanoparticles".

Ovonic Research , Vol. 8, 15-20.

[19] S. Biswas, and S. Kar (2008) Fabrication of ZnS nanoparticles and Nanorods with Cubic and Hexagonal Crystal Structures: A Simple Solvothermal Approach. Nanotechnology, Vol 19,045710. http://dx.doi.org/10.1088/0957-4484/19/04/045710

[20] Baset, S., Akbri, H., Zeynali, H. and Shafie, M. (2011)"Size Measurement of Metal and Semiconductor Nanoparticles Via UV-Vis Absorption Spectra ". Dig. J. Nanomater. Bios., Vol. 6, PP: 709-716

[21] B. Gilbert, C. Frandsen, E.R. Maxey and D.M. Sherman (2009) "Band-gap measurements of bulk and nanoscale hematite by soft x-ray spectroscopy", Physical Review B, vol.79, pp:035108. <u>http://dx.doi.org/10.1103/PhysRevB.79.035108</u>. [22]X.G. Wen, S.H. Wang, Y. Ding, Z.L. Wang, S.H. Yang, (2005)"Controlled growth of large-area, uniform, vertically aligned arrays of α-

Fe₂O₃nanobelts and nanowires. Journal of Physic Chemistry. B Vol. 109, pp. 215-220. http://dx.doi10.1016/j.tsf.2014.05.016