

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

Mechanism of Secure and Distributed Data Discovery and Dissemination in Wireless Sensor Networks

Indermohan Singh Major¹, Dr. R. S. Kawitkar²

PG Student, Department of ETC, Sinhgad College of Engineering, Vadgaon (BK), Pune, Savitribai Phule Pune University, Pune India.

Prof. Department of ETC, Sinhgad College of Engineering, Vadgaon (BK), Pune, Savitribai Phule Pune University, Pune India

ABSTRACT: Wireless Sensor Network (WSN) are in a general sense orbited structures or a gathering of sensor focuses which aggregate data which are utilized to eviscerate physical or regular conditions. WSNs are consistently setup in remote and undermining zones and work in amazing conditions. Employments of WSN merge living space checking, mechanical applications, fight zone perception, awesome homes and so on. An endless section of them require general upgrading of programming in sensor focus focuses through the remote channel for practical association and working. So it is fundamental to spread information through the remote medium after the focuses are sent. This is known as information scattering or structure repeating. Information scattering custom must be fast, secure, reliable and centrality able. To satisfy these we can make use of system coding procedure which decreases the measure of retransmissions as an aftereffect of any bundle drops. Regardless, coordinate coding fabricates the shot of different sorts of structure assaults. In like way to avoid spreading of malevolent code in the structure, every sensor focus direct needs toward avow its got code before bringing on it further. So here a novel spread custom is presented in light of direct cryptographic systems which impedes pollution and DoS assaults and then accomplishes speed utilizing the procedure of structure coding.

KEYWORDS: Dissemination, network coding, pollution attack, reprogramming, security, wireless sensor network.

I. INTRODUCTION

Wireless Sensor Network (WSN) is one of the important pivotal turning points in the field of correspondence. These planned collections of focuses make us a stage nearer to increasing crucial data about the physical world. WSN are utilized discernibly as a piece of different applications like remote control and checking, change security frameworks, regular watching, social insurance association, fiasco association, observation operations, awesome homes, living space viewing, indoor sensor systems, seismic seeing of structures and so forth [1]. In programming planning and correspondence remote sensor structures strengthen bundle of examination today. A WSN is made of sensor focus focuses utilized for checking and examination purposes as appeared in Fig 1. These sensor focus focuses pass the data that they gather to a prime district called a base station. In various frameworks, a WSN relates with a LAN or WAN through a door like medium. The area is really an increase between the WSN and the unmistakable structures [2]. This licenses information to be secured by contraptions and which can be taken up for get prepared later. Every sensor focus point or bit has several ranges: a circuit for interfacing with other sensor focus focuses, a downsized scale controller, a radio handset, and a battery for force supply. The topology utilized can be either a star, ring, structure or multi-jump remote cross range system. WSN is utilized basically as a bit of remote and incapacitating circumstances for data gathering. Thusly it is a critical test to pass on disreputable sensor focuses. They should be made deliberately by considering all the different objectives of the earth in thought.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016




Fig -1: An example wireless sensor network

Remote sensor frameworks must be worked for long haul of time and generally don't get any human association or mediation amidst [3]. Propelling conditions and circumstances can in like manner; cause changes in application highlights, which thus provoke the need to change the framework conduct by introducing new code or programming. In any case, the remote method for WSN is an injury here. It will require the expansion of new code updates over the remote medium i.e. over the air as manual upgrading of such frameworks won't be possible. This methodology is known as spread or framework rethinking. Regardless, scrambling obtains an impressive measure of challenges [3]. One essential test is authentic and complete dispersal of information to all sensor center points in the framework. This is troublesome since the amount of center points in the framework can be tremendous and nature is continually fast, henceforth the fundamental topology keeps advancing dependably. Besides the information to be scattered may be made at a single center, for instance, the prime source i.e. the base station, or at the sensor centers themselves. Thirdly data must be scattered safely or else adversaries can track out essential data. Furthermore there is a likelihood of attackers sending sham data into the framework which ought not be gotten by the sensor centers as they can achieve different ambushes like sullyng strikes, denial of organization ambushes and so forth. So dispersal of code or program data in remote sensor frameworks is a zone to be worked in significantly and new techniques ought to be familiar with finish tradeoffs amidst essentialness and rate in spread. The purpose of this work is to develop a novel secure and speedy data dispersal tradition for use in remote sensor frameworks. This work concentrates on adding to a dispersal tradition for disseminating of little data.

Straight framework coding is a technique used to finish pace and imperativeness adequacy in the midst of dissipating [4]. It is a strategy that combines bundles in the framework; extending the throughput, reducing essentialness usage, and diminishing the amount of messages transmitted. In ordinary structures dropped packs are recovered using retransmissions. Regardless, in framework coding we can join groups using exploratory operations and after that scatter so that recovery of lost bundles can be expert without retransmission. In any case, framework coding nearby its essentialness efficiency great circumstances gets an impressive measure of cerebral agonies. It is significantly disposed to attacks like pollution, foreswearing of-organization ambushes and various others. So to deal with these proposed system uses clear however capable cryptographic methodology for data dissipating. This guarantees we can fulfill direct yet secure data spread in remote sensor frameworks. Our work is sorted out as takes after. In any case we focus on the need of data spread in remote sensor frameworks and some of its related works. Next the diagram and use which concentrates on the spread of little values and variables is cleared up. By then we consider the execution of the new tradition through wide propagation using TinyOS finally have the conclusion and references.

II. RELATED WORKS

Information dispersal in remote sensor systems is a basic and crucial undertaking. It depends on the idea of conventional correspondence framework, where we have a sender and beneficiary. The situation is fundamentally a

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

sender conveying some data, and beneficiary gathering the data sent, preparing it and sending some data back. While in information scattering, just 50% of this idea is connected. Some data is conveyed and got at the destination; however no answer is given back. The sender conveys data, not to one hub, but rather to numerous as in a television framework. Dispersal is utilized to send code upgrades or program pictures to the sensor hubs intermittently in order to perform reconstructing of the hubs. This over the air demonstration is required since manual upgrading of sensor hubs conveyed in remote situations is alongside outlandish in a large portion of the cases. The principle point of a spread convention in WSN is to guarantee that all the sensor hubs have predictable information with them generally. There are two kinds of dissemination in WSN [5].

1. Code dissemination - to send program images which are generally bulky data. Usually they are divided into fixed sized pages and packets and then disseminated.
2. Data discovery and dissemination - to disseminate small configuration parameters, variables, queries, commands etc in packets.




Fig -2: Dissemination process in WSN

1. Small Value Dissemination

This work focuses on information revelation and spread conventions i.e. dispersal of little values like variables, parameters etc. Figure 2 gives a general thought regarding information spread. Conventional conventions accessible for this incorporate Drip, DIP and DHV. They are all in view of Trickle calculation [6].

Trickle proposed by Tolle et. al [7] is the least difficult of all spread conventions and depends on Trickle calculation and sets up an autonomous stream for every variable in the information. Each time an application needs to transmit a

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

message, another rendition number is created and utilized. This will bring about the convention to reset the Trickle clock and subsequently scatter the new esteem else the stream clock interim is augmented. Plunge (Dissemination Protocol) [8] is information identification and scattering convention proposed by Lin et al. It is a convention in view of the Trickle calculation. It works in two sections: figuring out if there a distinction in information put away at a hub, and after that figuring out which information is distinctive. It depends on the idea of form number and key tuple for every information thing. Plunge figures hashes that cover all form quantities of the information. Hubs that get hashes same as their own realize that they have steady information as for their closest neighbors. In the event that a hub gets a hash that contrasts from its own particular hash, it realizes that a distinction exists in the information. DHV (Difference discovery Horizontal inquiry Vertical pursuit), [9] is a code consistency upkeep convention given by Dang et al. It tries to keep codes on various hubs in a WSN reliable and up and coming. Here likewise information things are spoken to as tuples (key, adaptation). It depends on the perception that if two information things are distinctive, they will just vary in a couple of slightest huge bits (LSB) of their adaptation number as opposed to in every one of their bits. So just those bits should be checked. For this strides took after are recognition and distinguishing proof. There are numerous code spread conventions like Deluge [10] also. They are utilized to disperse substantial code redesigns into the system. For this the code is regularly separated into pages and afterward encourage into bundles. Here we have seen some fundamental information revelation and scattering conventions. They don't support any methods which diminish bundle retransmissions. Additionally none of these conventions give security to the information spread.

2. Network Coding and Data Dissemination

System coding [4] plans to supplant the customary store and forward method utilized as a part of systems; by better directing calculations that will permit middle of the road hubs to change the moving information. System coding has ended up mainstream because of its properties like power and better throughput. It accomplishes quick information scattering as it decreases the quantity of retransmissions that will be required if there are bundle misfortunes. Numerous scattering conventions have been created utilizing the idea of system coding [4] [5].

The upsides of system coding based dispersal conventions are that they accomplish vitality investment funds and correspondence effectiveness, particularly amid expanded parcel misfortune or system thickness. So arrange coding based conventions can be gainful for reconstructing of WSNs. Nonetheless we confront a potential issue in antagonistic situations. A foe may dispatch contamination assaults, in which a malevolent hub sends terrible encoded parcels that comprise of sham information, which prompts inaccurate translating of the first information upon recovery.

Here we utilize twofold system coding i.e. the scientific operation utilized is XOR to consolidate the substance of bundles [4]. Just two bundle system coding is done here. Additionally here we concentrate on dispersal of little values like setup parameters, variables, questions, summons and so forth whose size extent from 2-4 bytes and along these lines is change of the current DRIP convention.

III. ASSUMPTIONS AND THREAT MODEL

1 Assumption

Here expect that the wellspring of the reinventing variables, i.e., the base station, is a safe area. Additionally every sensor hub has a novel recognizable proof number. We expect that while every sensor hub is asset restricted, it has adequate memory to store all the security instruments of the convention.

2 Threat Model

Here expect that the individual sensor-hubs are unprotected. A foe may embed its own aggressor hubs into the system, or it might catch different hubs. The foe can endeavor to dispatch contamination assaults to degenerate the information in the system furthermore to expend the constrained assets on sensor hubs.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

IV. PROPOSED SYSTEM

In this protocol data dissemination is done in a secure and fast way by using the techniques of network coding and cryptography. Network coding reduces the number of retransmissions due to any packet losses happening in the network by combing and sending data. Also data disseminated is always sent as encrypted data. For this nodes first perform node to node authentication and establish session keys. Then the session key is used for encrypted transfer of data. This protocol ensures that the system is free of pollution [13] and Denial-of-Service attacks. The different phases of this protocol include:

1 System Initialization Phase

This phase is done before the WSN is deployed in the application field. In this phase the base station generates a master key K_m and a unique random number R_m and stores them safely in each node. Also a list of all the valid node ids is maintained in each node.

2 Packet Processing Phase

In this phase the actual data dissemination occurs. Before disseminating data a node will generate a real time key using a key generation algorithm. This includes the generation of two unique random numbers $R1_node$ and $R2_node$. Key generation is done using Trivium-Multilinear Modular Hashing (MMH) as the MAC function and SHA1 as hashing function $H(x)$. The steps are:

1. $MAC[i] = R1_node \text{ XOR } K[i]$ (1)
2. $a[i] = node_id + MAC[i]$ (2)
3. $h = MMH(a[i])$ (3)
4. $Key = H(h \text{ XOR } R2_node)$ (4)

Where $K[i]$ is the master key of the MAC function, $node_id$ is the identifier of the corresponding node, XOR is the logical XOR operation. This real time key is broadcast by the node in a packet which will include the $node_id$ and the key. The destination node who receives it will check the $node_id$ with its list of valid nodes and ensure this packet is coming from a valid node. If yes that node will also generate a real time key using the same process as above and send back a reply packet to the sender node which will contain the $node_id$ and the newly generated key. If this packet is also validated, then the two nodes are ready to generate a session key. The key is generated as:

Session key = $K_m \text{ XOR } K_a \text{ XOR } K_b$ (5)

Where K_a and K_b are keys generated at any two nodes A and B. Now this key is used for encrypting the data to be disseminated. The advantage of this scheme is that there is no need of actual exchange of the session key through the network. To encrypt the data we use symmetric encryption techniques preferably Advanced Encryption Standard (AES). So the data packet disseminated from a node will contain the data in encrypted form i.e.

Data = $E(d)_{sk}$, where sk is the session key. (6)

Dissemination in wireless sensor networks works on the basis of Trickle algorithm [2]. It takes on the concept of gossiping. Whenever a new data is to be disseminated the trickle timer is reset to 0 and the data is broadcasted. When a node receives a new data it will store it. But if it receives a data which it already is aware of then it will increase the trickle timer interval and suppresses the duplicate incoming data.

To achieve immediate authentication of data packets a onetime hash of the initially generated random number is also calculated and included in each packet. The steps are:

1. Calculate Hash = $H(R_m)$ (7)
2. Result = $ADD(\text{Hash})$ (8)

Where $H()$ is SHA-1 and $ADD()$ is basic addition operation. The result is included in the packets sent.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

3 Packet Verification Phase

To achieve immediate authentication of the received packet, the destination node will calculate the hash of R_m stored in its memory and compare it with the value in the received packet. If they match, then the received packet is a valid node. Thus it will be acknowledged ACK by the destination. Otherwise a NACK (negative ack) is sent to the sender.

Next we will have to ensure the integrity of the data. For this first the node checks the id in the received packet. If it is a valid node_id, then it will attempt to decrypt the data using the session key already generated and stored. Every node has an original data and combined data buffer. So the node will check whether it is an original data or combined data. If it is an original data it will be stored and disseminated after a trickle timer fire and if it is a combined data, the node will check whether it is possible to extract any other data from this newly received data using network coding. After that the data will be stored or disseminated out.

So likewise all the data disseminated from the original source node will be distributed to all the nodes and a round of dissemination will be completed. This technique thus makes sure that only valid data is sent out and data is been sent out safely.

V. IMPLEMENTATION AND RESULTS

This protocol has been implemented in TinyOS-2.1.2 simulator TOSSIM [7]. We have considered a network topology consisting of 100 nodes and 25 different data variables are disseminated. The packet size in TinyOS [8] is 29bytes. The sensor node considered for simulation here is micaz. Cryptographic support has been achieved using hashing algorithms like SHA-1 which generates a 160 bit hash value, MAC functions like Trivium Multilinear Modular Hashing (MMH), and symmetric encryption algorithms like AES which uses a 128 bit key. The new protocol is found to resist cases of pollution attacks i.e. only valid data packets are received and processed by the intermediate nodes in the network. Also immediate authentication of packets is achieved using the one time hash value generated and stored in the data packets disseminated.

VI. SECURITY AND PERFORMANCE ANALYSIS

First we perform and analyze the security offered by this protocol.

1. Resistance to pollution attacks- Attackers can't pollute the network with bogus data since data transfer done is always verified using cryptographic techniques.
2. Resistance to Denial-of-Service attacks- Immediate authentication of packets is done at each destination, so bogus packets can be discarded and only valid packets pass through.
3. Session key agreement- Session keys are used for encryption and decryption. Also this key is locally generated and used, hence not exchanged in the network.
4. Real time key generation- No-pre stored keys in nodes; they are calculated at time of data transfer only.
5. Light-weight- Only simple yet good mathematical operations and encryptions techniques are used hence no much resource usage in nodes.

VII. EXPERIMENTAL SETUP

We have assessed the execution of the proposed convention by reenactment utilizing Java [2]. We consider a rectangular district of zone 100£100m, in which the remote sensor hubs are conveyed in a specially appointed way. There is one BS to which all the sensor hubs in the system need to send their information bundles. The transmission scope of every hub is 20 m. We have contrasted the execution of proposed convention and SEEM [4]. Every reproduction trial was directed utilizing 10 distinctive system topologies, and every outcome was arrived at the midpoint of more than 10 keeps running of various system topologies. The execution of the planned convention is

International Journal of Innovative Research in Science, Engineering and Technology


(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

thought about under two conditions: ordinary conditions and conditions with half of pernicious hubs. The execution of the de-marked convention is measured by the quantity of sensor hubs hindered by an arrangement of traded off hubs in each round by expanding the quantity of bargained hubs in the net-Work. The accompanying key parameters are measured amid the reenactment run: Throughput. This is the rate of effectively gotten information bundles by BS. Control Overhead. Control overhead is characterized as the proportion of control parcels (Route Discovery, Route Discovery Reply, Neighbor Collection, Data dispersal Enquiry, and Data scattering Reply) to information transmissions.

System Lifetime. The lifetime of the system is characterized as the time at which the First hub disappointment happens, i.e., the time at which some hub's vitality re-serve is decreased to zero. The lifetime of a WSN is specifically connected to the vitality utilization of every hub. Hub Resilience. The hub resilience power after the assault happens on the system. Figures 3, 4, 5 demonstrate the execution correlation of SEEM [2] and proposed convention when there is no at-tack on the system. From the Figures, we can watch that both SEEM and proposed plan have a high parcel conveyance proportion which increments as the quantity of hubs increments. Both SEEM and proposed plans select an ideal way from various decisions. The proposed plan picks the best way relying on R metric. 2. Likewise control overhead increments as the extent of the system increments. This is because of the way that both BS and sensor hubs need to control bundles to the entire system. At the point when the hubs thickness builds every hub has more neighbors and more control parcels are sent and got between neighbors. However the control overhead is less in the proposed plan than SEEM because of the way that proposed plan picks the best accessible way progressively by utilizing R metric. Additionally just the session key is required to validate the information to be sent to the separate hubs, while hub id is utilized for open key of every hub. Additionally organize lifetime increments than SEEM extensively. R metric in the proposed plan is versatile in nature and pick the best accessible way so that less vitality can be expended which directly affects the system lifetime. This is because of the way that all the past proposed plans utilize the same way for all interchanges between the source and BS. The immediate outcome of this is hubs on this specific way may drain vitality soon. Yet, in the proposed plan, the CH chooses another way with least estimation of R metric. With this dynamic way choice component, the CH guarantees that it can choose the most ideal way for information scattering. Figures demonstrate the outcomes when half of hubs are malignant. The throughput does not diminish in both conventions. At the point when vindictive hubs are on the steering way and don't forward bundles for the source, the proposed plan can distinguish this conduct as clarified in Section 4.3 in which different sorts of assaults can be guarded utilizing existing methods. Hub Resilience: In the nearness of half of the bargained hubs (very nearly 100 hubs out of 200 hubs taken) which drop all the re-laying parcels and promote conflicting directing data, the impact of proposed plan on a proportion of blocked hubs is appeared in Figure 6. Without the proposed plan, the impact of traded off hubs over the system is more since bargained hubs even pull in the system Traffic and drop them. Utilizing proposed plan, in any case,

1. Delay Computation




International Journal of Innovative Research in Science, Engineering and Technology


(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

2. ThroughputComputation



3. RoutingComputation



VII. CONCLUSION

This paper proposes a novel data disclosure and disseminating tradition for remote sensor frameworks which can be used to perform secure and fast data dispersal especially for little setup parameters and variables. This methodology unites the thoughts of framework coding and clear cryptographic strategies to scatter data. The advantages of this tradition are that it is impenetrable to pollution strikes, and finishes brief affirmation of data been scattered. Session keys are used to encode and send data amidst center points and there is no need of genuine trade of the session keys through the framework. In like manner simply essential experimental operations are used to figure keys for encryption of data so next to no of advantage use at the center points. All together it arrangements to give an essential yet secure

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 6, June 2016

and snappy data spread tradition for usage in remote sensor frameworks. Center point deal by an attacker can be an issue in this tradition. It will be overseen as a noteworthy viewpoint without limits works.

REFERENCES

- [1] Mohammad A. Matin, *Wireless Sensor Networks: Technology and Protocols*: Published by InTech, Croatia, ISBN 978-953-51-0735-4, 2012.
- [2] Salvatore La Malfa, *Wireless Sensor Networks*, 2010.
- [3] Jisha Mary Jose, Jomina John, "Data dissemination protocols in wireless sensor networks-a survey", *IJARCCCE*, March 2014.
- [4] T. Ho and D. Lun. *Network Coding: An Introduction*. Cambridge University Press, 2008.
- [5] Daojing He, Sammy Chan, Shaohua Tang and Mohsen Guizani, "Secure Data Discovery and Dissemination based on Hash Tree for Wireless Sensor Networks", *IEEE transactions on wireless communications*, Vol. 12, No. 9, September 2013.
- [6] P. Levis, N. Patel, D. Culler and S. Shenker, "Trickle: a self regulating algorithm for code maintenance and propagation in wireless sensor networks", in *Proc. 2004 NSDI*, pp. 15-28.
- [7] G. Tolle and D. Culler, "Design of an application-cooperative management system for wireless sensor networks," in *Proc. EWSN*, pp. 121–132, 2005.
- [8] Lin, K., Levis, P.: "Data discovery and dissemination with dip." In: *Proceedings of the 2008 International Conference on Information Processing in Sensor Networks (IPSN 2008)*, Washington, DC, USA, IEEE Computer Society (2008) 433-444.
- [9] T. Dang, N. Bulusu, W. Feng, and S. Park, "DHV: a code consistency maintenance protocol for multi-hop wireless sensor networks", in *Proc. 2009 EWSN*, pp. 327-342.
- [10] Hui, J.W., Culler, D.: "The dynamic behaviour of a data dissemination protocol for network programming at scale." In: *Proceedings of the 2nd international conference on Embedded networked sensor systems (Sensys 04)*, New York, NY, USA, ACM (2004) 81-94.
- [11] Nildo dos Santos Ribeiro Junior, Marcos A. M. Vieira, Luiz F. M. Vieira and Om Gnawali, "CodeDrip: Data Dissemination Protocol with Network Coding for Wireless Sensor Networks", In *Proceedings of the 11th European conference on Wireless sensor networks (EWSN 2014)*, Feb. 2014.
- [12] Hailun Tan, "Secure multi-hop network programming with multiple one-way key chains", In: *Proceedings of the International conference on Embedded networked sensor systems (Sensys 07)*, Sydney, Australia, ACM.
- [13] Yingpei Zeng, Jiannong Cao, Shigeng Zhang, Shanqing Guo, Li Xie, "Pollution Attack: A New Attack Against Localization in Wireless Sensor Networks", *IEEE, WCNC-2009*.
- [14] I-Hong Hou, Yu-En Tsai, T.F. Abdelzaher, and I. Gupta. Adapcode: Adaptive network coding for code updates in wireless sensor networks. In *INFOCOM 2008. The 27th Conference on Computer Communications*. IEEE, pages 1517–1525, 2008.
- [15] Andrew Hagedorn, David Starobinski, and Ari Trachtenberg. Rateless deluge: Over-the-air programming of wireless sensor networks using random linear codes. In *Proceedings of the 7th international conference on Information processing in sensor networks, IPSN '08*, pages 457–466, Washington, DC, USA, 2008. IEEE Computer Society.
- [16] S. Katti, H. Rahul, W. Hu, D. Katabi, M. Medard, and J. Crowcroft, "XORs in the air: practical wireless network coding", *ACM SIGCOMM Computer Communication Review*, vol. 36, no. 4, pp. 243-25, 2006.
- [17] Philip Levis, Nelson Lee, Matt Welsh, and David Culler. "Tossim: accurate and scalable simulation of entire tinyos applications, In *SenSys '03*, pages 126-137, New York, NY, USA, 2003. ACM Press.
- [18] TinyOS: an open-source OS for the networked sensor regime. Available: <http://www.tinyos.net/>.
- [19] *Simulating a Wireless Sensor Network, 2010-2013*, [Online] Available: <http://virtual-labs.ac.in/cse28/ant/ant/8/theory/>.