

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 8, August 2019

CO Emissions for CI DI Engine Using Blends of Combinations of Biodiesel with Diesel Fuel

Rajesh Gurani¹, S. N. Kurbet²

Research Scholar, Department of Mechanical Engineering, Basaveshwar Engineering College, Bagalkot,
Karnataka, India.¹

Professor and Head of Dept of Mechanical Engineering, Basaveshwar Engineering College, Bagalkot,
Karnataka, India.²

ABSTRACT: In addition to the widespread use of automobiles in transportation with many advantages, they play a negative role in environmental pollution problems worldwide. Diesel engines are considered as one of the major contribution to environmental pollutants due to exhaust emissions and they may be accountable for numerous health issues as properly. The second aspect of the fossil gasoline is the depletion of fuel ends in considering opportunity fuel for running the engine. Biodiesel is proved to be the pleasant substitute for diesel because of its specific properties like significant reduction in greenhouse gas emissions, non-sulfur emissions, non-particulate be counted pollution, low toxicity and biodegradability. This paper is specially concentrated the impact of combination of biodiesel (WCO and Pongamia) blends on CO emissions. The consequences imply that for the mixture of biodiesels famous higher CO emissions and (WCO 25 + P75) reveals decrease CO emissions than pure diesel. Therefore this combination is preferable for biodiesel operated engine.

KEY WORDS: Combinations of Biodiesel and blends (WCO and Pongamia), CO emission levels

I. INTRODUCTION

Climate alternate is being counted as a worldwide environmental danger due to human beings, it's far seen as the second maximum critical issue that the world faces and has brought about consequences that have an effect on existence adversely. The greenhouse effect is an herbal process that performs a chief function in shaping the earth's weather. Human sports, specifically burning fossil fuels, have contributed to the enhancement of the herbal greenhouse impact. Currently Delhi authorities has added a brand new rule (odd or even days) to govern the emission stage within the metropolis. Researches display that the essential pollution inside the city is from the fossil gas utilization in the cars. Another factor with the fossil fuel is its depletion. Those components are results in suppose an alternate to the fossil fuel. masses of researchers have look into the alternatives, biodiesel is being proposed to be the satisfactory answer because biodiesel is superior to fossil diesel fuel in terms of exhaust emissions, cetane variety, flash point and lubricity traits, with none widespread difference in warmness of combustion of those fuels.

Carbon monoxide effects from the incomplete combustion in which the oxidation process does not occur completely, inside the wealthy mixtures, because of air deficiency and reactant attention, all the carbon can't convert to CO₂ and be shaped CO awareness., despite the fact that CO is produced at some stage in operation in wealthy mixtures, a small portion of CO is also emitted under lean conditions because of chemical kinetic results. Furthermore, biodiesel returns approximately 90% greater power than the power this is utilized to produce it. Biodiesel combined with traditional diesel in a few proportions may be used to run any existing traditional compression ignition engine and does not require any modifications to be performed to the engine.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 8, August 2019

II. OBJECTIVES

The primary destinations of this are:

- Investigating the properties of the biodiesel additionally as blends of biodiesel with diesel.
- Experimental investigation of the performance on single cylinder four stroke diesel engine using waste cooking oil methyl ester biodiesel, combinations of Pongamia and WCO and its blends.
- CO emissions are measured using smoke meter and gas analyzer.

III. EXPERIMENTAL SET UP

The experiments are finished on single cylinder, four-stroke Kirloskar diesel engine. The schematic experimental setup is shown in fig. 1. Engine is interfaced with laptop for measuring the unique parameters. Engine software program is utilized in computer to carry out the measurements. The engine is coupled with an eddy contemporary dynamometer used to measure the emissions mainly CO level.

Table 1. Engine specification

Make	Kirloskar Engine
Bore & Stroke	87.5mm X 110mm
Type of cooling	Water cooled
Speed	1500rpm
Compression ratio	17.5:1
Number of cylinder	1
Rated power	5.2KW
Start of injection	23 ⁰ bTDC
Injection pressure	190 bar




Figure 1: Schematic diagram of Experimental set up.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 8, August 2019

IV. RESULTS AND DISCUSSION

The overall performance of CI DI engine using the one of a kind forms of biodiesel (WCO and pongamia) blends and natural diesel are studied at exceptional loads and at 190bar injection pressure. The performance and emissions of various blends and for neat diesel is executed at distinctive masses and as compared the effects of various blends of biodiesel and diesel with neat diesel fuel as follows.

a) Emission for WCO biodiesel and pure diesel at 190 bar injection pressure:

The CO emission level for distinctive BP for every blend is acquired from records and was plotted as proven in figure 4.1. the graph suggests that CO emissions for WCO biodiesel and its blends has multiplied with less percent as compared with that of the pure diesel engine up to a load of 4.2kw or 15kg and past this 4.2kw load there's a signal of decrease in CO emissions for WCO biodiesel and its blends. On the time of injection a smaller atoms of biodiesel fuel having lesser inertia takes longer time for combustion or incomplete combustion at decrease masses (under 4.2kw). This results in boom co emissions for WCO biodiesel and its blends.




Figure 4.1: Emissions of Smoke Density for WCO biodiesel and pure diesel for 190 bar injection pressure

b) CO emissions for different combinations of biodiesel and pure diesel without any blend:




Fig 4.2: Emissions of CO for combinations of biodiesel and pure diesel at 190 bar injection pressure

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 8, August 2019

The CO emission for different mixtures for biodiesel (WCO and pongamia) and their blends are combined with pure diesel are plotted towards one-of-a-kind bp as shown on fig 4.2. from fig4.2 it is evident that at initial loads the co emission degree of biodiesels are much less than that of the pure diesel and as the load increases the CO emission stage of biodiesels are increasing greater than that of the diesel, pure WCO biodiesel famous more emission degree amongst all other mixtures of biodiesels. the unfinished combustion may be due to decrease injection pressure which gives large atoms of fuel are injected in to the combustion chamber ends in the unfinished combustion of biodiesel and diesel blends which will increase the co emissions.

c) CO emission for different combinations of biodiesel for 20% and 40% blend with diesel:

The CO emission for different combinations for biodiesel and pure diesel with 20% and 40% combination are plotted against specific BP is proven oin fig 4.3 and fig 4.4. the graph suggests that at lower masses (up to 2.86kw) the CO emission stage for pure diesel is more than the biodiesel combinations. at better loads the presence of oxygen utilises in a high gasoline combustion resulting in decrease of co for 100% WCO biodiesel. for this reason WCO biodiesel is most advantageous for these ratios of blends.




Fig 4.3: CO Emissions for combinations of biodiesel and pure diesel with 20% blend at 190 bar injection pressure

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 8, August 2019




Fig 4.4: CO Emissions for combinations of biodiesel and pure diesel with 40% blend at 190 bar injection pressure

d) CO emissions for different combinations of biodiesel for 60% and 80% blend with diesel:

The CO emissions for different combinations of biodiesel and natural diesel with 60% and eighty% combo are plotted in opposition to one-of-a-kind bp is proven in fig 4.5 and fig 4.6. from graph it can be seen that the smoke emission degree for diesel is less than the mixtures of biodiesel. because the blends of biodiesel with the diesel increases, there might be reduction in heating value, excessive viscosity and low calorific value. this leads to partial combustion or incomplete combustion. therefore there will be increase in CO emission for better blends for combos of biodiesel. and among these biodiesel the (WCO25+p75) famous lower co emission that's greatest for biodiesel engine.




Fig 4.5: CO Emissions for combinations of biodiesel and pure diesel with 60% blend at 190 bar injection pressure

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 8, August 2019




Fig 4.6:CO Emissions for combinations of biodiesel and pure diesel with 80% blend at 190 bar injection pressure

V. CONCLUSIONS

From the prevailing research it is concluded that

- i) Whilst the exceptional blends are taken into consideration for person biodiesel (WCO), the blend B20 is more reveals decrease emission of co. because of lifestyles of oxygen in decrease blends leads to complete combustion and outcomes decreased emission level.
- ii) While specific combinations of biodiesel are blended with natural diesel with 20% and 40% combo, the emission stage for pure diesel is greater than the biodiesel combinations. The presence of oxygen utilises in an excessive gas combustion ensuing in lower of co emission for 100% WCO biodiesel. hence WCO biodiesel is premier for those ratios of blends.
- iii) while exclusive mixtures of biodiesel are blended with pure diesel with 60% and eighty% combination, because the blends of biodiesel with the diesel increases, there could be discount in heating value, excessive viscosity and coffee calorific value. This results in partial combustion or incomplete combustion. For this reason the co emission for diesel is less than the combinations of biodiesel (WCO and pongamia).

REFERENCES

1. Jagannath Hirkude, Atul Padalkar, Deepa vedartham, "An Investigations on the effect of waste fried oil methyl ester blends and loads on performance and smoke opacity of diesel engine using response surface methodology". Energy Procedia 54 (2014) 606 – 614 2013.
2. Wail M. Adailleh, and Khaled S. AlQdah (2014) has investigated "The Performance of Diesel Engine Fuelled by a Biodiesel Extracted from a Waste Cooking Oil.
3. Shivaji Bhandarkar, "Vehicular Pollution, Their Effect on Human Health and Mitigation Measures". Vehicle Engineering(VE) Volume 1 Issue 2, June 2013.
4. Bhargavi R. "Biodiesel production from waste cooking oil". Journal of Chemical and Pharmaceutical Research, 2015, 7(12):670-681.
5. Ibrahim Aslan Res_itog`lu • Kemal Altinis_ik Ali Keskin, "The pollutant emissions from diesel-engine vehicles and exhaust after treatment systems", Clean Techn Environ Policy (2015) 17:15–27.
6. C. Syed Aalam, C.G. Saravanan, " Effects of Fuel Injection Pressure on CRDI Diesel Engine Performance and Emissions using CCD", IRJET Volume: 02 Issue: 05 | Aug-2015