

# International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

## An Overview of 4G Wireless Networks and Handover Techniques

Vijay Namavaram<sup>1</sup>

Senior Software Engineer - Research and Development, Wyrta Ltd., UK<sup>1</sup>

**ABSTRACT:** In the transformation to next-generation networks, the combination of IP-based center networks with heterogeneous cordless systems is actually anticipated. In this particular job, a review of the handover schemes as well as algorithms proposed for wireless interaction bodies in mobile phone environments existed. Adhering to a layered viewpoint, the designed schemes around were grouped into 2 groups and contrasted in terms of guidelines, system selection approaches as well as their components. This paper provides a detailed study on 4G wireless networks and handover techniques.

**KEYWORDS :** networks, mobility, wsn

### I. INTRODUCTION

Range of motion is a quite significant function of a 4G cordless networks system. Mobile terminals ought to be able to choose the very best network among the readily available networks including WLAN, WiMAX, as well as satellite devices and then create handover. The conventional methods where the handover is actually per-based on the manner of the examination of signal durability are actually not enough. They do certainly not consider different mobile phone user accessory options like the existing circumstance or even the accessory of the customer choices. 4G technologies must swindle- sider adaptive and intelligent method for vertical handover and also think about various other factors such as financial price, surveillance, energy usage, and also the mobile terminal speed [1].

Thereby, an even more cutting-edge strategy is actually needed to have for vertical handoff methods execution to make a satisfactory outcome for each, the consumer and the system. Ant swarm strategy can easily encounter the unpredictability of structure systems because of the center of the ant colony idea to establish procedures that can easily do reasoning as well as handling issues that need individual intellect. An additional explanation responsible for using ant swarm method is actually the simple fact that, provided the great deals of linked MTs that we have today, making use of ant's nest adaptive method are going to use the best QoS to all MTs regularly and also a worldwide optimization answer for the system. Concurrently, utilizing this method will definitely take full advantage of the top quality of service by reducing the likelihood of unnecessary handover occasions and handover breakdowns from cellular networks to WLANs. Reducing the cost of the network and increasing the user satisfaction would be another benefit. The success of researches in which ants' colonies optimization was used to solve network issue such as "ant-swarm-inspired energy- aware routing protocol for wireless ad hoc networks," in which Sudip Misra et al. proposed an energy-aware routing protocol for wireless ad hoc networks [2], and "an ant-swarm- inspired energy-efficient ad hoc on-demand routing protocol for mobile ad hoc networks," proposed by [3], encouraged us to use ants' colony in our work.

### II. BACKGROUNDANDRELATEDWORK

Several researchers have actually assessed on numerous facet related to QoS in vertical handoff monitoring with respect to 4G networks and also have suggested concepts for much better seamless connection in various networks. The literature study has actually supported to know the various accessible modern technologies involved in providing QoS in 4G networks and also aid to discover methods utilized for information appropriation amongst mobile phone consumers.

## International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

Thereby it has actually assisted to discover the values and mark against ones of a variety of versions which has actually paved method to pinpoint today suited study problem. A fancy content on the literature poll exists in the complying with section.

[3] described a practical world wide web based style of UMTS-WIMAX and also MIH (IEEE 802.21 standard) based upon the VHO protocol for UMTS as well as WIMAX heterogeneous connect with respect to seamless intersystem handoff, packet loss and unit throughput. They have actually even more mentioned that the handover operation depends upon the media individual handover feature (MIHF) that is actually assisted by Media-Independent Info Company (MIIS) web server.

[4] have actually explained concerning system choice in heterogeneous cordless networks with unclear multiple criteria decision making. Their job mostly covers the element of network collection protocol based on Fuzzy Multiple Quality Decision Making. The algorithm includes the aspects like Monetary price( C), Received Indicator Toughness (RSS), Band Size (BW), individual Inclination (P) and Speed (V). It also identifies the System assortment function (NSF) which makes up the effectiveness being used radio sources by handing off to a particular system. The system which offers the best NSF is selected as the most ideal system to hand off coming from the existing access network. The protocol has taken mobility parameters like user preference as well as speed of the mobile phone into account and favours seamless flexibility as well as lessens excess handovers.

[5] have actually grown a design and also likeness of vertical handover protocol for automotive interaction. They have declared radio accessibility networks (WLAN, UMTS, WiMAX) as the TRANQUILITY (ongoing sky interface for lengthy as well as medium selection), with global standard (ISO 21217) for ITS that assists each one of them. Analytic Power Structure Refine (AHP). It is utilized to learn the concern of the requirements and also the uniformity of the selection is utilizing the Consistency Proportion (CR). By using inserted MATLAB, a plan is created through which the tool decides on an ideal system resulting in upright handoff based upon various standards. A bedtime of twenty secs is actually fixed prior to as well as once again repeating the program in the event the auto relocates coming from one tissue to one more. This program is graphed in SDR to establish a reconfigurable hardware and also hence SIMULINK is chosen by the scientist as the platform for advancement.

The congestion command mechanism deals with blockage in the 4G cordless networks through launching a vertical handover one of chosen resources and intended networks. The vertical handoff formula proposed by all of them takes into consideration the concept purpose of 4G wireless networks. This design recommends a new remedy to blockage management device through union video game version as well as by replicating their vertical handoff algorithm VHCCG technique reduces the hold-up as well as takes less company time for refining handoff phone calls. Their searchings for show that the vertical handoff together with union game considerably decreases the problem and solution time for handoff calls. The primary limit of this version is actually that it performs not bear in mind the actual time as well as non-real time companies.

HNE looks at several network criteria as inputs as well as the output is actually a binary worth. The inputs include RSS samples, AP electrical power level, velocity of the Mobile Terminal (MT), the span of the network, excessive handover possibility needs and also handover latency handover failing. Output '1' signifies that a handover is actually necessary and also an outcome of '0' means the handover is actually not called for based on this design. The writers popped the question a multi-criteria upright handoff selection formula based upon two parts. They are opportunity threshold computation as well as taking a trip time evaluation. The proposed techniques were actually compared to various other pair of suggested strategies like hysteresis strategy and the repaired RSS limit located approach. The end results of the Simulation uncover that, this method minimizes the amount of handover failings as much as 80% and also needless handover through 70 %. The restriction of the suggested procedure is that they have ruled out the throughput metrics for the mobility control procedure. They have actually concentrated to review the Blurry reasoning located Vertical Handoff Decision Protocol based on three input specifications namely Gotten Signal Durability, Cost as well as Transmission capacity, against one

## International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

input criterion such as Received Sign Stamina just in case of standard Upright Handoff Decision Protocol. The necessary component of Upright Handoff Decision in 4G networks strengthened the overall effectiveness of smooth range of motion relative to 4th creation various networks.

[5] have studied making use of Infotech (IT) in 4G cordless systems through advising an upright handoff scheme and explained its operations like system choice, handoff decision-making and also handoff execution. The recommended handoff agrees with for both freely as well as tightly paired 4G cordless system designs. Their program clarifies handoff functions via two basic assimilation strategies. A likeness research of the vertical handoff is actually carried out to understand its efficiency in regards to gone down packages throughout handoffs in freely as well as firmly coupled designs. The outcomes verifies that VHO units influences package decrease fee in limited and also loosened combination approach under different bunch ailments. In this particular method, Premium of Service specifications, the connection length range of motion, network gain access to cost and also the info on location and also the signaling lots of the network for the upright handover were thought about. The protocol was actually based upon the solution of CMDP along with the motive of raising the overall benefit of the link. The spending plan to become invested by user for the link is actually the major constraint. A static randomized plan is achieved during the geometrical circulation of the connection termination time.

Several procedures as well as studies of upright handover choice formula have actually been mentioned in the technological literature. A training class of approach is actually based upon RSS. This technique chooses the strongest received BS whatsoever opportunities. It has been actually enhanced through conforming RSS limit as well as likewise has been actually integrated along with other parameters including user's velocity, site, system expense, and system tons.

The 2nd technique utilizes artificial intelligence tech- niques (structure as well as may be actually complicated to apply in practi- cal bodies) mixing numerous guidelines such as system disorders and also mobile phone terminal's wheelchair in the handoff selection including the semantic network version which has actually been presented by Mrs. Chandralekha and Behera to refine multicriteria vertical handoff choice metrics. An adaptive vibration idea (CRAFT) has actually been created as a changed type of competitive finding out to get rid of the problem of finding out reliability. A VHO choice formula has been actually suggested which permits a wireless gain access to network to take full advantage of the aggregate battery life-time of mobile nodes (MNs) as well as harmonize the total tons one of all attachment points (e.g., base stations as well as get access to points). As well as a VHD scheme was pro- positioned for optimizing the effectiveness of upright handover pro- cesses in the Fourth-Generation (4G) various wireless systems by utilizing three very closely combined components: handover necessity estimation (HNE) finds out whether handover is actually essential to an available system, handover target choice chooses the "ideal" system one of the accessible prospects based upon a collection of standards, and handover triggering ailment evaluation finds out the ideal second to trigger handover away from the presently linked system.

The 3rd strategy blends several metrics like gain access to expense, speed of a bunch, power intake, band- width, and premium of service ina price functionality estimated for the accessible accessibility networks. We can easily have user-related cost feature, network-related cost functionality or a mix of both.

Likeness located performance evaluations of provided jobs illustrate that the system proposed by [1] is actually one of the most full answer by minimizing the number of handover failings and also unnecessary handover instances through up to 80% and 70%, specifically. Nevertheless, there is still area for improvement, because even though using this algorithm we can easily decrease handover failings and also excessive handover occasions, it performs not make the most of the visibility in the system of a very significant amount of MTs and the visibility of several networks, due to the fact that each opportunity our experts pick the very first system if it delights needs, and our team carry out certainly not evaluate all on call systems so our experts carry out not choose the general greatest accessible system. MTs would certainly select the exact same system if they observe the same velocities. This administers our team to overflow in one system as well as by the exact same technique diminishing the general functionality.

# International Journal of Innovative Research in Science, Engineering and Technology

*(A High Impact Factor, Monthly, Peer Reviewed Journal)*

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

In our protocol, our company benefit from both functionalities made use of in HNE to calculate the time limit and also journeying opportunity prophecy and afterwards incorporate them in a brand-new algorithm that uses ACOR to acquire the very best option for the overall network and also not just one MT. Unlike HNE, our ACOR located formula evaluates all readily available networks and decides on the greatest one.

Our team benefit from the presence of a really essential variety of MTs to get worldwide visibility of the system and the on call remedies. If a brand-new system appears, we assess it, and also the access concerning the new system is actually put in the repository table (sustain the list of the most effective readily available networks). Through this, our team optimize using network sources along with the total network functionality as we are going to show in our simulation where we can decrease the variety of handover breakdowns and excessive handover through as much as 95% by utilizing our VHD algorithm..

### III. VHD ALGORITHMS

#### RSS Based VHD Algorithms:

In RSS located algorithms Obtained Signal Strength is the principal standards. These sorts of VHD formulas compare the RSS of the existing aspect of add-on against the others to produce handover selections.

The formula is actually popped the question for handover in between 3G systems and WLANs by mixing the RSS sizes either with a determined life time measurement or even the accessible bandwidth of the WLAN applicant. Our company may illustrate the technique utilizing observing two scenarios.

In the 1st instance, when the mobile phone incurable moves from the insurance coverage location of a WLAN in to a 3G, a handover to the 3G system is actually initiated. When RSS average of the WLAN relationship drops below a predefined threshold, as well as the determined lifetime is actually less than or equal to the handover delay, the handover is actually activated. In the 2nd circumstance when the mobile phone incurable steps in the direction of a WLAN cell, the handover to the WLAN is activated if the ordinary RSS dimensions of the WLAN signal are actually higher a threshold as well as the available transmission capacity of the WLAN fulfills the transmission capacity requirements of the function.

A formula in between WLAN and 3G which is based on comparison of the current RSS and also a compelling RSS limit when a mobile terminal is actually attached to a WLAN get access to point. The powerful RSS threshold serves in the manner in which it decreases the occurrences of misleading handover commencement and maintain the handover failures below a limit.

To do away with the excessive handovers which is introduced in the above approach, a travelling proximity forecast based protocol is actually created. The protocol thinks about the time the mobile terminal is counted on to devote within the tissue. The strategy relies upon the evaluation of WLAN journeying opportunity (i.e. time that the mobile terminal is actually expected to invest within the WLAN cell) and also the computation of a time limit. A handover to a WLAN is actually induced if the WLAN insurance coverage is actually accessible and the estimated journeying time inside the WLAN cell is bigger than the amount of time threshold.

The principal advantage of the procedure is actually that it decreases handover failures, unneeded handovers as well as hookup break downs nevertheless improved handover delay is introduced.

# International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

## Bandwidth Based VHD Algorithms:

In these form of protocols the accessible data transfer is actually the main requirements for the handover.

A QoS based algorithm is recommended which takes recurring transmission capacity and also consumer company criteria into account in deciding whether to handover coming from a WLAN to Wireless Wide Region Network (WWAN) as well as vice versa. The algorithm also takes the condition of the mobile phone terminal right into consideration.

If the mobile terminal is in the unoccupied state, a handover to the recommended gain access to system is executed; typically the handover choice is actually based upon the customer use kind.

This procedure manages to achieve higher throughput as the readily available bandwidth is actually considered as the primary standards for VHD. Additionally through taking treatment kinds in to profile, reduced handover latency for delay-sensitive requests is actually obtained.

To enhance the general unit throughput a formula is created between WLAN and also Wideband Regulation Branch A Number Of Access (WCDMA), which takes note of the Signal to Obstruction as well as Sound Proportion (SINR). The SINR estimate of the WLAN signals is turned to a comparable SINR to become compared to the SINR of the WCDMA channel.

SINR located handovers may give individuals greater general throughput than RSS based handovers because the offered throughput is directly depending on the SINR, and this formula causes a balanced tons in between the WLAN and also the WCDMA systems. However these protocols may likewise offer ping-pong result.

To lessen the unneeded handovers an Inappropriate Decision Probability (WDP) prediction located protocol [2] is actually recommended. Within this technique the chance of excessive and also missing hanovers is actually integrated as well as WDP is actually figured out. This formula has the ability to decrease the WDP as well as equilibrium the visitor traffic tons.

## Cost Function Based VHD Algorithms:

The basic idea of a price feature based vertical handoff decision formula is to decide on a combo of network and DE elements including RSS, network dealing with area, readily available bandwidth, solution cost, stability, security, battery energy and DE wheelchair model, etc. and determine an expense function based upon these elements to analyze the functionality of intended systems. The handoff selection may after that be actually created as necessary.

A multiservice located algorithm relies on an expense functionality which works out the cost of all feasible aim at systems. In this particular algorithm all the energetic uses are focused on and then price of each achievable aim at network for the service along with the greatest top priority is computed. This approach is actually helpful due to the use of cost function, additionally the percent of user delighted asks for is actually enhanced as well as handover obstructing chance is actually decreased.

Expense feature located handover decision formula with normalization as well as weight circulation is planned through which the normalization and also body weights circulation techniques are actually supplied. A network top quality factor is utilized to assess the performance of a handover aim at prospect. With help from this method higher system throughput as well as consumer's satisfaction is actually attained.

A weighted functionality based algorithm which delegates the VHD estimation to the checked out system as opposed to the mobile terminal. The system candidate with the highest possible weight feature is actually picked as the handover aim

## International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

for. The conveniences of this approach is handover selection delay is actually minimized, low handover shutting out cost and also high throughput.

### Multiple Attributes Decision Making Based Algorithms:

The several features decision making located algorithm (MADMA) computes the measurable market value of each stabilized attribute as well as assesses the aim at units by means of the heavy functionality of the measurable values, the decision can at that point be actually created.

In Easy Additive Weighting (SAW) located MADM, various aspects are appointed different weights which may be dynamically adjusted depending on to network condition and different individual services, therefore, it is actually achievable to assure various individual QoS requirement and boost the performance of the whole system at the same time.

Gray Relationship Review Located Formula (GRAA) is a logical approach to determine relationship degree of different variables based upon the similarity and also distinction of variables worked with by grey relational coefficient (GRC). GRC is actually related to determine the correlation of each candidate network with consumer current network and the candidate network with highest correlation of current network is chosen as handoff destination network. GRA can also be combined with other methods such as fuzzy logic and AHP to improve the performance of vertical handover algorithm.

GRAA is able to analyze different system factors given only few data and the trend of system development can be measured quantitatively, thus GRAA is very suitable for dynamic network analysis, however, the computation complexity is large which limits the practical application.

### Combination Algorithm:

Combination formulas combine different specifications in the handover selection including the ones utilized in the price functionality protocols. These algorithms are based on man-made neural networks or even fuzzy logic.

A VHD formula is actually cultivated based on synthetic semantic networks (ANN). The mobile phone picks up components of on call wireless systems as well as delivers all of them to a middleware called vertical handover supervisor through the existing links. The upright handover manager features 3 main components: network handling supervisor, attribute collection agency and ANN training/selector. A multilayer feed ahead ANN is utilized to identify the most ideal handover intended cordless network offered to the cell phone, based on the consumer's desires.

Fuzzy logic approach can be made to deal with vertical handoff problem along with fuzzy specifications. These kind of algorithms deal with wealthy set of input criteria for making vertical handover decision. A blurry logic located algorithm is actually established which is actually made use of to handle handovers between WLAN and UMTS. A pre-decision unit is used in this method. This algorithm is able to improve the performance by reducing the number of unnecessary handovers and avoiding ping-pong effect.

### Authentication Based Algorithms:

In NGN, safety and security is actually thought about as one of the best tough problems presented through mobile phone media. Individual movement enhances the threat of prohibited customers impersonating legal customers. Therefore there is a need that the handover method ought to provide security along with authentication system. Likewise it needs to be able to lessen the verification problem in the course of the handover method.

An authentication plan for fast handover in between WI-Fi gain access to points is actually planned, in which the writer has actually made use of the EAP-SIM (Expandable Verification Method). The scheme makes use of the pre-authorization and it eliminates the requirement for interaction along with the remote control server when the handover actually happens. This system can reducing the authentication hold-up and the direct reliance on the RTT

# International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

(round trip delay) in between the AP as well as the authorization server is actually likewise broken.

In [2], the author has recommended a holistic method that gets rid of the repeated steps of verification without impacting the safety level, to enhance QoS criteria throughout handover. In this strategy a legitimate certification is actually provided at that time of enrollment of MN with AAA web server. This legitimate certificate resides in consensus with all the company which will definitely be special and also authentic for each network. This approach decreases the amount of repetitions which will certainly spare the data transfer, opportunity and also price. Decrease is actually handover latency, package reduction as well as cost is actually secured.

## IV. HANDOVER TECHNIQUES

### Horizontal Handover

In Horizontal handover the individuals use the same network gain access to modern technology and also wheelchair do on the same levels. In parallel handover the on-going calls are to be preserve and although the change of IP deal with due to the mobile phone nod activity.

### Vertical Handover

In vertical handover the consumer can easily move in between various network get access to innovations. In vertical handover the range of motion perform in between the various layers. In vertical handover the mobile phone node crosses the various systems and also certainly not simply alters the IP address but likewise alter the system user interface, QoS characteristics etc

	Vertical Handover	Horizontal Handover
Access Technology	Changed	Not changed
QoS Parameters	May be hanged	Not changed
IP Address	Changed	Changed
Network Interface	May be change	Not Changed
Network Connection	More than on connections	Single connection.

**Table 1: Difference between Vertical/Horizontal Handover**

### Downward and Upward Vertical Handover

When consumer relocation form connect with lower tissue dimension and greater transmission capacity to network with bigger tissue measurements and normally lower bandwidth is named downward-vertical handover, as an example WPAN to FRYING PAN. On the other, handover that is actually executed along with much higher tissue size as well as commonly lesser transmission capacity is actually referred to as upward-vertical handover.

### Microcellular Handover


This handover approach is actually typically utilized in inhabited locations to satisfy high device capability by reuse frequency.

## International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019



**Figure 1 : Base Stations Deployed in Streets**

Figure 1 reveals that there are actually 3 Base Stations in three streets. The Base Station 1 and Base Station 3 have line-of-sight (LOS) whereas Base Station 2 and Base Station 1 has no-line-of-sight (NLOS). As a result our experts may say that there is actually LOS handover in between Base Station 1 as well as Base Station 3 whereas between Base Station 2 as well as Base Station 1 there is actually NLOS handover.

When the Mobile Terminal misplaces the LOS because of turning the corner along with his present Base Station in NLOS then Acquired Signal Toughness reduced. This RSS decreasing result called the section effect. Within this condition quick handover algorithms are called for to avoid from phone call dropping due to the fact that RSS reduce rapidly because of corner impact. LOS attempts to decrease the excessive handover between the Base Stations whereas NLOS need to be actually as easily as feasible due to edge impacts.

### **Multilayer Handover**

In multilayer handover the microcells are laid over with macrocell to decrease the variety of handover as well as to raise the system capacity. For GSM900 the microcell and also macrocell have place range from five hundred gauges to 35 Km. In multilayer handover depending on to speed up, individuals are consigned with each coating. To minimize the number of handover microcell layer is set aside to decrease consumer whereas macrocell allotted to fast user. When microcell ends up being stuffed then within this situation macrocell not just work for swift individual but additionally work with slow users. Handover telephone calls are actually decant to macrocell when the microcell coating circulates all of it channels to reduce consumers. When the lots in microcell reduces then it is actually practical for microcell to designate networks to brand-new individual. This type of handover is known as take-back.

### **Limitations of Vertical Handover**

There are some limitations of upright handover, e.g. it handles all the hookups in same way. When all TCP/IP link immediately transmissions from one interface to one more, within this circumstance just one cordless interface (the most ideal one) is utilized then. The phrase made use of 'the most effective one' normally interest in end user particular application. For the most part it make use of different techniques for multiple connections as well as it may also suited for finer grained approach ('this method refers to consecutive direction for stream implementation in similarity on asynchronous multiprocessor').

The second constraint of vertical handover is actually that vertical handover need to have the exact same system user interface. All the wireless interfaces must be actually made use of as component of the same Mobile IP and DNS infrastructure because mobile nodes and peers must be able to reach the Mobile IP and DNS server.

# International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: [www.ijirset.com](http://www.ijirset.com)

Vol. 8, Issue 6, June 2019

Because of these two limitations vertical handover can not bring together the ad-hoc technologies, such as ad-hoc 802.11 b, IrDA and Bluetooth. The ad-hoc networks contain some nodes that may not be the part of direct peer to peer infrastructure. This means that, because of peer to peer connections we are missing the very important part of wireless diversity. Usually the peer to peer connections are most efficient because some time they offer the shortcuts for slow and expensive infrastructure.

## V. CONCLUSION

The monitoring of systems to lower the processing problem and a trusted handover choice is actually performed in various wireless networks. Within this paper we proposed choice creators VIEWED as well as WPM to choose the greatest network coming from the guest system for the Upright decision plans. The most effective decision creator is actually studied by the relative standard deviation as well as the very best one is actually WPM. This paper provided a detailed review on 4G wireless networks and handover techniques.

## REFERENCES

- [1] K. Ayyappan and also P. Dananjayan, "RSS dimension for vertical handoff in heterogeneous system," Publication of Theoretical and Applied Infotech, vol. 4, no. 10, pp. 989-- 994, 2008.
- [2] W.-T. Chen, J.-C. Liu, and also H.-K. Huang, "An adaptive program for vertical handoff in cordless overlay networks," in Proceedings of the 10th International Seminar on Identical as well as Circulated Equipment (ICPADS '04), pp. 541-- 548, IEEE, Newport Coastline, Calif, UNITED STATES, July 2004.
- [3] Kiran Kumar S V N Madupu, "Challenges and CloudComputing Environments Towards Big Data", International Journal of Scientific Research in Science, Engineering and Technology (IJIRSET), Online ISSN : 2394-4099, Print ISSN : 2395-1990, Volume 1 Issue 1, pp. 203-208, 2014. Available at doi : <https://doi.org/10.32628/IJRSET207277>
- [4] Kiran Kumar S V N Madupu, "Data Mining Model for Visualization as a Process of Knowledge Discovery", International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering, ISSN: 2278 – 8875, Vol. 1, Issue 4, October 2012.
- [5] M. Liu, Z.-C. Li, X.-B. Guo, and H.-Y. Lach, "Style and evaluation of upright handoff decision algorithm in heterogeneous cordless networks," in Process of the 14th IEEE International Conference on Networks (SYMBOL '06), pp. 1-- 6, IEEE, Singapore, September 2006.
- [6] Chandralekha and also P. K. Behera, "Use of adaptive vibration theory for vertical handoff choice in heterogeneous cordless environment," International Diary of Recent Styles in Engineering, vol. 2, no. 3, pp. 56-- 60, 2009.
- [7] Pushpa Mannava, "Research Challenges and Technology Progress of Data Mining with Bigdata", International Journal of Scientific Research in Computer Science, Engineering and Information Technology (IJRSCSEIT), ISSN : 2456-3307, Volume5 Issue 4, pp. 08-315, July-August 2019. Available at doi : <https://doi.org/10.32628/CSEIT206274>
- [8] Pushpa Mannava, "Big Data Analytics in Intra-Data Center Networks and Components Of Data Mining", International Journal of Scientific Research in Computer Science, Engineering and Information Technology (IJRSCSEIT), ISSN : 2456-3307, Volume 1 Issue 3, pp. 82-89, November-December 2016. Available at doi : <https://doi.org/10.32628/CSEIT206272>
- [9] Kiran Kumar S V N Madupu, "Advanced Database Systems and Technology Progress of Data Mining", International Journal of Innovative Research in Science, Engineering and Technology, ISSN: 2319 – 8753, Vol. 2, Issue 3, March 2013
- [10] Kiran Kumar S V N Madupu, "Functionalities, Applications, Issues and Types of Data Mining System", International Journal of Innovative Research in Computer and Communication Engineering, Vol. 5, Issue 8, August 2017
- [11] Pushpa Mannava, "An Overview of Cloud Computing and Deployment of Big Data Analytics in the Cloud", International Journal of Scientific Research in Science, Engineering and Technology (IJRSET), Online ISSN : 2394-4099, Print ISSN : 2395-1990, Volume 1 Issue 1, pp. 209-215, 2014. Available at doi : <https://doi.org/10.32628/IJRSET207278>
- [12] Pushpa Mannava, "Role of Big Data Analytics in Cellular Network Design", International Journal of Scientific Research in Science and Technology (IJRST), Online ISSN : 2395-602X, Print ISSN : 2395-6011, Volume 1 Issue 1, pp. 110-116, March-April 2015. Available at doi : <https://doi.org/10.32628/IJRST207254>
- [13] Sriramoju Ajay Babu, Namavaram Vijay and Ramesh Gadde, "An Overview of Big Data Challenges, Tools and Techniques" in "International Journal of Research and Applications", Oct - Dec, 2017 Transactions 4(16): 596-601
- [14] Ramesh Gadde, Namavaram Vijay, "A SURVEY ON EVOLUTION OF BIG DATA WITH HADOOP" in "International Journal of Research In Science & Engineering", Volume: 3 Issue: 6 Nov-Dec 2017.
- [15] Pushpa Mannava, "A Comprehensive Study on The Usage of Big Data Analytics for Wireless and Wired Networks", International Journal of Scientific Research in Science and Technology (IJRST), Online ISSN : 2395-602X, Print ISSN : 2395-6011, Volume 4 Issue 8, pp. 724-732, May-June 2018. Available at doi : <https://doi.org/10.32628/IJRST207256>
- [16] Pushpa Mannava, "A Big Data Processing Framework for Complex and Evolving Relationships", International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering, ISSN: 2278 – 8875, Vol. 1, Issue 3, September 2012
- [17] Pushpa Mannava, "A Study on the Challenges and Types of Big Data", "International Journal of Innovative Research in Science, Engineering and Technology", ISSN(Online) : 2319-8753, Vol. 2, Issue 8, August 2013
- [18] Pushpa Mannava, "Data Mining Challenges with Bigdata for Global pulse development", International Journal of Innovative Research in Computer and Communication Engineering, ISSN(Online): 2320-9801, vol 5, issue 6, june 2017
- [19] Ajay Babu Sriramoju, Namavaram Vijay, Ramesh Gadde, "SKETCHING-BASED HIGH-PERFORMANCE BIG DATA PROCESSING ACCELERATOR" in "International Journal of Research In Science & Engineering", Volume: 3 Issue: 6 Nov-Dec 2017.
- [20] Namavaram Vijay, Ajay Babu Sriramoju, Ramesh Gadde, "Two Layered Privacy Architecture for Big Data Framework" in "International Journal of Innovative Research in Computer and Communication Engineering", Vol. 5, Issue 10, October 2017