

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

Smart Gas Level Monitoring, Booking and Gas Leakage Detector over IOT

G.Neelakrishnan¹, R.S.Jeevitha², P.Srinisha³, S.Kowsalya⁴, S.Dhivya⁵

Assistant Professor, Department of EEE, Muthayammal College of Engineering, Rasipuram, Namakkal,

Tamil Nadu, India ¹,

UG Scholar, Department of EEE, Muthayammal College of Engineering, Rasipuram, Namakkal,

Tamil Nadu, India ^{2,3,4,5}

ABSTRACT: Gas is detecting innovation has among the topical research, ponder for rather now and then. With the reason for local gas chamber cooking turned out to be simple and settling them is moreover abbreviated. Be that as it may, at that point are likewise sick impacts of utilizing these barrels. Spillage of residential gas isn't just lethal to human and creature life, yet in addition aims colossal property misfortune. In this way, location and essential advances are to be considered to forestall unfortunate mishaps. Many accidents tendencies due to short circuits, gas leakages, Etc. won't permit a normal person to enter the accident space, therefore on the scale back any harm. Such accidents are a unit, increasing every day, owing to lack of awareness, precaution measures and mental object. Multiple sensors were used for detection method. This paper presents an intelligent security system helpful for many of the house and business application.

KEYWORDS: MQ5 Gas Sensor, Smart Alerting Techniques, Raspberry-pi3, Buzzer, Light Emitting Diode.

I.INTRODUCTION

Nearly 62 citizens pass on reliably for the reason of fire disasters in our country. Out of nowhere 17 percentage passings for the reason of Gas chamber/stove fire break open. The framework provides protection to the citizens the fire break open are not made easy in the livestock. The implementation. The Framework will assist in allowing effective protection to human being and belongings. Internet of things is a gadget driver which is identified with varieties of sensors. With the help of attached to the ARPANET. Which is fit for exchanging data by utilizing Internet of things. Its purpose can be extended for expanding the endure insurance models. It assists in making applications which are price productive. Internet of things stage takes an essential job around the security to the human life. LPG is an ignitable gas, which is basically connected to the family unit and business situations. The greatest part of the humankind in our nation uses Liquefied Petroleum Gas is utilized as burnable for cooking use. The alarming framework can persistently decide the spillage of gas with the documentation of the sensors. Therefore, we have utilized the IOT connected sciences too.

Assemble a Gas cautioning framework for the residents that has canny cautioning systems, including sending an instant message to the bothered authority [10]. This framework won't just ready to distinguish the spillage of gas yet in addition cautioning through perceptible alerts.

The Proximity of excess proportions of frightful gas in condition then this structure can advise the customer. The system can encourage the public administration about the state before the danger occurs through a message. Cell interfaces are used to caution the whole concerning the people by sending SMS around gas spillage. Internet of things based Gas Spillage Recognition Framework, Expectation and Shrewd Cautioning will recognize gas spillage using MQ5 sensor is used for recognizing LPG, vaporous oil, town gas, keep up a vital separation from the upheaval of alcohol and cooking vapor and smoke. Additionally, check the nearness of riches extents of ruinous gases and exhorted through alerts. With the help of IOT it'll caution as to in regards to the gas spillage condition through the SMS abuse gas application and

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

elective texts send to gas association with individual areas and a ready SMS are sent through Email for explicit talented. Wi-Fi interfaces are utilized to caution the all inclusive community by the light control structure and sound sign when gas spillage happens [10].

A.LPG

Auto gas has a risky subject of 1.8 and 9.5 percentage container of gas in air. This is altogether smaller than other regular vaporous powers. Gas moreover with other oil determined can be joined with sustainable power sources to give more prominence unwavering quality while as yet accomplishing some decrease in CO₂ transmission. Gas vapors can keep operating for long separations along the ground and can gather in the Channel or Cylinder can detonate whenever engaged in a fire. The state of being way this hazardous gas can make cool consumes the skin and it can go about as an unconsciousness at high focuses [10] Break cause a negative impact to the state of being with the end goal that the hydrocarbons and different synthetic concoctions of the Gas causes long rest. It likewise causes bothered respiratory tract, nose and eyes.

B.PROBLEM STATEMENT

To investigate Gas spilling and alarming the citizens about the spilling who are situated locally and remote location through this system Examinations by oil organizations found that numerous LPG customers are ignorant of security checks of gas chambers [10] .Another reason is unlawful filling of gas barrel likewise causes disasters. There is a requirement for a framework to identify and furthermore avert spillage of LPG.

1. To detect the leakage of LPG system
2. By sending message through Email, text messages, light control system and audio indication (voice) to alert the people about the gas leakage.
3. To alert the gas office about the spillage of gas by instant messages with individual locations.

II. RELATED WORK

Depending upon the review of gas spilling investigate techniques were exhausted the later analytics paper and report towards the gas spilling investigation techniques and gas related subjects Chet Sandber, Jim Holmes, Ken Mc Coy, And Heinrich koppitsch [1]. They have proposed this method in ongoing year the issue of break discovery in pipelines, tanks, and process vessels has been the focal point of many worker hours of exertion. A few instances of breaks happening in pipelines, a diagram of established hole location frameworks, and the building premise of another sort of finder framework are inspected. This framework is an adaptable hydrocarbon detecting link that can be introduced dong pipelines, in two fold regulation tanks and channeling, or in trenches to distinguish and find breaks of basic mechanical hydrocarbon solvents or powers while overlooking the nearness of water. The basic electrical circuit is likewise depicted, which finds and identifies a break anyplace along the length of the sensor. The present significant technique for hole recognition is the remunerated volume balance strategy. This strategy basically measures the "volume in" and subtracts the "volume out". There are meters that are ensured repeatable to inside - 05 percent. A caution will sound when there is a noteworthy contrast in volume. The siphon station the executives will decide whether the distinction in the two estimated volumes is the aftereffect of an operational change or if the pipe is spilling. Operational changes can result from an adjustment in item review, change of pumps or pumping pressure, or an adjustment in temperature in view of capacity tank changes. P.Siva Nagendra Reddy, S. Nanda Kishore [2]. They implemented a security issues against the crime, gas leakage and fire break. In this planning system they have proposed system, LPG gas spilling and Rebooking of a cylinder with a ready system. This report identifies the gas, oil, fluids and alcohol, Etc. and caution surrounds people about the leakage of gas through Message. It accordingly temperature, with the goal that there is no fire break danger takes places. The one increment critical element is booking of barrel by seeing the present use of gas in our daily lives. The active, alert is sent to the customers in case of 3 conditions. When there is

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

an LPG weight of cylinders in the edge level message is sent to the householders. They accordingly give the system windows opening so that the gas goes out. Subsequently a fire disaster does not take place in the developed framework.

The main scope of this objective is to plan the system by alarming the people is to use Gas sensor MQ5 to detect the gas explosion. The alert mechanisms like ringing bells, A rectifier and a message is sent to the authority mobile user with the help of Global system for mobile communication. The controller will control all the devices. The Microcontroller has low consumption and price too. Abhishek Gupta [4]. They have implemented this method with an Arduino primarily based Gas escape detector system meets the security necessities, Which area unit given within the paper. The check result area unit obtained exploitation fuel primarily based lighter as a replicate of an LPG Gas source. The check result verifies the effectiveness and economical operation of the Prototype of detective work low and high gas escape levels and motor vehicle shut-off the gas Supply associated alert the user by providing a sounding alert alarm. The projected Arduino primarily based gas escape detector provides high and quick Response than the manual operation throughout the essential things. The system will be put in for detective work the assorted escaping gases at residential Hotel restaurants, alternative business commodities and industrial space to avoid Imperiling of Human lives. M. Alexander Baranov [5]. In this paper they have implemented a wireless based system that can be system for flammable gas leak watching in flat building is given. The system consists of autonomous gas sensors, actuators, routers and a gateway and is connected to the web. The design of the system permits to regulate the quality of Nodes betting on the quantity of residences. The gas Concentration knowledge is kept within the net service information on the web and might be simply accessed from any mobile device (laptop, tablet PC, good phone, etc.). The system time interval is decided by the duty cycle of paraffin concentration measurements and might vary in numerous tasks. The peculiarity of the system is in relocation of network organization, event management and knowledge storage functions to an internet service in interaction with wireless sensor network. To increase the autonomous life we tend to progress to use energy sources For parts of the wireless system within the near future. M.R Pruthvi Veena.M [6]. They proposed the method of an outpouring and cylinder thieving could be a major drawback round-faced by the folks. For safety purpose, we tend to develop a centralized cylinder thieving detection the system Whenever a thieving happens can, it will generate associate alert associated a message, will send to the owner by that the cylinder thieving are often prevented manually and mechanically we will able to close up the cylinder of the L293D motor. The Microcontroller is that the heart of this project to that the RFID reader and tags are a unit interfaced that area unit kind of like the Regulator of the cylinder. Each of the cylinder has distinctive RFID TAG through that the cylinder are often known.

The RFID reader is connected to Microcontroller that successively is connected to GSM therefore, Whenever a thieving occur, it will send associate tuned in to the user. C.Nagarajan et al [3,11,17] proposed a system for avoiding the risks of disasters to be occurring mainly at home, working places. For this system they development they used Arduino board and Mobile phone which have features like Google maps, Google cloud messaging and messages, Global positioning system. In this they are used 3 pivots Accelometer to identify the person in case if the person fall has happened, Gas sensor is used to detect the LPG gas and GPS is used to track the person with the help of internet, In accordingly if any disasters take places message notification is sent to caretakers to take measures. This all are implemented to make a smart home and provide safety to citizens living conditions for ages people. N. Sushma Rani [8]. In this paper they implemented a system based upon the Android application to investigate gas detection by robot technology. They developed an android based framework which receives the date from the robot by Bluetooth. When the gas spilling takes place we can also control the robot movements by Bluetooth with makes direction and voice alert. The different applications are used among an element of mobile phones, Bluetooth controls the robot. They can develop the system can conveniently in synthetic enterprises, different working places, home and coal mine territories. By this robot they can save any human beings from the disasters to not to be taken places. Hence, by the robot application they developed this system to take certain measures about the disasters to be occurring.

III. PROPOSED METHODOLOGY

The proposed framework is produced utilizing the Raspberry Pi 3. Raspberry Pi may be a digital computer which might created and adjusted completely different ways it permits us to run different projects and moreover bolster

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

distinctive peripherals that are to ways in which it permits us to run different projects and moreover bolster numerous peripherals which are to be utilized in our framework MQ Sensors are introduced on the point of the LPG Supply to acknowledge the spillage of gas, Once the button edge is achieved it will send an alarm message to power versatile, The message is send to Email.LED is cautioned while gas spillage takes places and furthermore. The sound sign is associated with the framework. This data is kept in webpage utilizing it. The whole working on the framework can be accomplished by executing a python code and by introducing the required sensor libraries.

IV. SYSTEM DESIGN FOR IOT BASED LPG GAS LEAKAGE SENSING AND ALERTING SYSTEM




Fig 1: LPG Gas Leakage Sensing and Alerting System

The fig1 gives the brief description about the prototype. And also explain about the smart techniques that are used here.

V. OPERATIONS OF MODULES

A. RASPBERRY PI 3

The raspberry pie 3 is introduced in our project show, which bolsters UNIX system and python language. Different devices are connected to Raspberry pie to detect the spilling of gas. Interfacing the modules that contain four stick Breadboard, session initiation protocol, one I/O for Microcontroller. When gas spilling takes places gas gives an alert the Microcontroller to send the message to the authority and Gas agency. It looks like a credit card size. It contains 40 pins of general purpose input/output pins they connect with 5V rail. GPIO offers digital input/output. These pins are interfaced with raspberry pie. The pi controls the LED turns ON/OFF. Out of 40 pins 26 pins provide different functions.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020



Fig I(A):Raspberry pi3

S. NO	GAS SENSORS	GAS TO DETECTED
1	MQ2	Methane, Butane, Propane, LPG, Smoke
2	MQ3	Alcohol, Grain Alcohol, Smoke
3	MQ4	Methane, Fuel and Alkane series
4	MQ5	H ₂ ,LPG,CH ₄ ,CO,Alcohol
5	MQ6	ISO-butane, Fuel and LNG
6	MQ7	Carbon monoxide
7	MQ8	Hydrogen
8	MQ9	LPG, CO,CH ₄ .

Table1.Different Types Of Sensors

B.MQ5 Gas Sensor:

This is the MQ5 gas detection module which is mostly used for investigation gas spilling in the particular area this sensor module. It is mainly used to judge the concentration. It is mainly recognizing LPG, coal, Alcohol Etc. It is mainly contained 6 pins,4 pins are used to get signals when spilling happens. The other 2 pins are not used. The four pins are Digital output ,Analog output, VCC and GND. The VCC contain a positive power supply in between (2.5V to 5.0V).



Fig I (B):MQ5 Gas Sensor Features of MQ5 Sensor

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

- High affect ability to LPG, gaseous petrol, Town gas
- Small affect ability to liquor, smoke.
- Fast Reaction
- Stable and long life
- Simple drive circuit.

C. Buzzer:

A Buzzer is a sound gadget which creates sound allocated to it. It will alarm around the citizens when the gas spilling occurs. There are two fundamental kinds of buzzer: Active and Passive.



Fig I(C):Buzzer

D.AUDIO INDICATION

At the point when gas spilling happens a sound sign as "Gas is Leakage" is cautioning the neighbors about the spilling of gas.

E.LED

Light Emitting Diode is a diode which contains 2pins, one negative and other positive pins are present. The long leg pin is positive and the short leg is negative pin and transmits light which current flow through it. When gas spilling occurs LED will be turned ON and glow.



Fig I(E):Light Emitting Diode

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

S.NO	Test Condition	LED	Buzzer
1	No Gas Spills	Off	Off
2	Gas spills	Glow	Sound

Table2. Test Condition for LED and Buzzer

F. SYSTEM DESIGN SOFTWARE

The Software coordinated with LPG Gas Leakage detecting and cautioning System utilizes python 2.7.15 software. System programming is made out of implanted c language and application program. Python joins astounding force with clear sentence structure. It has modules, classes, exemptions, exceptionally abnormal state dynamic information types, and dynamic composing. There are interfaces to numerous framework calls and libraries, just as to different windowing frameworks. New inherent modules are effectively written in C or C++ (or different dialects, contingent upon the picked execution). Python Language uses is in addition used an associate augmentation language for applications and Written in several dialects that require a straight forward to utilize scripting or mechanization interfaces.

VI. WORKING DESCRIPTION

The working of any propelled framework is for the most part subject to the Raspberry-pi, which the whole working of the gadget. In this situation the Raspberry-pi acts like a restrictive switch. It performs two arrangements of activity relying on the present condition.

At the point when gas spilling is more than sensor value ($>700\text{ppm}$ or $<700\text{ppm}$) at that point ready message is sent to a separate email specialist with specific sensor esteem and furthermore LED shines and alarm the neighbors about the gas spilling. It triggers the bell rings and furthermore sound sign as "Gas Leakage Detected" with specific sensor esteem and to show the message "Gas Leakage Detected" when the spillage of the gas is distinguished by the sensor ($>700\text{ppm}$). The other activity is to show the message as "LPG GAS SENSOR" when the spillage of the gas is identified by the sensor ($<700\text{ppm}$). On the off chance that the sensor recognizes the nearness the gas in the region the Gas application. It will send "Gas Leakage Detected" message to the pertinent expert and organization with individual area. Gas application is incorporated into this gadget to make the partners mindful about the spillage of gas occurring at their home in their nonappearance so vital activities can be executed quickly to keep a mishap. Consequently Buzzer and LED ON/OFF procedures is worked through the web page and show "LPG Gas Detected Value" in cellular phone and computer.

VII. RESULT AND DISCUSSION

Here the MQ5 sensor is assigned in this channel. The figure below shows the demonstrates the trial setup of the framework.. The setup gives brief data about the interfacing of segments to the Raspberry pi. We guarantee you that the planned technique will fulfill the client's prerequisites. It gives the sign in less time contrasted with the best strategies.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020




Fig 3: Overall Hardware Setup.

In figure 3 demonstrates the general equipment setup and associations in relating port pins. When gas discharge is on the far side the edge worth LED glow and Buzzer rings. An Alert message is sent to Gmail, user mobile and Gas Agency.

Output for Gmail When Gas is Detected:

```
Python 2.7.9 Shell
File Edit Shell Debug Options Windows Help
Python 2.7.9 (default, Sep 17 2016, 20:26:04)
[GCC 4.9.2] on linux2
Type "copyright", "credits" or "license()" for more information.
>>> ===== RESTART =====
>>>
smtp.gmail
ehlo
starttls
reading mail & password
from
successfully sent the mail
>>> |
```

Fig 4: Message is sent

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020



Fig 5: Received Message to the Gmail

The Fig 4 and 5 speaks to yield when the sensor recognizes gas past a breaking point the alert message is sent to Gmail.

Output for User Mobile When Gas is Detected:



Fig 6: SMS indication on user mobile phone.

The Fig6 speaks to yield once the sensing element acknowledges gas past a snapping point the alert message is distributed to users.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

Output Message Received to Gas Agency When Gas is Detected:




Fig 7: Received Message to the Gas Agency.

The Fig7 speaks to yield once the device acknowledges gas past a threshold point The alert message is shipped to Gas Agency with the location of the address.

Gas Leakage Detection Displayed through Webpage:

The LED and Buzzer ON/OFF procedures is worked through the web page and show "LPG Gas Detected Value" in cellular phone and computer.




Fig 8: Gas Leakage Detection Displayed through Webpage.

The Fig8 speaks to yield Gas Leakage Detection Value is Displayed and LED, Buzzer ON/OFF procedures can be operated through the web page.

VIII. SUMMARY AND CONCLUSION

From the accomplishment of this examination, the accompanying can be reasoned.

- (i) The configuration will discover the extraordinary use of a domain where anyone is, or individuals are deaf and dumb of the red LED shine with extreme danger signs.
- (ii) In the instance of the blind, the buzzer ready will offer a method for advising the previous of an approaching danger.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

IX. CONCLUSION

The Developed prototype won't solely offer safety to the users against harmful gases. However, this system provides alert information to the Gas agency and other mobile when gas spilling occurs. It also gives an alert indication to buzzer and LED. And also the operation of Buzzer/LED through webpage takes place. When comparing to the other system, it creates a less expensive and safety to the citizens also provide fast alerting Techniques compared to the other prototype.

FUTURE SCOPE

The conduct of the gases is reliant on the Temperature and Humidity of the air around. A gas at certain focus probably won't be combustibile at low temperature yet may have touchy nature at high temperature. Therefore expansion of a Temperature and Humidity Sensor will be exceptionally useful. The other alteration which can be actualized in this gas spill locator is utilizing a tripped circuit which will trip off the principle supply once the gas spill is distinguished. During a gas spill it is unsafe to switch any apparatuses as it might start and this tripper circuit helps to reduce the electrical risks that can be caused because of a gas release. Alongside the stumbling off of the primary supply it is especially important to kill the gas controller so no further spillage of the gas happens. A robot has been utilized in trading human for taking care of different errands in a risky and perilous working environment where human life may in danger. A portable gas detecting robot can be built to detect the spillage of gas through pipelines as the robot can proceed onward a track which is arranged along the length of pipeline.

REFERENCES

1. R.Srinivasan, G.Neelakrishnan, D.Vinoth and P.Iraianbu, "Design and Implementation of Novel Three Phase Multilevel Inverter for Smart Grid" International Journal of Multidisciplinary Educational Research, Jan 2020, Volume 9, Issue 1(3)
2. G. Neelakrishnan, D. Chellapandi, R. Sathesh, K. Tamil selvan, "Design and control of low Frequency Ripple Free Current for quasi Z-Source PV Gird Connected Inverter" World Journal of Engineering Research and Technology, 2019; 5(2):448-460.
3. C.Nagarajan and M.Madheswaran - 'Stability Analysis of Series Parallel Resonant Converter with Fuzzy Logic Controller Using State Space Techniques' - *Electric Power Components and Systems*, Vol.39 (8), pp.780-793, May 2011
4. G. Neelakrishnan, D. Chellapandi, R. Sathesh, K. Tamil selvan, "Design and Analysis of Multiplexer DC-DC Converter" World Journal of Engineering Research and Technology, 2019; 5(2):484-499.
5. G. Neelakrishnan, M. Kannan and D. Vinoth, "Hybrid Power System for PSO Tuned Load Frequency Control", World Journal of Engineering Research and Technology, 2018; 4(6):221-232.
6. M.Kannan and G.Neelakrishnan, "Advanced Electricity Usage via Power Line Communications", Global Research and Development Journal for Engineering, April 2018: 252-257
7. M.Kannan, G.Neelakrishnan et.al, "High Efficiency Transformer less Inverter for Single-Phase Photovoltaic Systems using Switching Converter", International Journal of Advanced Research in Electronics and Communication Engineering, November 2013; 2(11): 894-899.
8. D.Vinoth, R.Saranya and G.Neelakrishnan, "A Wide Area Monitoring System Base Load Restoration Method", International Journal of Applied Engineering Research, 2015; 10(9): 8898-8902.
9. G.Neelakrishnan, P.Ganeshkumar and D.Vinoth, "Power Quality Improvement Using Multi Level Inverter Operated in Grid Connected Mode" International Journal of Applied Engineering Research" 2015; 10(9): 8922-8928
10. G.Neelakrishnan, V.Sundarajan and D.Vinoth, "Simplified Reactive Power Control for Single-Phase Grid-Connected Photovoltaic Inverters", International Journal of Applied Engineering Research" 2015; 10(9): 9051-9055.
11. Dr.C.Nagarajan, G. Neelakrishnan, V.Sundarajan, and D.Vinoth, "Simplified Reactive Power Control for Single- Phase Grid-Connected Photovoltaic Inverters" International Journal of Innovative Research in Science, Engineering and Technology, May 2015; 4(6): 2098-2104
12. G.Neelakrishnan, M.Kannan, S.Selvaraju and T.Keerthana, "An Improved AC to DC Flyback Converter with Power Factor Correction fed PMDC Motor", International Journal of Research in Information Technology, January 2014; 2(1): 216-223.
13. M.Kannan, G.Neelakrishnan and S.Selvaraju, "A High Efficiency Power Factor Correction Scheme based AC/DC Converter Fed PMDC Drive", International Journal of Research in Advent Technology, February 2014; 2(2): 131- 135.
14. G.Neelakrishnan, M.Kannan, R.Srinivasan and D.Vinoth, "AC/DC SEPIC Converter for Non-Linear Controller", International Journal of Advanced Research in "Electrical, Electronics and Instrumentation Engineering, November 2014; 3(11): 13266-13273
15. M.Kannan, R.Srinivasan and G.Neelakrishnan, "A Cascaded Multilevel H-Bridge Inverter for Electric Vehicles with Low Harmonic Distortion", International Journal of Advanced Engineering Research and Science, November 2014; 1(6): 48- 52.
16. S.Selvaraju, K.Vijayraj, K.Jaganraj, M.Kannan and G.Neelakrishnan, "Hexagram-Converter based STATCOM for Integrating Twelve Bus Systems with Wind Farm", International Journal of Engineering Research and Technology, October 2013; 2(10): 34193425.
17. C.Nagarajan and M.Madheswaran - 'Stability Analysis of Series Parallel Resonant Converter with Fuzzy Logic Controller Using State Space Techniques' - *Electric Power Components and Systems*, Vol.39 (8), pp.780-793, May 2011



ISSN(Online): 2319-8753
ISSN (Print): 2347-6710

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 9, Issue 3, March 2020

18. G.Neelakrishnan, M.Kannan, S.Selvaraju, K.Vijayaraj, M.Balaji and D.Kalidass, "Transformer Less Boost DC-DC Converter with Photovoltaic Array", IOSR Journal of Engineering, October 2013; 3(10): 30-36.
19. R.Baskar, R.Jayaprakash, M.Balaji, M.Kannan, A.Divya and G.Neelakrishnan, "Design of Nanoscale 3-T DRAM using FinFET", IOSR Journal of Electrical and Electronics Engineering, November-December 2013; 8(1):1-5.