

# **An Autonomous Agrobot Vehicle for Greenhouse Cultivation**

Sivaranjani s<sup>1</sup>, Sparsha S D<sup>2</sup>, Vidhya M<sup>3</sup>, Vinodhini C<sup>4</sup>, Mannivannan P<sup>5</sup>.

U.G. Students, Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India<sup>1,2,3,4</sup>

Associate Professor, Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India<sup>5</sup>

**ABSTRACT:** Lately, individuals' advantage has developed for the improvement of the self-ruling vehicles like robots in the farming. In excess of 40% of the populace in over the globe picks farming as the essential occupation. This undertaking means to deliver a multifunctional farming robot. The tropical atmosphere of India, which makes it hard for the cultivators to work for extensive stretches of time. Accordingly making issues, for example, wastage and practical misfortune. The significant test looked by the cultivators is work accessibility, this agrobot lessens work cost up to almost 50%. The current horticultural robots performs fundamental rudimentary capacities like collecting, planting and watering. Accordingly, utilizing an agrobot gives an ideal answer for the cultivators in such conditions. The created agrobot is controlled by an Arduino microcontroller and a hub MCU which plays out a couple of errands at a specific time slip by. The venture intends to ensure the protection of individuals and planning an agrobot vehicle constrained by portable application for different horticultural exercises, for example, furrowing( till the dirt ), seeding, planting samplings, water system and detecting moistness saltiness and sand pH levels inside the nursery.

**KEYWORDS:** Wifi, Agrobot, ATMEGA 328.

## **I. INTRODUCTION**

As of late, individuals' advantage has developed for the advancement of the independent vehicles like robots in the horticulture. In excess of 40% of the populace over the globe picks horticulture as the essential occupation. Horticultural mechanization begins with some fundamental thoughts making an advancement in rural strategies. It limits the human endeavors in the MODERN WORLD. Presently a day's horticultural robotization is created by utilizing Wireless Technology. Remote correspondence in agrarian mechanization begins with Bluetooth, Wifi, gsm and GPS. In light of the Requirement and Application correspondence is conveyed in Projects. Presently a day's Indoor limitation Technologies are created, limiting work for people. This venture means to control their agrobot with a portable application for a different water content in the dirt inside the nursery. This venture additionally points in to give cultivators security to control their agrobot with a versatile application for different horticultural exercises.

## **II. PROPOSED SYSTEM**

The multipurpose independent agrobot vehicle which can be controlled through Mobile application for furrowing, seeding and water system frameworks. This agrobot is controlled by an arduino and a hub MCU which plays out the assignments at a specific time pass automatically. ESP8266 module associated with either Hotspot or any Router, which has a balanced out Internet association. As per their necessities, the client can build up an association among microcontroller and water system toolbox or boring tool stash or the dirt sensor . The client ought to have versatile application that gives a simple method to assemble IoT models. At the point when the client controls the switch in versatile application, the RF signal is sent to the Cloud Server and simultaneously signal is gotten through ESP8266 board.

### III. ARCHITECTURE

To look at about the strategy where this module is arranged is clarified in Figure 1.. The Module made is a joining of hardware and programming. The gear is made using agotfeatures and is constrained by android application through cell phones is the structure.

#### A. Block diagram

The block diagram is shown in figure 1, which helps inn understanding the working principles.




Figure 1- Block diagram for agrobot

ESP8266 module associated with either Hotspot or any Router, which has a settled Internet association. The program for this proposed framework will be arranged and transferred to the controller utilizing Arduino IDE. As per their necessities, the client can build up an association among microcontroller and water system toolbox or penetrating tool stash or the dirt sensor . The client ought to have portable application that gives a simple method to fabricate IoT models. At the point when the client controls(ON/OFF) the switch in portable application, the RF(Radio Frequency) signal is sent to the Cloud Server and simultaneously signal is gotten through esp8266 board. What's more, the mentioned activity by client is finished.

#### B. Circuit Analysis

The circuit diagram is shown in figure 2,helps in analyzing the circuit with a clear thought of its working using component working and their detailed use.



Figure 2 Circuit diagram.

## 1) 12V POWER SUPPLY

The motivation behind the battery is to supply the fundamental current to the start framework. Overwhelmed lead-corrosive batteries are the most financially savvy and in past commonest footing batteries accessible. There are two fundamental sorts of lead-corrosive batteries: motor starter batteries, and profound cycle batteries. No lead corrosive battery ought to be released beneath half of its ability, since it abbreviates the battery's life. Overflowed batteries require investigation of electrolyte level and periodic substitution of water which gases away during the customary charging cycle. Generally, the vast majority of the electric vehicles use lead-corrosive batteries because of their develop innovation, high accessibility, and minimal effort.



Figure 3 Lead acid battery

Like all the batteries in the market, these have an ecological effect through their development, use, removal or reusing. On the upside, vehicle battery reusing rates top 95% inside the us . Profound cycle lead batteries are alot more costly and have a shorter life than the vehicle itself, normally requiring substitution like clockwork

## 2) BUCK BOOST CONVERTER

The buck–boost converter is a kind of DC-to-DC converter that has an output voltage magnitude that's either greater than or the input voltage magnitude.It is like a fly back converter employing a single inductor rather than a transformer. Two different topologies are called buck–boost converter. Both of them can produce a variety of output voltages, starting from much larger than the input voltage, right down to almost zero. These converters are also known as the step up and step down transformers and these names are coming from the analogous step up and step down transformer. The input voltages are step up/down to some level of quite or but the input voltage. By using the low conversion energy, the input power is adequate to the output power.

The accompanying articulation shows the low of a conversion.This is a LM2596 DC-DC buck converter step-down module with high-exactness potentiometer, fit for driving a heap to 3A with high proficiency, which can work with arduino UNO, different mainboards and essential modules. At the point when the yield current keeps more prominent than 2.5A (or yield power more prominent than 10W) , please include a conductor subsequently . The working activity of the DC to DC converter is that the inductor inside the information opposition includes the unforeseen variety inside the information current. In the event that the switch is ON, at that point the inductor feed the vitality from the info and it stores the vitality of attractive vitality. On the off chance that the switch is shut it releases the energy.The yield circuit of the capacitor is accepted as high adequate than the time steady of a RC circuit is high on the yield arrange.

The tremendous time consistent is contrasted and the exchanging time frame and affirm that the consistent state might be a steady yield voltage  $V_o(t) = V_o(\text{constant})$  and present at the heap terminal. Right now essential transistor is turned ON constantly and for the second transistor the square flood of high recurrence is applied to the entryway terminal. The subsequent transistor is in directing when the on state and in this way the information current be expected the inductor L during that time transistor. The negative terminal energizing the

**Organized by**

**Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India**

attractive transition round the inductor. The D2 diode isn't led in view of the anode is on the potential ground by profoundly leading the subsequent transistor.

### 3) ARDUINO UNO R3




Figure 5 Arduino uno rev3

The Arduino Uno is a microcontroller board dependent on their datasheet. They have 14 computerized info and yield pins. Here 6 pins are utilized as Pulse Width Modulation (PWM) for example yield and another 6 can be utilized as simple sources of info. Arduino board can be associated with USB link or likewise by the force jack. It begins with the assistance of AC to DC connector or battery. The outside force supply can be worked at 6 to 20 volts. In the event that the inventory of outside force is more than 12v, at that point, the voltage controller comes overheat and influences the board. It expands the range from 7 to 12 volts as it were. The uno can be modified by the Arduino Software. Arduino uno having the length of 2.7 and 2.1 inches. It additionally having the recollections like EEPROM and SRAM with KBs..

### 4) NODEMCU

NodeMCU is an open-source firmware and improvement pack that causes you to model or fabricate IoT item. It incorporates firmware which runs on the ESP8266 Wi-Fi SoC from Espressif Systems, and equipment which depends on the ESP-12 module. The firmware utilizes the Lua scripting language. It depends on the ELUA venture, and based on the Espressif Non-OS SDK for ESP8266

MCU represents Microcontroller Unit - which truly implies it is a PC on a solitary chip. A microcontroller contains at least one CPUs (processor centers) alongside memory and programmable info/yield peripherals. They are utilized to computerize car motor control, implantable medicinal gadgets, remote controls, office machines, apparatuses, power instruments, toys and so forth.




Figure 5 Node mcu

The pin portrayal is given underneath. As Arduino.cc started growing new MCU sheets dependent on non-AVR processors like the ARM/SAM MCU and utilized in the Arduino Due, they expected to adjust the Arduino IDE with the goal that it would be generally simple to change the IDE to help interchange toolchains to permit Arduino C/C++ to be accumulated for these new processors. As Arduino.cc started growing new MCU sheets dependent on non-AVR processors like the ARM/SAM MCU and utilized in the Arduino Due, they expected to adjust the Arduino IDE with the goal that it would be generally simple to change the IDE to help substitute toolchains to permit Arduino C/C++ to be gathered for these new processors.

### 5) MOTOR DRIVER

The motor driver is a coordinated solid circuit in a 15-lead Milliwatt and PowerSO20 bundles. It is a high voltage, high ebb and flow double full-connect driver de-marked to acknowledge standard TTL rationale level sand drive inductive loads, for example, transfers, solenoids, DC and venturing engines. Two empower inputs are given to empower or debilitate the gadget freely of the in-put signals. The producers of the lower transistors of each scaffold are associated together rand the comparing outside terminal can be utilized for the association of an outer detecting resistor. An extra Supply input is given with the goal that the rationale works at a lower voltage.



Figure 6 soil sensor

### 6) SOIL SENSOR

The Soil Moisture Sensor utilizes capacitance to quantify dielectric permittivity of the encompassing medium. In soil, dielectric permittivity is an element of the water content. The sensor makes a voltage relative to the dielectric permittivity, and in this manner the water substance of the dirt. The sensor midpoints the water content over the whole length of the sensor.



Figure 7

There is a 2 cm zone of impact regarding the level surface of the sensor, yet it has almost no affectability at the outrageous edges. The Soil Moisture Sensor is utilized to gauge the loss of dampness after some time because of dissipation and plant take-up, assess ideal soil dampness substance for different types of plants, screen soil dampness substance to control water system in nurseries and improve bottle science tests.

#### IV.RESULT AND DISCUSSION

The venture framework with the assistance of iot based portable application. So we can accomplish our point for example different agrarian exercises, for example, furrowing (till the dirt), seeding, water system and soil mugginess level inside the nursery through the self-ruling agrobot

##### A. Result

The charts is appeared underneath are the equipment working piece of the venture and the product portable application (screen capture of the versatile application is given in the picture) used to control the equipment part is appeared




Fig.9. Equipment Part

##### B. Future Enhancement

This idea can be later improved by including numerous highlights. As, the present framework can be overhauled with programmed collecting frameworks which will help the purchaser reaping the harvest inside the nursery.

**International Journal of Innovative Research in Science, Engineering and Technology**  
*An ISO 3297: 2007 Certified Organization* *Volume 9, Special Issue 1, March 2020*  
**8<sup>th</sup> National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '20)**  
**18<sup>th</sup>-19<sup>th</sup> March 2020**

**Organized by**

**Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India**

## REFERENCES

1. Ashish Lalwani, mrunmaiBhide, S. K. Shah, A Review: Autonomous Agribot For Smart Farming, 46th IRF International Conference, 2015
2. AkhilaGollakota, M.B.Srinivas, Agribot-A multipurpose agricultural robot, India Conference (INDICON), IEEE, 2011.
3. Sandeep Konam, "Agricultural Aid for Mango cutting (AAM)," Electronics & Communication Engineering, RGUKT, R.K. Valley Kadapa, India, 978-1-4799-3080-7 IEEE 2014.
4. Rasin, Z., H. Hamzah and M.S.M. Aras, 2009. Application and evaluation of high power Zigbee based wireless sensor network in water irrigation control monitoring system. Proceedings of the IEEE Symposium on Industrial Electronics and Applications, Volume, 2, October 4-6, 2009, Kuala Lumpur, Malaysia, pp: 548-551.
5. M. priyadarshini, Mrs. L. Sheela, "Command based self-guided digging and seed sowing rover",International Conference on Engineering Trends and Science & Humanities, ISSN: 2348 – 8379, ICETSH-2015.
6. Shivaprasad B. S., Ravishankara M. N.,B. N. Shoba, "Design and implementation of seeding and fertilizing agriculture robot", International Journal of Application or Innovation in Engineering & Management (IJAIEM), Volume 3, Issue 6, June 2014.