

Protective Coloration Technique Based Multifunctional Army Robot

Subhash.J¹, Ranjith.P², Ravikumar.R³, Srinath.B⁴, Surendran.S⁵

Assistant Professor, Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India¹,

U.G. Student, Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India^{2,3,4,5},

ABSTRACT : These days, numerous costs are made inside the part of safeguard in embracing crude safety efforts to shield the fringe from the trespassers. Some military associations take the assistance of robot inside the risk inclined regions which are not unreasonably compelling when done by armed force men. These military robots are limiting with the camera, sensors, locator and video screen. the most goal of our framework is to encourage covered including PIR sensor to follow the gate crashers. Along these lines the proposed framework additionally utilizes IR sensor for hindrance location.

KEYWORDS: Camera, Sensor, Video screen, Camouflage, Blue-tooth

I. INTRODUCTION

A robot is a programmed robot frequently looking like a person's or creature. Current robots are normally a guided by a PC infection or electronic hardware. Robots have supplanted people in performing dreary and perilous undertakings. the use of robots in military battle raises moral concerns. the odds of robot self-governance and potential repercussions are tended to in fiction and should be a reasonable worry inside the up and coming days. Fundamentally Army Robot is equipped for performing undertakings like headway, detecting the hurtful gas, detecting the people underneath the surface, metal recognition. Armed force robot is an independent robot involving remote camera which might be utilized as a government operative and Bluetooth wont to control it remote. This military robot is increasingly proficient contrasted with the troopers. Excellency of this robot is in being worked remote from re-bit which offers no hazard to the officer lives. Robots are improved to be vigorous and sturdier giving the assurance of progress inside the risk inclined condition. The most point of the paper is to execute a Camouflaged innovation based Wireless multifunctional Army Robot which can be controlled through advanced mobile phone utilizing Blue-tooth. The disguise showed screen make the robot difficult to find out. Encompassing shading matches with the screen make the robot difficult to determine. From one perspective, to understand these objectives, we utilized a LED (RGB) which may diffuse uniform hues, coupled to sensors which will absolutely distinguish ground hues. This robot is proficient contrasted with the fighters. Excellency of this robot is in being worked remote from remote which offers no hazard to the fighter lives. Robots are upgraded to be powerful and sturdier giving the assurance of accomplishment inside the peril inclined condition. The Camouflage innovation based robot are frequently controlled through advanced cell. This robot is implied in such how that it can repeat the shading freely at different regions every territory being able to breed shading with explicit spots of the base surface, which grant the robot to demonstrate as a checkerboard of numerous hues – the changed hues it rolls over. The route and motion of the model are regularly controlled through advanced mobile phone utilizing blue-tooth module. On the contrary hand, we likewise made a framework which may get and disentangle data got from the Smart telephone utilizing IOT to additionally guide engines which progressively drive the robot any necessary way.

II. HARDWARE SPECIFICATION

A. RASPBERRY PI PROCESSOR

The activity of the gadgets constrained by Raspberry pi processor. The Raspberry pi processor may be a lone board PC used for controlling the movement. It controls signal stream in transmitting and getting signal from the gadgets. It contains 40 pins including input, yield, power supply and ground pins. It contains pin gathering of intensity source, correspondence interface, input/yield pins, Pulse Width Modulation, External interferes. Force source pin contains power yield, +3.3V-power yield, GND pin. Correspondence interface pin bunch contains UART, SPI, TWI pins. General Asynchronous Receiver Transmitter (UART) is for interfacing various contraptions and sensors. Sequential Peripheral Interface (SPI) is for correspondence with outer sheets or different peripherals. Two Wire Interface (TWI) is for associate peripherals. Info/Output pin play out various capacity. All the I/O pins are utilized for hinder inside the board. The Operating temperature of the board is - 40 degree Centigrade to +85 degree Centigrade. it's the Operating voltage of three .3V. It contains interior RAM of 1Gbytes and non-unpredictable capacity of 16Gbytes. It additionally has the clock recurrence of 1.2GHz. The exceptional sort connector inside the board are Ethernet, Memory card space, Display connector, Camera connector, Video yield, Audio yield and USB.

B. PIR SENSOR

The Passive Infra-Red (PIR) sensor distinguishes the alterations in object by infrared level assessing made by improvement of article. it's a Pyroelectric sensor and it produces electric charges when displayed to radiation. it's stock voltage of 5V. The PIR sensor contains three pins. PIN 1 is that the Drain and it related with 5V DC positive stock. PIN 2 is that the source terminal and it's related with 47K or 100K resistor. PIN 2 recognizes the IR sign and it's the yield pin of sensor. PIN 3 is related with Ground.

C. GAS SENSOR

The Gas sensor sense the gas present inside nature. it's high affectability to LPG, Propane and Smoke. By changing the opposition produce a potential distinction upheld the convergence of gas. The Gas sensor sense the gases by the loop inside it and opposition of the layer changed. The Gas sensor has 6 terminals. The simple yield pin Ao, advanced yield pin Do, Vcc and Ground GND go about as information or yield terminal. Staying 2 terminals warmth of the loop of the sensor. The Vcc and GND is for power supply. The Digital yield pin gives yield in rationale of high or low. The Analog yield gives nonstop voltage bolstered gas focus inside the earth.

D. CAMERA

Camera is used for consistent data interpretation, which the transmitting and tolerating of data is done by RF trans beneficiary. The camera contains inbuilt RF trans collector. Camera is appended to show the continuous information remote through RF. There are two cameras utilized, one for the forward perception and another for show the ground surface.

E. METAL DETECTOR

Metal vicinity finder sensor gadget recognize the metal items between 1cm to 7cm. Discovery of metal item can be demonstrated by LED or Buzzer. It is utilized to discover concealed metal items or close by metal articles. It has oscillator and curl that transmits electromagnetic field. The metallic item makes changes in the electromagnetic field. Location of Eddy current misfortune that created by high recurrence demonstrates the metal item. The separation of metal article changes the yield current. Current stream is most extreme when metal is close and the present stream is least when the metal article is far. The stockpile voltage is 5V DC and supply current is 50mA. The Detection extend is up to 7cm from the metal item.

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

F. MOTOR DRIVER

Motor driver is utilized for the velocity driven by the force supply of 12V. The activity of the engine driver is constrained by smaller scale controller. The development order is given by the client utilizing advanced mobile phone. The smaller scale controller gets the sign from client and imparts the sign to engine driver for velocity.

III. BLOCK DIAGRAM




Fig.1 Block diagram

IV. IMPLEMENTATION

The framework constrained by the Raspberry pi processor. Force supply of 5V is given as info. The headway is finished by the engine driver and it is constrained by Raspberry pi processor. Gas sensor is associated with power supply and sign pin of the processor for imparting sign to the processor. At the point when a poisonous gas or smoke is detected, it imparts sign to the processor. PIR sensor additionally associated with power supply and GND. This sensor identifies the development and imparts sign to the processor. The camera associated with power supply and GND and imparts sign to the processor. The Smart telephone and camera associated by processor by means of blue-tooth. The headway is likewise controlled utilizing cell phone. Another camera shows the genuine ground surface where it will be proceeding onward, thus being covered. These military robots are keeping with the camera, metal discoverer, video screen and sensors. During motion it get covered and the front camera gives the ongoing information process and the advanced cell associated with processor utilizing blue-tooth module and constrained by android application in PDA.

V. CONCLUSION

The protective coloration strategy robot can be constrained by advanced mobile phone has been effectively practiced driven by android application and utilizing Blue-tooth. Camera is associated with show the continuous data remote through RF. Gas sensor to distinguish smoke or lethal gases. Metal sensor identifies metal arm or weapon if any metal articles around it. PIR sensor recognizes the human interlopers utilizing the infra-red waves. Right now utilized camera to transmit the information from outskirts to the watch region for compelling information handling. Cover is fundamental in armed force strategic. In addition, in the fundamental division use for seeing the fringes and foe zones. It is savvy. It is conceivable to give 24 hours security in protection application.

REFERENCES

- [1] P. Hymavathi, T. Jyothy "Surveillance Alive Human Detection Robot using Zigbee Technology"SSRG International Journal of Electronics and Communication Engineering (SSRG-IJECE) – volume issue 4 June 2014.
- [2] Akash Ravindran and AkshayPremkumar "CAMOFLAGE TECHNOLOGY"International Journal of Emerging Technology in Computer Science & Electronics (IJETCSE) ISSN: 0976-1353 Volume 8 Issue 1 –APRIL 2014.
- [3] Premkumar .M "UNMANNED MULTI-FUNCTIONAL ROBOT USING ZIGBEE ADOPTER NETWORK FOR DEFENSE APPLICATION" International Journal of Advanced Research in Computer Engineering & Technology (IJARCET)Volume 2, Issue 1, January 2013.
- [4] Robotic Systems Joint Project Office- Unmanned Ground Systems Roadmap by Materiel Decision Authority (MDA):Macro USA, McClellan, CA, February2012.
- [5] RF Controlled Terrorist Fighting Robot By Abhinav Kumar Singh., NilayaMitashShanker., Anand Prakash Yadav, International Journal of Computer Science & Communication, vol. 1, No. 1, January-June 2010, Pp. 109-112.
- [6] 7th Sense: A Multipurpose Robot For Military by L.Srinivasavaradhan., G.Chandramouli.,Mr.A.G.Maniprashanna MEMSTECH'2009, 22-24 April, 2009, Polyana - Svalyava (Zakarpattya),Ukraine.
- [7] . Analysis And Design of Human-Robot Swarm Interaction in Firefighting By Amir M.Naghsh., JeremiGancet., AndryTanoto., Chris Roast Proceedings of the 17th IEEE International Symposium on Robot and Human Interactive Communication, Technische Universität München,Munich, Germany, August 1- 3, 2008.
- [8] Landmine Detection Technologies to Trace Explosive Vapour Detection Technique, C.Kapoor1 and G.K. Kannan, Defense Science Journal, Vol. 57, No. 6, November 2007, Pp. 797-810, 2007, Desidoc.
- [9] Robert L.Boylestad and Louis Nashelsky, "Electronic Devices and Circuit Theory", 8th Edition, 2006.
- [10] George Bekey," Autonomous Robots: From Biological Inspiration to Implementation and Control", MIT Press, Cambridge, MA, 2005.
- Mr. M. Arun Kumar, Mrs. M. Sharmila "Wireless Multi Axis ROBOT for Multi-Purpose Operations", Department of ECE, SVCET & JNT University Anantapur, India.
- [11] Pete Miles & Tom Carroll, Build Your Own Combat Robot,(2002)
- [12] Dr. S. Bhargavi, S. Manjunath, "Design of an Intelligent Combat Robot for war fields", Department of Electronics and Communication Engineering, S.J.C.I.T, Chikballapur, Karnataka, India