

DIY Sensor-Based Automatic Monitoring System for Hydroponics

Subhash.J¹, Ranjith.P², Ravikumar.R³, Srinath.B⁴, Surendran.S⁵

Assistant Professor, Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India¹,

U.G. Student, Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India^{2,3,4,5}

ABSTRACT: Hydroponics might be a strategy for developing plants without utilizing soil. This procedure employs mineral supplement arrangement in a water dissolvable, permitting the supplement take-up procedure to be more proficient than when utilizing soil. Hydroponics is appropriate for business nourishment creation. Hydroponics has a few focal points over a dirt medium. Dissimilar to plants developed in soil, plants developed during a hydroponics framework don't find a workable pace pull structures to search for supplements. It is simpler to check and change pH levels. In hydroponics strategies, plants are brought up in an idle and flawlessly pH adjusted developing medium where the plants just find a workable pace vitality to amass supplements from the roots. The vitality spared by the roots is better spent on leafy foods creation. The rate and result of substance responses occurring in water, and it's thusly helpful to comprehend the corrosiveness of the water, regularly estimated by methods for a pH sensor. Water level sensor is utilized to recognize the degree of hydroponics framework that can stream in one of a kind. Hydroponics supplement arrangements are made of mineral salts disintegrated in water. The quality of the supplement's answer are regularly identified by observing the electrical conductivity. Temperature and stickiness sensor use to gauge the nursery condition. GSM module is utilized to pass on the hydroponic framework messages to the client normally. The framework was fruitful in filing information continuous for client get to.

KEYWORDS: Hydroponics, pH sensor, Arduino, Liquid level sensor, Temperature sensor

I. INTRODUCTION

People require air, nourishment, water, and measurable in order to endure. These things are not interminable in nature and in this way people are needy upon the advancement of land territory and the conservation of biodiversity. The human populace is expanding and anticipated to grow from 7.0 billion to 9.5 billion individuals inside consequent 40 years (Sahara Forest Project, 2009). An ever-expanding interest for nourishment species is inferred, and it's assessed that nourishment creation should be multiplied to redress and supply accessibility to all or any.

"Hydroponic" characterizes as any way to develop plants by means of a medium that does exclude the utilization of soil however includes inorganic supplements or supplement arrangement. Be that as it may, mechanical advancement was excessively lacking because of deficient information about the supplements and significant expense engaged with the procedure. Notwithstanding of all, nations like USA and others were quick to receive this innovation so developing plants inside without the ideal soil required just as controlling the supplement is conceivable.

One of the fundamental standards for agribusiness, both in soil and in hydroponic, is to give all the supplements the plant needs. A few concoction components are fundamental for development and creation of plants, in sixteen components: carbon, hydrogen, oxygen, nitrogen, phosphorus, potassium, sulfur, calcium, magnesium, manganese, iron, zinc, boron, copper, molybdenum and chlorine. Among the climate referenced over, there's a division predictable with their inception: natural, C, H, O and minerals; debilitated into macronutrients, N, P, K, Ca, Mg, S, and smaller scale supplements, Mn, Fe, B, Zn, Cu, Mo, Ni, Cl. In hydroponic harvests, assimilation is regularly corresponding to the concentration of supplements inside the arrangement close to the roots, being

abundantly impacted by natural components like saltiness, oxygenation, temperature, pH and conductivity of supplement arrangement, candlepower, photoperiod and air dampness.

Other than these realities, the advancement of Hydroponics is being energized in India economically. Letcra Agritech is Goa's first indoor Hydroponics fire up that produces 1.5-2 tons of verdant vegetables of good quality and vermin free. Junga Fresh n Green, a beginning up concerning Statistics Times, India represents 7.68% GDP of the all out worldwide agrarian yield.

As per the World Population Prospects, India positions number 2 in the rundown of nations by populace. This populace is developing at the pace of 1.2% consistently. The significant need of each person is nourishment. So as to get together to the nourishment requests of this developing populace, it is important to actualize vertical planting, which will give ideal produce in a restricted space. As we probably am aware, states like Madhya Pradesh, Uttar Pradesh, Telangana, Orissa, Karnataka and Maharashtra face serious dry spell conditions. This has an unfavorable monetary effect on the agrarian division of India. As referenced in the Economic Survey of Maharashtra, there was a 2.7% decrease in the economy of farming division in 2015-16. Be that as it may, if the previously mentioned strategies are executed, the ranchers will not stay ward of the climatic changes, absence of water and difficulties looked because of fluctuating dampness conditions. As said before, the salary of a normal rancher in India is around 6426 INR, which will restrain him from actualizing such a helpful innovation.

II. HARDWARE SPECIFICATION

A. ARDUINO UNO

The least complex board to encourage began with gadgets and coding. A few sheets look a touch not quite the same as the one given underneath, however most Arduinos share greater part of those segments for all intents and purpose. Arduino might be a model stage (open-source) bolstered a simple to-utilize equipment and programming. It comprises of a circuit card, which might be customized and an instant programming called Arduino IDE, which is utilized to compose and transfer the pc code to the physical board. The key highlights are - Arduino sheets are prepared to understand simple or computerized input signals from various sensors and switch it into a yield like actuating an engine, turning LED on/off, connect with the cloud and loads of different activities. The board capacities are constrained by sending a gathering of directions to the microcontroller on the board by means of Arduino IDE. Unlike most past programmable circuit sheets, Arduino needn't bother with an extra bit of equipment (called a software engineer) in order to stack a substitution code onto the board. You can basically utilize a USB link. Furthermore, the Arduino IDE utilizes a rearranged rendition of C++, making it simpler to discover to program. Arduino gives a run of the mill structure factor that breaks the elements of the miniaturized scale controller into a progressively open bundle. Different sorts of Arduino sheets are accessible relying on various microcontrollers utilized. All Arduino sheets make them thing in like manner: they're modified through the Arduino IDE. The distinctions are bolstered the measure of sources of info and yields, speed, working voltage, structure factor and so on. A few sheets are intended to be implanted and haven't any programming interface (equipment), which you'd found a good pace. Some can run straightforwardly from a 3.7V battery, others need at least 5V.

B. WATER LEVEL SENSOR

Water sensor is intended for water level identification, which might be generally used in detecting precipitation, water level, and even fluid spillage. The water sensor to an Arduino could likewise be a legit because of identify a hole, spill, flood, downpour, and so on. It are regularly wont to identify the nearness, the level, the amount or potentially the nonattendance of water. While this may be wont to remind you to water your plants, there's an obviously better Grove sensor for that. The water level sensor is anything but difficult to utilize and just has three pins to interface. Ground, +5V, and the sign pin. The sign pin is a simple yield that will be associated with any of the simple yields on your Arduino. Sensor's GND pin is associated with the Arduino GND pin. Water Sensor Signal to Arduino A5. Water Sensor +5V pin is associated with Arduino 5V. Water Sensor GND is associated with Arduino GND.

C. TEMPERATURE / HUMIDITY SENSOR

For estimating dampness, the mugginess detecting segment which has two terminals with dampness holding substrate between them. So on the grounds that the mugginess changes, the conductivity of the substrate changes or the obstruction between these terminals changes. This opposition change is estimated and prepared by the IC which makes to peruse by a microcontroller. On the contrary hand, for estimating temperature these sensors utilize a NTC temperature sensor or a thermistor. A thermistor is actually a rheostat that changes its opposition with change of the temperature. These sensors are made by sintering of semi conductive materials like pottery or polymers in order to supply bigger changes inside the opposition with simply little changes in temperature. The expression "NTC" signifies "Negative Temperature Coefficient", which proposes that the opposition diminishes with increment of the temperature.

D. PH SENSOR

There are a few different ways to gauge pH from a fluid. One very normal way is that the shading changes in substance powders, similar to litmus strips used in basic science. In present day mechanical applications, a pH test is generally utilized. This test contains two terminals that produce voltage signal. One of the 2 cathodes might be an estimation anode developed out of uncommon glass request to make particle particular obstruction. This obstruction hen screens out hydrogen particles from the monstrous herd of particles in any case present inside the arrangement. Reference cathode is implied during a way that it keeps up a proceeding with potential at some random temperature. At the point when reference potential is contrasted with the capability of the pH cathode, a milli volt signal corresponding to pH is made permitting the measurement. This terminal makes a reference that it the two attempts to deal with which on which to coordinate potential readings from the estimation anode. Explanation behind use of wet compound interface is that they produce less voltage over the interface of contact, permitting progressively precise estimations.

E. GSM MODULE

GSM represents Global System for Mobile Communications. It is the worldwide standard for versatile correspondence. GSM is a circuit for correspondence between figuring machine and client mobile. It is play double band and exceptionally adaptable attachment. Double band scope of 900/1800MHz and Operating temperature about - 40 degree celsius to +85 degree celsius. The sign addition is around 2 dB. The GSM module is associated with outside force supply and arduino. GSM module contains transmitter that move information to client portable. When the arduino signals the GSM it sends the reaction to client portable. It bolsters highlights like GPRS, SMS, Voice.

III. IMPLEMENTATION

The system controlled by Arduino uno AT Mega 328p processor. The arduino board is equipped with digital and analog pins. Water level sensor signal pin connected to an analog pin, positive voltage pin connected to +5V terminal and Ground pin connected to ground pin on the arduino. Temperature / Humidity sensor contains four pins, Data pin connected to analog pin, Vcc pin connected to power supply, GND pin connected to ground of the arduino. The pH sensor contains six terminals, they are To, Do, Po, GND1, GND2, Vcc. The pin Po of the pH sensor connected to analog pin, Vcc connected to power supply, Do pin connected to digital pin and GND1 pin connected to ground on the arduino. GSM analog pin used to transmit and receive data and it is connected to arduino analog pin. An external power supply is connected to GSM, and then LED in the GSM starts blink, GND pin connected to ground of the arduino. The sensor data are send to the user mobile, when they request by using there mobile.

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

IV. BLOCK DIAGRAM




Fig.1 Block diagram

V. CONCLUSION

The point of this task is to show the subtleties of hydroponics that is actualized utilizing electronic circuit, water and supplement arrangement for example soilless. The framework naturally supplies supplement and supplements can be checked. When the checking is finished revisions are regularly done for example framework can be controlled in like manner prompting higher profitability. We are expecting to execute bug identification and interfacing with GSM module to make the mechanized model progressively adaptable. This framework spares water and manures, gives better yields when contrasted with soil framework. Client can execute more framework in the hydroponics. For future improvement, client can utilize more sensor like electrical conductivity sensor. To decrease the warmth over the green house, client can utilize cooling fan to diminish the indoor temperature level. client can make the hydroponics framework completely programmed.

REFERENCES

- [1] M. Azaza , C.Tanougast , E.Fabrizio , A.Mami "Smart greenhouse fuzzy logic based control system enhanced with wireless data monitoring" , 61, 297307, 2016.
- [2] C. Harper and M. Siller, "OpenAG: A Globally Distributed Network of Food Computing," in Proc. 4th IEEE Pervasive Computing, Vol 14, 2015, pp24-27.
- [3] Vijendra Sahare, Preet Jain " Automated Hydroponic System using Psoc4 Prototyping Kit to Deliver Nutrients Solution Directly to Roots of Plants on Time Basis" Dept. of ECE, SVITS College, Indore, MP, India,2015.
- [4] Mark Griffiths " The Design and Implementation Of a Hydroponics Control System" M.S theses, Dept. of Information Technology, Oulu University of Applied Sciences, Finland.,2014.
- [5] Dr.Hector Munoz.(2010). "Home Based Vegetable Production System." Date of retrieval 28.01.2014
- [6] Growgear , "Are LED Grow Lights Really That Efficient?" September 21, 2013.

International Journal of Innovative Research in Science, Engineering and Technology
An ISO 3297: 2007 Certified Organization *Volume 9, Special Issue 1, March 2020*
8th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '20)
18th-19th March 2020

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

- [7] Carlos A.P.camara “Automated system developed to control pH and concentration of nutrient solution evaluated in hydroponic lettuce”, Department of Chemistry, State University of Londrina,Brazil,2012
- [8] D. S. Domingues, H. W. Takahashi, Carlos A.P. Camara, S. L. Nixdorf “Automated system developed to control pH and concentration of nutrient solution evaluated in hydroponic lettuce production”, In: Computer and Electronics in Agriculture, Vol 84, Elsevier, pp 53-61,2012.
- [9] O. V. Avercheva, "Growth and photosynthesis of Chinese cabbage plants grown under light-emitting diode-based light source", Russia journal of plant physiology, Volume 56, Issue 1, pp 14–21, January,2009.
- [10] Dimitrios Savvas “Hydroponics: A modern technology supporting the application of integrated crop management in greenhouse ”, Department of Floriculture and Landscape Architecture, Faculty of Agricultural Technology,Greece,2003.