



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 12, Issue 7, July 2023

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com

Degradation of Persistent Organic Pollutants from Contaminated Wastewater Using Photocatalytic Processes

Mr. Sahil Ghurde¹, Prof. Anurag K. Gahalod²

P.G. Student, Department of Civil Engineering, G. H. Rasoni University, Amravati, Maharashtra, India¹

Associate Professor, Department of Civil Engineering, G. H. Rasoni University, Amravati, Maharashtra, India²

ABSTRACT: In this work, photocatalytic corrosion interceded by lit TiO₂ was investigated for the treatment of weakened natural copper wastewater released from semiconductor creation plants. Because of their boundless use in different assembling processes and their very hurtful ecological impacts, two natural mixtures ethyl lactates and phenol and copper particles were analyzed. The end proficiency of ethyl lactate and phenol was shown by photocatalytic tests to be reliant upon the TiO₂ impetus stacking, beginning pH, oxygen content, and TiO₂ impetus qualities. We tracked down that an underlying pH of 3.0 and a TiO₂ portion of 0.1 g/L were great. Under unadulterated oxygen conditions, the photocatalytic cycle showed essentially higher evacuation proficiency. Under the experimental circumstances used in this work, kinetic studies on the photodegradation of ethyl lactate and phenol showed that the photodegradation processes were consistent with first-order rate reactions. It was discovered that the removal of phenol and ethyl lactate from TiO₂ particles may be disregarded.

KEYWORDS: Titanium Oxide, Photocatalyst, Photoreactor, Waste water

I. INTRODUCTION

As the new century draws near, the overall market result of the gadgets area — which incorporates the semiconductor business — has proactively outperformed that of the vehicle business (Chang and Sze, 1996). The development of semiconductors involves an enormous scope of extraordinary unit tasks and is continually evolving. Albeit huge endeavors have been made to forestall ecological pollution by process change or substance substitution, large numbers of the cycles utilized in the semiconductor business bring about emanations of a scope of pollutants, including both inorganic and natural synthetics.

Before wastewater in Singapore is delivered into a public sewer or stream, the natural substance of the wastewater should be decreased to inside permitted limits in accordance with the Ecological Contamination Control Act (EPCA) and the Sewerage and Seepage Act (SDA) (Service of Climate, 2001).

By far most of wastewater treatment methodology as of now utilized in semiconductor producing offices are intended to dispose of weighty metals like copper, cobalt, and silicon as well as inorganic synthetic compounds like hydrofluoric corrosive, sulfuric corrosive, phosphoric corrosive, nitric corrosive, and ammonium hydroxide (Huang and Liu, 1999). Then again, the potential issues welcomed on by the natural waste have not been enough tended to. Presently, there are a few waste disposal approaches that are presently utilized with different degrees of achievement. Treatment modalities like essential screening that depend intensely on applying actual powers are alluded to as unit tasks. Treatment procedures, for example, balance, that eliminate pollutants by substance or natural responses are alluded to as unit processes. Essential, high level essential, auxiliary, and high level treatment are various levels of care that are given by unit exercises and strategies. All poisonous species present in the waste stream ought to be completely mineralized during the best waste treatment strategy, abandoning no unsafe extras. Furthermore, it should be reasonable. As of now, most of treatments call for follow-up care, which raises the cost. For example, air-stripping cancels for later gas treatment. Natural waste streams containing profoundly unsafe substances are not reasonable for organic breakdown. Complex natural parts present in wastewater that are challenging to break down organically are oxidized into easier finished results utilizing progressed oxidation processes (AOPs).

II. LITERATURE REVIEW

1. Kansal et al.

They investigated the orange degradation of methyl and rhodamine 6G dyes utilising a heterogeneous photocatalytic method. The testing findings showed that the employment of the ZnO catalyst and basic pH resulted in the greatest degradation (above 90%) of the dyes; also, the performance of the photocatalytic system employing ZnO/sunlight was found to be more efficient than the ZnO/UV system. Concerns concerning residual water treatment are not limited to the industrial sector; a new concept of sustainable chemistry has recently arisen that pushes for waste minimization in industrial and laboratory effluents. The design, development, and implementation of chemical products and processes to decrease or eliminate the use and manufacture of harmful compounds is the notion of sustainable chemistry.

For photocatalytic degradation of methylene blue (MB), Acosta-Silva et al. employed TiO₂-decorated Santa Barbara Amorphous (SBA-15) mesoporous material. Green synthesised zinc oxide nanoparticles mediated by Sambucus ebulus leaf extract and employed this material for photocatalytic degradation of methylene blue dye in aqueous medium, according to Alamdari et al.³⁵. The current study looked at the impacts of operational factors including catalyst load, solution pH, and dye starting concentration on the kinetics of photocatalytic degradation of methylene blue under UV light.

2. Sobsey et al. (2008)

They reviewed some of the POU technologies that have been shown to be effective in terms of microbiological efficacy and diarrhoeal disease reduction, such as chlorination with safe storage, combined coagulant-chlorine disinfection systems, solar disinfection, ceramic filters, and biosand filters. Furthermore, as a novel POU technology, Ehdaie et al. produced a silver-infused ceramic tablet for long-term water disinfection. When put into a domestic water storage container, the tablet releases silver ions that eliminate microbiological infections. It is constructed of clay, water, sawdust, and silver nitrate. The measures described above are largely intended to prevent diarrhoea and other water-borne diseases. Thus, for water polluted with heavy metals and metalloids, conventional approaches may be insufficient and require more specialised treatment.

3. Fowler et al. (2015)

According to author, artisanal gold mining, a small-scale business, employs around 20 million people globally and is the second greatest source of mercury emitted into the atmosphere after coal-fired power stations. Metallic mercury is used in the procedure to generate gold-mercury amalgams by passing river water containing sedimentary gold particles through mercury-coated channels and then extracting the gold by burning off the mercury using propane torches. Because of the mobility of mercury in the atmosphere and its buildup in fishing products, this produces environmental contamination as well as evident detrimental health impacts on both a local and global scale. Regardless, it provides significant cash resources to disadvantaged people in developing nations.

III. METHODOLOGY

Experimental procedure

Studies of organic substances adsorption onto TiO₂ (1g/L) were conducted in the pH range of 4 to 10 to explore the adsorption of phenol and ethyl lactate onto TiO₂ particles. The pH ranges of 4.0, 7.0, and 10.0 were selected. Ethyl lactate and phenol have identical 1mM concentrations. Every 20 minutes for the duration of the 4 hours of reaction time, a 5mL sample was taken for analysis.

The catalyst dose in slurry photocatalytic systems is a crucial factor that has undergone substantial research. Under UV irradiation, 1mM solutions of ethyl lactate and phenol were photocatalytically degraded. TiO₂ catalyst loading ranged from 0.05g/L to 1.00g/L. The oxygen flow rate is 300 mL/min, and the UV exposure period is 120 minutes. The pH is 5.0 at the start.

The separation of phenol and ethyl lactate as well as the surface charge attributes of TiO₂ are both essentially affected by the suspension's underlying pH. To decide the starting pH influence, tries different things with four different introductory arrangement pHs — 3.0, 6.0, 8.0, and 10.0 — were directed at a similar TiO₂ portion. The UV openness period is 120 minutes, and the TiO₂ stacking is 0.25g/L. The underlying convergences of phenol and ethyl lactate are every one of the 1 mM, and the oxygen stream rate is 300 mL/min.

The photocatalytic response component intensely relies upon oxygen. The examinations were completed in three distinct conditions: oxygen, nitrogen, and air, to analyze the job of oxygen in the photooxidation cycle. The UV openness period is 120 minutes, and the TiO₂ stacking is 0.25 g/L. The pH is 5.0 and the underlying phenol and ethyl lactate focuses are 1mM.

There are three distinct gem types of titanium dioxide known to exist: anatase, brookite, and rutile. Most of specialists utilize Dessuga P25 TiO₂, which is exceptionally popular. In this work, the surface regions and phenol and ethyl lactate



expulsion abilities of two particular kinds of TiO₂ (Merck and Dessuga) were analyzed. The UV openness period is 120 minutes, and the TiO₂ stacking is 0.1g/L. The pH is 5.0 and the underlying phenol and ethyl lactate fixations are every one of the 1 mM.

A huge part of the wastewater delivered by the semiconductor business is copper particles. To reproduce wastewater in this trial, 1 mM of copper nitrate was infused. . A similar pH esteem (5.0) and TiO₂ fixation (1.0g/L) were utilized for all trials. The strategies for natural compound disposal and copper particle recuperation were concentrated on under high-impact and anaerobic settings.

To see how Cu(II) fixation impacted the decrease in the convergence of natural parts in the engineered wastewater, three further runs (1mM, 2mM, and 5mM Cu(II)) were done under high-impact conditions. The oxide of titanium (IV) is insoluble in water. When joined with water, the TiO₂ particles produce a fine suspension. With an end goal to typify TiO₂ to work on the division.

Following the photo catalytic interaction, TiO₂ is added to the sodium alginate arrangement and very much disturbed to make a uniform suspension. Seven elements are controlled in this TiO₂ exemplifying strategy, as recorded in Table 3.1.

Table 3.1 is a rundown of the control boundaries for the TiO₂ interaction.

Control Parameters	Set Values	Units
Syringe Pump Volumetric Flow rate	2	ml/h
Needle Size	0.50×16	mm
Plate Distance	3	cm
Voltage Applied	5	kV
Sodium Alginate Concentration	1	v%
Calcium Chloride Concentration.	5	v%
TiO ₂	0.25	g/L

Chromatography (HPLC) (Shimadzu, Japan) was utilized to decide the grouping of phenol, and a ZORBAX SB-C18 LC section (4.6 mm 25 cm, HP, USA) was utilized to isolate the mixtures. Gas chromatography (GC) (Shimadzu, Japan) was utilized to evaluate the grouping of ethyl lactate, and a 60-m HP-Voc slim section (i.d. of 0.32mm; film thickness of 1.8 m; HP, U.S.A.) was utilized to isolate the constituents. Inductively Couple Plasma Outflow Spectroscopy (ICP) (Perkin Elmer) was utilized to recognize the centralization of metal copper particles.

USA: Optima 3000. Whatman Autovial Syringeless separating was utilized on all examples.

PTFE channel, 0.45 (Clifton, NJ).

The arrangement pH was resolved utilizing an Orion model 525A pH meter (Boston, Mama). The arrangement ORP was observed utilizing a Jenco model 3676 14 Racket pH/ORP regulator (USA). The arrangement's conductivity was estimated utilizing an Oakton conductivity meter (Eutech, Singapore). The HACH DR/2010 Spectrophotometer (USA) was utilized to gauge turbidity. An analyzer for absolute natural carbon, the Shimadzu TOC-5000, was utilized to quantify TOC focuses. A Coulter LS Molecule Size Analyzer was utilized to quantify molecule size.

SEM (JEOL, JSM-5600V, Japan) was utilized to imagine the surfaces' morphology in the precipitation strong. The surface complex of the copper green solids and earthy colored solids that hastened were distinguished by X-beam photoelectron spectroscopy (Krotos Pivot His, Perkin-Elmer Organization, USA). The monochromatic Mg K radiation energy source (1253.6 eV), worked at 15kv and 10mA, was utilized to produce the XPS spectra. The energy scope of 928-960 eV was utilized to examine the component Cu. The bend fitting system decoded the spectra by deducting the Shirley foundation and computing the Gaussian (0) to Lorentzian (100 percent) proportion. The limiting energy of the spectra was determined utilizing the C 1s pinnacle of the aliphatic polluting carbons, which is situated at 284.5 eV, for alignment purposes..

IV. RESULT AND ANALYSIS

Turbidity

Turbidity is a term used to portray how hazy or dim the water is, or to depict how much light is diverted by suspended particles as it goes through a water section. How much shadiness in the arrangement would vary as TiO₂ particles were added. Turbidity is an estimation of how light is scattered by suspended materials; the more seriously dispersed light is, the more prominent the turbidity.




Figure 4.3 The turbidity in solution with changing TiO₂ dosage

Figure 4.3 shows the straight association between the turbidity of the TiO₂ suspension and the TiO₂ stacking. The turbidity ascends with an expansion in TiO₂ portion, which negatively affects UV oxidation in the arrangement. Turbid waters diminish how much light that arrives at the water, which brings down photooxidation movement all through the whole arrangement and diminishes how much TiO₂ particles that are available to get UV illumination.

4.3 Impacts of TiO₂ stacking, area

The impetus portion in slurry photocatalytic frameworks is a significant component that has gone through significant exploration. With a TiO₂ impetus stacking of 0.05g/L to 1.00g/L and UV light, 1mM ethyl lactate and phenol arrangements were photocatalytically corrupted. Figure 4.4 showcases the corruption of phenol and ethyl lactate according to how much TiO₂. In the analyses for this examination, 0.1 g/L of TiO₂ was the best portion. The presence of overabundance photocatalyst in the fluid will bring the turbidity up in the arrangement when the TiO₂ stacking surpasses the proper portion, which will significantly affect the entrance of UV radiation.

The decrease in UV light entrance causes the impediment impact for dosages over the ideal (Ku et al., 1996; Chen and Chou, 1993). The centralization of Goodness. extremist in the fluid is compelled assuming there is deficient light entrance in the arrangement. At lower impetus loadings, a significant part of the light was gone through the slurry in the reactor when the TiO₂ portion was beneath the best stacking. The little surface region of the TiO₂ particles causes the impediment impact for TiO₂ dosages beneath the ideal level. It decreased the convergence of OH• revolutionaries in the arrangement since there wasn't sufficient surface region on the TiO₂ particles.




Figure 4.4. Effect of TiO₂ dosages on the photooxidation phenol and EL (Experimental conditions: UV exposure time=120min; Initial conc. [Phenol]₀=1mM; [Ethyl lactate]₀=1mM; O₂ flowrate=300ml/min; pH = 5.0 [Cu²⁺] =0)




Figure 4.5 Phenol concentration in solution vs. time under different TiO₂ loading (Experimental conditions: UV exposure time=120min; Initial conc. [Phenol]₀=1mM; [Ethyl lactate]₀=1mM; O₂ flowrate=300ml/min; pH = 5.0 [Cu²⁺] =0)




Figure 4.6 Ethyl lactate (EL) concentration in solution vs. time under different TiO₂ loading (Experimental conditions: UV exposure time=120min; Initial conc. [Phenol]₀=1mM; [Ethyl lactate]₀=1mM; O₂ flowrate=300ml/min; pH = 5.0 [Cu²⁺] =0)




Figure 4.7 Intermediate detected during the degradation of 1mM phenol solution under different TiO₂ loading (Experimental conditions: UV exposure time=120min; Initial conc. [Phenol]₀=1mM; [Ethyl lactate]₀=1mM; O₂ flowrate=300ml/min; pH = 5.0 [Cu²⁺] =0)

Figures 4.5, 4.6, and 4.7, separately, show the time courses of phenol, ethyl lactate, and the amalgamation of the synthetic moderate hydroquinone at different TiO₂ stacking values. Phenol and ethyl lactate were consumed at a pseudo-first request rate. Table 4.1 contains the outcomes for the paces of phenol and ethyl lactate disposal. Table 4.2 records the maximal transitional focuses for the photocatalytic breakdown of 1 mM phenol.

V. CONCLUSION

Because of their more slow settling speeds, TiO₂ particles have demonstrated to be a critical boundary to expulsion from the treated wastewater stream. The assembling of exemplified titanium dioxide dabs was demonstrated to be very feasible when the epitome cycle was utilized to titanium dioxide, which photograph catalyzed the oxidation of organics in semiconductor wastewater treatment. The exemplified TiO₂'s settling skill was significantly moved along. All the more essentially, the TiO₂'s capacity to photograph oxidize natural solvents was not lost. Slurry reactors can be improved by titanium dioxide powder being typified in dots because of the straightforwardness with which the dots might be effectively isolated from the treated wastewater and the quick settling speed.

REFERENCES

- [1] Ansari, S. A., Khan, M. M., Ansari, M. O., Kalathil, S., Lee, J. & Cho, M. H. 2014 Band gap engineering of CeO₂ nanostructure using an electrochemically active biofilm for visible light applications. Rsc Advances 4 (32), 16782–16791.
- [2] Abhang, R., Kumar, D. & Taralkar, S. 2011 Design of photocatalytic reactor for degradation of phenol in wastewater. International Journal of Chemical Engineering and Applications 2 (5), 337.
- [3] Ali, A. M., Emanuelsson, E. A. & Patterson, D. A. 2010 Photocatalysis with nanostructured zinc oxide thin films: the relationship between morphology and photocatalytic activity under oxygen limited and oxygen rich conditions and evidence for a Mars Van Krevelen mechanism. Applied Catalysis B: Environmental 97 (1–2), 168–181.
- [4] Becheri, A., Dürr, M., Nostro, P. L. & Baglioni, P. 2008 Synthesis and characterization of zinc oxide nanoparticles: application to textiles as UV-absorbers. Journal of Nanoparticle Research 10 (4), 679–689.
- [5] Cassano, A. E. & Alfano, O. M. 2000 Reaction engineering of suspended solid heterogeneous photocatalytic reactors. Catalysis Today 58 (2–3), 167–197.



- [6] Chen, H., Nanayakkara, C. E. & Grassian, V. H. 2012 Titanium dioxide photocatalysis in atmospheric chemistry. *Chemical Reviews* 112 (11), 5919–5948.
- [7] Chong, M. N., Jin, B., Zhu, H., Chow, C. & Saint, C. 2009 Application of H-titanate nanofibers for degradation of Congo Red in an annular slurry photoreactor. *Chemical Engineering Journal* 150 (1), 49–54.
- [8] Chong, M. N., Jin, B., Chow, C. W. & Saint, C. 2010 Recent developments in photocatalytic water treatment technology: a review. *Water Research* 44 (10), 2997–3027.
- [9] Cocha, M., Farinelli, G., Tiraferri, A., Minella, M. & Vione, D. 2021 Advanced oxidation processes in the removal of organic substances from produced water: potential, configurations, and research needs. *Chemical Engineering Journal* 414, 128668.
- [10] Coleman, H., Vimonses, V., Leslie, G. & Amal, R. 2007 Degradation of 1, 4-dioxane in water using TiO₂ based photocatalytic and H₂O₂/UV processes. *Journal of Hazardous Materials* 146 (3), 496–501.
- [11] Correa, A. X., Tiepo, E. N., Somensi, C. A., Sperb, R. M. & Radetski, C. M. 2010 Use of ozone-photocatalytic oxidation (O₃/UV/TiO₂) and biological remediation for treatment of produced water from petroleum refineries. *Journal of Environmental Engineering* 136 (1), 40–45.
- [12] Dillert, R., Engel, A., Grobe, J., Lindner, P. & Bahnemann, D. W. 2013 Light intensity dependence of the kinetics of the photocatalytic oxidation of nitrogen (ii) oxide at the surface of TiO₂. *Physical Chemistry Chemical Physics* 15 (48), 20876–20886.
- [13] Dong, H., Zeng, G., Tang, L., Fan, C., Zhang, C., He, X. & He, Y. 2015a An overview on limitations of TiO₂-based particles for photocatalytic degradation of organic pollutants and the corresponding countermeasures. *Water Research* 79, 128–146.
- [14] Dong, S., Feng, J., Fan, M., Pi, Y., Hu, L., Han, X., Liu, M. & Sun, J. 2015b Recent developments in heterogeneous photocatalytic water treatment using visible light-responsive photocatalysts: a review. *RSC Advances* 5 (19), 14610–14630.
- [15] Enesca, A. 2021 The influence of photocatalytic reactors design and operating parameters on the wastewater organic pollutants removal – a mini-review. *Catalysts* 11 (5), 556.



INNO SPACE
SJIF Scientific Journal Impact Factor
Impact Factor: 8.423



ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

9940 572 462 6381 907 438 ijirset@gmail.com



www.ijirset.com

Scan to save the contact details