



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 8, August 2024

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.524

9940 572 462

6381 907 438

ijrset@gmail.com

www.ijrset.com

Efficient Wastewater Treatment for PVC and CPVC Resin Production Plants Utilizing DAF and Using Pam in Non-Biological Methods with Tertiary Treatment

Sarath R^[1], Senthil N^[2]

M. E. Environmental Engineering, Department of Civil Engineering, Gnanamani College of Technology, Pachal, Namakkal, Tamil Nadu, India^[1]

Assistant Professor, Department of Civil Engineering, Gnanamani College of Technology, Pachal, Namakkal, Tamil Nadu, India^[2]

ABSTRACT: Wastewater management in the production of polyvinyl chloride (PVC) and chlorinated polyvinyl chloride (CPVC) resins is a critical aspect of maintaining environmental sustainability and regulatory compliance. This abstract presents an overview of an efficient wastewater treatment approach tailored for PVC and CPVC resin production plants. The proposed method focuses on the integration of Dissolved Air Flotation (DAF) and using of Polyacrylamide (PAM) without the need for biological treatment processes. Because of the effluent have presents of Chloroide and high Temperature so its affects microbes' growth and by using this we can able to reduce the fouling and flux of the membrane and its increase the durability. The utilization of DAF involves the removal of suspended solids and colloidal particles from the wastewater stream through flotation and bottom sedimentation, resulting in improved clarity and reduced turbidity. Concurrently, Polyacrylamide (PAM) is introduced as a coagulant aid and flocculant to enhance the efficiency of solid-liquid separation in the DAF process for reducing the retention time. The synergistic effect of DAF and using PAM facilitates the effective removal of contaminants, including organic matter and chemical residues, thereby mitigating potential environmental impacts associated with wastewater discharge for reduce the source water consumption the treated water from secondary treatment are utilized on using of Tertiary Treatment the water has been recycled for Production unit as a DM water. By opting such as DAF and PAM, the wastewater treatment system avoids the complexities and operational challenges often encountered with biological processes, such as nutrient management and sludge handling. This streamlined approach not only reduces the overall footprint of the treatment infrastructure but also enhances operational flexibility and reliability. Overall, the proposed wastewater treatment strategy offers a comprehensive solution for PVC and CPVC resin production plants to address their environmental obligations while optimizing process efficiency and resource utilization. Through the integration of DAF and using of PAM, in non-biological methods, this approach demonstrates a sustainable and cost-effective means of managing wastewater in the PVC and CPVC resin manufacturing industry.

KEYWORDS: Wastewater management, polyvinyl chloride (PVC) and chlorinated polyvinyl chloride (CPVC) resins, Dissolved Air Flotation (DAF) and using of Polyacrylamide (PAM)

I. INTRODUCTION

The production of polyvinyl chloride (PVC) and chlorinated polyvinyl chloride (CPVC) resins is vital for various industries, ranging from construction to automotive manufacturing. However, along with the benefits of these materials comes the challenge of managing the wastewater generated during the production process. Effective wastewater treatment is essential to mitigate environmental impacts and ensure compliance with regulatory standards. In recent years, there has been a growing focus on developing efficient treatment methods tailored specifically to the needs of PVC and CPVC resin production plants.

This introduction provides an overview of the challenges associated with wastewater treatment in the PVC and CPVC resin manufacturing industry and introduces the concept of Utilizing Dissolved Air Flotation (DAF), Polyacrylamide

(PAM), and non-biological methods as a promising approach to address these challenges and reduce the footprint of plants and treating time.

PVC and CPVC resins are widely used in various applications due to their versatility, durability, and cost-effectiveness. However, the production processes involve the use of chemicals and generate wastewater containing suspended solids, organic compounds, and other contaminants. Improper management of this wastewater can lead to adverse environmental impacts, including pollution of water bodies and harm to aquatic ecosystems and affect the land.

To address these challenges, wastewater treatment technologies tailored to the specific characteristics of PVC and CPVC resin production wastewater are essential. In recent years, the integration of Dissolved Air Flotation (DAF) and using Polyacrylamide (PAM) has emerged as a promising approach to effectively treat industrial effluents. DAF facilitates the removal of suspended solids and colloidal particles through flotation and sedimentation, while PAM acts as a coagulant aid and flocculant, enhancing the efficiency of solid-liquid separation processes and its faster process because of its high in Molecular weight.

Furthermore, the adoption of non-biological treatment methods offers advantages such as operational simplicity, reduced footprint, and lower costs compared to traditional biological treatment approaches. By focusing on DAF, PAM, and non-biological methods, PVC and CPVC resin production plants can optimize their wastewater treatment processes, minimize environmental impacts, and ensure compliance with regulatory requirements.

And by using of the effluent are treated by primary, secondary settling system (DAF) and the Treated water has been treated by using of Tertiary Treatment the water has been treated as per its requirements.

In this context, this paper explores the application of DAF, PAM, and non-biological methods in wastewater treatment for PVC and CPVC resin production plants. Through a review of existing literature and research findings, the paper aims to provide insights into the potential benefits and challenges of implementing these technologies and to offer recommendations for optimizing wastewater treatment practices in the industry.

II. RELATED WORK

The treatment of wastewater generated from PVC and CPVC resin production plants is a crucial aspect of environmental management within the chemical manufacturing industry. This literature review examines existing research and developments related to efficient wastewater treatment strategies, focusing on the integration of Dissolved Air Flotation (DAF), Polyacrylamide (PAM), and non-biological methods [1]. Numerous studies have investigated the application of DAF in treating industrial wastewater, emphasizing its effectiveness in removing suspended solids, colloidal particles, and organic contaminants. For PVC and CPVC resin production plants, DAF has been identified as a promising technology for clarifying wastewater streams and achieving compliance with discharge regulations (Xu et al., 2018) [2]. The use of DAF is particularly advantageous due to its ability to operate efficiently in treating high-load industrial effluents while requiring minimal space and energy consumption [3]. Complementing DAF, the addition of Polyacrylamide (PAM) has been explored as a means to enhance solid-liquid separation and improve the performance of flotation processes. PAM acts as a coagulant aid and flocculant, facilitating the aggregation of fine particles and improving the efficiency of contaminant removal (Zhu et al., 2019) [4]. Studies have demonstrated the synergistic effects of combining DAF with PAM, resulting in higher removal efficiencies for suspended solids, oils, and grease in various industrial wastewaters. Moreover, the adoption of non-biological treatment methods aligns with the industry's demand for cost-effective and reliable wastewater management solutions. By eliminating the complexities associated with biological processes, such as nutrient requirements and sludge handling, non-biological methods offer operational simplicity and flexibility (Wu et al., 2020) [5]. This approach not only reduces capital and operational costs but also minimizes the environmental footprint of wastewater treatment facilities [6]. Dissolved air flotation (DAF) is a separation process based on the generation of microbubbles (Santana et al., 2012) and can be used as an alternative for the wastewater treatment for water reuse in apatite flotation. DAF is based on the variation of the air solubility in water, according to the pressure in the system. In this process, the water is first saturated with high-pressure air, usually between 3 and 6 atm. Next, the saturated water is forced to flow through needle valves or orifices, and microbubbles (10–100 μm diameter) are produced just down-stream of the constriction (Santana et al., 2012) [7]. Performance assessment of PAM in wastewater treatment involves measuring parameters such as turbidity reduction, settleability of flocs, and overall treatment effectiveness (Zhu et al., 2021) [8].

III. METHODOLOGY

Methodology for Efficient Wastewater Treatment for PVC and CPVC Resin Production Plants

I. Introduction

PVC (Polyvinyl Chloride) and CPVC (Chlorinated Polyvinyl Chloride) resin production generates wastewater containing contaminants like suspended solids, heavy metals, and organic compounds.

Efficient treatment is crucial to minimize environmental impact and meet regulatory standards.

II. Primary Treatment

DAF (Dissolved Air Flotation): Remove suspended solids, oils, and greases using DAF units.

Add chemicals (e.g., alum, ferric chloride) to enhance flocculation.

Inject air to create micro-bubbles, which attach to particles and float to the surface for removal.

III. Non-Biological Treatment (Chemical Coagulation)

PAM (Polyacrylamide): Add PAM to remove remaining suspended solids and organic matter.

PAM enhances flocculation, allowing for easier removal of contaminants.

Optimize PAM dosage and mixing conditions for maximum efficiency.

IV. Tertiary Treatment

Filtration: Use filters (e.g., sand, cartridge) to remove remaining suspended solids and contaminants.

Activated Carbon Adsorption: Remove organic compounds, heavy metals, and residual contaminants using activated carbon.

VI. Monitoring and Control

Regularly monitor wastewater quality, treatment efficiency, and chemical usage.

Adjust treatment parameters as needed to ensure optimal performance.

VI. EXPERIMENTAL RESULTS

- pH: Measured using a pH meter or indicator strips.
- Temperature: Recorded using a calibrated thermometer.
- Conductivity: Measured with a conductivity meter to assess salinity or total dissolved solids.
- Turbidity: Assessed using a turbidimeter to quantify suspended solids in water.
- Total Suspended Solids (TSS): Determined by filtering a water sample and weighing the residue after drying.
- Total Dissolved Solids (TDS): Estimated by evaporating a water sample and weighing the residue.

Table 1: Final output of DAF

Test no	PAC Dosage (mg/l)	PAM Dosage (mg/l)	Initial Turbidity NTU	Final Turbidity NTU	Initial O&G (mg/l)	Final O&G (mg/l)	Removal Efficiency %	DAF Quality
1	5	0.5	50	12	88	21	76	GOOD
2	10	1	50	8	88	14	84	EXCELLENT
3	15	1.5	50	6	88	10	88	EXCELLENT
4	20	2	50	5	88	8	90	EXCELLENT
5	25	2.5	50	4	88	3	92	EXCELLENT




Fig. No. 1. Final Result of DAF




Fig. No. 2. Effluent



Fig. No. 3. After chemical Dosing



Fig. No. 4. After DAF System

Using Polyacrylamide (PAM) in a Dissolved Air Flotation (DAF) system for PVC/CPVC plant wastewater treatment can lead to the following results:

1. **Improved removal of suspended solids:** PAM can increase the removal efficiency of suspended solids, including PVC and CPVC particles, by up to 95%.
2. **Enhanced flocculation:** PAM helps to form larger, more stable flocs, making it easier to remove contaminants through flotation.
3. **Increased efficiency in oil and grease removal:** PAM can improve the removal of oil and grease by up to 90%.
4. **Reduced sludge volume:** By improving the removal efficiency of contaminants, PAM can help reduce the volume of sludge generated.
5. **Improved water clarity:** The use of PAM in the DAF system can result in clearer treated water, with a turbidity reduction of up to 90%.

Compliance with regulations: The effective removal of contaminants using PAM in the DAF system can help the PVC/CPVC plant meet regulatory requirements for wastewater.

IV. DISUCSSION

In conclusion, implementing efficient wastewater treatment processes is paramount for PVC and CPVC resin production plants to meet regulatory requirements, minimize environmental impact, and ensure sustainable operations. The utilization of Dissolved Air Flotation (DAF), Polyacrylamide (PAM) flocculation, and non-biological methods presents a comprehensive approach to address the diverse challenges posed by wastewater generated in these industrial facilities.

Through the application of DAF, suspended solids, residual monomers, and other contaminants can be effectively removed from wastewater streams, enhancing treatment efficiency and water quality. PAM flocculation serves to further enhance particle removal, optimizing the performance of treatment systems and reducing the load on downstream processes. Additionally, non-biological methods such as chemical precipitation, adsorption, and advanced oxidation processes offer targeted solutions to address specific pollutants and meet stringent discharge standards.

The successful implementation of these techniques requires careful consideration of process parameters, monitoring protocols, and optimization strategies. Regular maintenance and monitoring of treatment systems are essential to ensure consistent performance and compliance with regulatory requirements over time.

Overall, by leveraging DAF, PAM, and non-biological methods, PVC and CPVC resin production plants can achieve efficient and sustainable wastewater treatment, contributing to environmental stewardship and responsible industrial practices. Continued research and innovation in wastewater treatment technologies will further enhance the effectiveness and sustainability of treatment processes, supporting the long-term viability of these industries while safeguarding the environment and public health.

REFERENCES

1. UNESCO, *The United Nations World Water Development Report 2019. Leaving no one behind.* UNESCO. Digital Library. 2019.
2. Agua.org.mx, *Agua en el planeta.* Fondo Para La Comunicación y La Educación Ambiental, A.C. 2017.
3. H. Ritchie; M. Roser, *Water Use and Stress.* Our World in Data. 2017.
4. SWAGL. *Water in Agriculture : Towards Sustainable Agriculture.* Washington, D.C. : World Bank Group. 2021.
5. A. Aziz; F. Basheer; A. Sengar; Irfanullah, S. U. Khan; I. H. Farooqi, "Biological wastewater treatment (anaerobic-aerobic) technologies for safe discharge of treated slaughterhouse and meat processing wastewater," *Sci. Total Environ.*, vol. 686, pp. 681-708, Oct. 2019. <https://doi.org/10.1016/j.scitotenv.2019.05.295>
6. A. Mirshafiee; A. Rezaee; R. S. Mamooory, "A clean production process for edible oil removal from wastewater using an electroflotation with horizontal arrangement of mesh electrodes," *J. Clean. Prod.*, vol. 198, pp. 71-79, Oct. 2018. <https://doi.org/10.1016/j.jclepro.2018.06.201>
7. C. J. Nawarkar; V. D. Salkar, "Solar powered Electrocoagulation system for municipal wastewater treatment," *Fuel*, vol. 237, pp. 222-226, Feb. 2019. <https://doi.org/10.1016/j.fuel.2018.09.140>
8. H. Wu *et al.*, "Comprehensive evaluation on a prospective precipitation-flotation process for metal-ions removal from wastewater simulants," *J. Hazard. Mater.*, vol. 371, pp. 592-602, Jun. 2019. <https://doi.org/10.1016/j.jhazmat.2019.03.048>
9. A. Azevedo; R. Etchepare; J. Rubio, "Raw water clarification by flotation with microbubbles and nanobubbles generated with a multiphase pump," *Water Sci. Technol.*, vol. 75, no. 10, pp. 2342-2349, May. 2017. <https://doi.org/10.2166/wst.2017.113>
10. A. Azevedo; H. Oliveira; J. Rubio, "Bulk nanobubbles in the mineral and environmental areas: Updating research and applications," *Adv. Colloid Interface Sci.*, vol. 271, p. 101992, Sep. 2019. <https://doi.org/10.1016/j.cis.2019.101992>
11. R. Etchepare; A. Azevedo; S. Calgaroto; J. Rubio, "Removal of ferric hydroxide by flotation with micro and nanobubbles," *Sep. Purif. Technol.*, vol. 184, pp. 347-353, Aug. 2017. <https://doi.org/10.1016/j.seppur.2017.05.014>
12. H. A. Oliveira; A. C. Azevedo; R. Etchepare; J. Rubio, "Separation of emulsified crude oil in saline water by flotation with micro- and nanobubbles generated by a multiphase pump," *Water Sci. Technol.*, vol. 76, no. 10, pp. 2710-2718, Nov. 2017. <https://doi.org/10.2166/wst.2017.441>
13. T. Temesgen; T. T. Bui; M. Han; T. Kim; H. Park, "Micro and nanobubble technologies as a new horizon for water-treatment techniques: A review," *Adv. Colloid Interface Sci.*, vol. 246, pp. 40-51, Aug. 2017.

- <https://doi.org/10.1016/j.cis.2017.06.011>
14. R. Etchepare; H. Oliveira; A. Azevedo; J. Rubio, "Separation of emulsified crude oil in saline water by dissolved air flotation with micro and nanobubbles," *Sep. Purif. Technol.*, vol. 186, pp. 326-332, Oct. 2017. <https://doi.org/10.1016/j.seppur.2017.06.007>
 15. M. W. Lim; E. V. Lau; P. E. Poh, "Micro-macrobubbles interactions and its application in flotation technology for the recovery of high-density oil from contaminated sands," *J. Pet. Sci. Eng.*, vol. 161, pp. 29-37, Feb. 2018. <https://doi.org/10.1016/j.petrol.2017.11.064>
 16. K. Ruby; S. K. Majumder, "Studies on stability and properties of micro and nano-particle-laden ionic microbubbles," *Powder Technol.*, vol. 335, pp. 77-90, Jul. 2018. <https://doi.org/10.1016/j.powtec.2018.04.069>
 17. M. Zhang; P. Guiraud, "Surface-modified microbubbles (colloidal gas aphrons) for nanoparticle removal in a continuous bubble generation-flotation separation system," *Water Res.*, vol. 126, pp. 399-410, Dec. 2017. <https://doi.org/10.1016/j.watres.2017.09.051>
 18. S. Calgaroto; A. Azevedo; J. Rubio, "Separation of amine-insoluble species by flotation with nano and microbubbles," *Miner. Eng.*, vol. 89, pp. 24-29, Apr. 2016. <https://doi.org/10.1016/j.mineng.2016.01.006>
 19. L. Zhang, "Advanced treatment of oilfield wastewater by a combination of DAF, yeast bioreactor, UASB, and BAF processes," *Sep. Sci. Technol.*, vol. 56, no. 4, pp. 779-788, Mar. 2021. <https://doi.org/10.1080/01496395.2019.1711411>
 20. G. H. Johansson; A. Crolla; J. D. Lauzon; B. H. Gilroyed, "Estimation of biogas co-production potential from liquid dairy manure, dissolved air flotation waste (DAF) and dry poultry manure using biochemical methane potential (BMP) assay," *Biocatal. Agric. Biotechnol.*, vol. 25, p. 101605, May. 2020. <https://doi.org/10.1016/j.bcab.2020.101605>
 21. T. Wallace; D. Gibbons; M. O'Dwyer; T. P. Curran, "International evolution of fat, oil and grease (FOG) waste management - A review," *J. Environ. Manage.*, vol. 187, pp. 424-435, Feb. 2017. <https://doi.org/10.1016/j.jenvman.2016.11.003>
 22. Q. Zhang; S. Liu; C. Yang; F. Chen; S. Lu, "Bioreactor consisting of pressurized aeration and dissolved air flotation for domestic wastewater treatment," *Sep. Purif. Technol.*, vol. 138, pp. 186-190, Dec. 2014. <https://doi.org/10.1016/j.seppur.2014.10.024>
 23. T. Azuma *et al.*, "Removal of pharmaceuticals in water by introduction of ozonated microbubbles," *Sep. Purif. Technol.*, vol. 212, pp. 483-489, Apr. 2019. <https://doi.org/10.1016/j.seppur.2018.11.059>
 24. Y. Sun; S. Wang; J. Niu, "Microbial community evolution of black and stinking rivers during in situ remediation through micro-nano bubble and submerged resin floating bed technology," *Bioresour. Technol.*, vol. 258, pp. 187-194, Jun. 2018. <https://doi.org/10.1016/j.biortech.2018.03.008>
 25. H. Al-Zoubi; K. A. Ibrahim; K. A. Abu-Sbeih, "Removal of heavy metals from wastewater by economical polymeric collectors using dissolved air flotation process," *J. Water Process Eng.*, vol. 8, pp. 19-27, Dec.
 26. V. R. Fanaie; M. Khiadani, "Effect of salinity on air dissolution, size distribution of microbubbles, and hydrodynamics of a dissolved air flotation (DAF) system," *Colloids Surfaces A Physicochem. Eng. Asp.*, vol. 591, p. 124547, Apr. 2020. <https://doi.org/10.1016/j.colsurfa.2020.124547>
 27. M. de Langlard; H. Al-Saddik; S. Charton; J. Debayle; F. Lamadie, "An efficiency improved recognition algorithm for highly overlapping ellipses: Application to dense bubbly flows," *Pattern Recognit. Lett.*, vol. 101, pp. 88-95, Jan. 2018. <https://doi.org/10.1016/j.patrec.2017.11.024>
 28. A. Gordiychuk; M. Svanera, S. Benini; P. Poesio, "Size distribution and Sauter mean diameter of micro bubbles for a Venturi type bubble generator," *Exp. Therm. Fluid Sci.*, vol. 70, pp. 51-60, Jan. 2016. <https://doi.org/10.1016/j.expthermflusci.2015.08.014>
 29. R. Prakash; S. Kumar Majumder; A. Singh, "Bubble size distribution and specific bubble interfacial area in two-phase microstructured dense bubbling bed," *Chem. Eng. Res. Des.*, vol. 156, pp. 108-130, Apr. 2020. <https://doi.org/10.1016/j.cherd.2020.01.032>
 30. S. J. Gulden; C. Riedele; S. Rollié; M.-H. Kopf; H. Nirschl, "Online bubble size analysis in micro flotation," *Chem. Eng. Sci.*, vol. 185, pp. 168-181, Aug. 2018. <https://doi.org/10.1016/j.ces.2018.04.009>
 31. L. Vinnett; J. Sovechles; C. O. Gomez; K. E. Waters, "An image analysis approach to determine average bubble sizes using one-dimensional Fourier analysis," *Miner. Eng.*, vol. 126, pp. 160-166, Sep. 2018. <https://doi.org/10.1016/j.mineng.2018.06.030>
 32. B. Swart *et al.*, "In situ characterisation of size distribution and rise velocity of microbubbles by high-speed photography," *Chem. Eng. Sci.*, vol. 225, p. 115836, Nov. 2020. <https://doi.org/10.1016/j.ces.2020.115836>
 33. M. dos S. Pereira; A. C. Borges; F. F. Heleno; L. F. A. Squillace; L. R. D. Faroni, "Treatment of synthetic milk industry wastewater using batch dissolved air flotation," *J. Clean. Prod.*, vol. 189, pp. 729-737, Jul. 2018.

<https://doi.org/10.1016/j.jclepro.2018.04.065>

34. L. de S. Leite; M. T. Hoffmann; L. A. Daniel, "Coagulation and dissolved air flotation as a harvesting method for microalgae cultivated in wastewater," *J. Water Process Eng.*, vol. 32, p. 100947, Dec. 2019. <https://doi.org/10.1016/j.jwpe.2019.100947>
35. A. Castillo; P. Vall; M. Garrido-Baserba; J. Comas; M. Poch, "Selection of industrial (food, drink and milk sector) wastewater treatment technologies: A multi-criteria assessment," *J. Clean. Prod.*, vol. 143, pp. 180-190, Feb. 2017. <https://doi.org/10.1016/j.jclepro.2016.12.132>
36. B. R. Baker; R. Mohamed; A. Al-Gheethi; H. A. Aziz, "Advanced technologies for poultry slaughterhouse wastewater treatment: A systematic review," *J. Dispers. Sci. Technol.*, vol. 42, no. 6, pp. 880-899, May. 2021. <https://doi.org/10.1080/01932691.2020.1721007>
37. V. Del Nery; M. H. Z. Damianovic; R. B. Moura; E. Pozzi; E. C. Pires; E. Foresti, "Poultry slaughterhouse wastewater treatment plant for high quality effluent," *Water Sci. Technol.*, vol. 73, no. 2, pp. 309-316, Jan. 2016. <https://doi.org/10.2166/wst.2015.494>
38. M. do S. Pereira; A. C. Borges; G. L. Muniz; F. F. Heleno; L. R. D. Faroni, "Dissolved air flotation optimization for treatment of dairy effluents with organic coagulants," *J. Water Process Eng.*, vol. 36, p. 101270, Aug. 2020. <https://doi.org/10.1016/j.jwpe.2020.101270>
39. G. L. Muniz; A. C. Borges; T. C. F. da Silva, "Performance of natural coagulants obtained from agro-industrial wastes in dairy wastewater treatment using dissolved air flotation," *J. Water Process Eng.*, vol. 37, p. 101453, Oct. 2020. <https://doi.org/10.1016/j.jwpe.2020.101453>
40. S. Ansari; J. Alavi; Z. M. Yaseen, "Performance of full-scale coagulation-flocculation/DAF as a pre-treatment technology for biodegradability enhancement of high strength wastepaper-recycling wastewater," *Environ. Sci. Pollut. Res.*, vol. 25, no. 34, pp. 33978-33991, Dec. 2018. <https://doi.org/10.1007/s11356-018-3340-0>
41. M. M. G. Mofrad; H. Pourzamani; M. M. Amin; I. Parseh; M. Alipour, "In situ treatment of metalworking wastewater by chemical addition-dissolved air flotation coupled with UV, H₂O₂ & ZnO," *Heliyon*, vol. 6, no. 1, p. e03091, Jan. 2020. <https://doi.org/10.1016/j.heliyon.2019.e03091>
42. Y. Shutova; B. L. Karna, A. C. Hambly, B. Lau, R. K. Henderson; P. Le-Clech, "Enhancing organic matter removal in desalination pretreatment systems by application of dissolved air flotation," *Desalination*, vol. 383, pp. 12-21, Apr. 2016. <https://doi.org/10.1016/j.desal.2015.12.018>.



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details