



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 12, December 2024

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

**Impact Factor: 8.524**

 9940 572 462

 6381 907 438

 [ijirset@gmail.com](mailto:ijirset@gmail.com)

 [www.ijirset.com](http://www.ijirset.com)

# Extraction of Curcumin in Turmeric

Rahul Vatsala Arun Lakhapate<sup>1</sup>, Pratik Mangala Dnyaneshwar Anarase<sup>2</sup>,

Lakhan Radha Dagdu Katkar<sup>3</sup>

Professor, Sandip University, Nashik, India<sup>1</sup>

Assistant Professor, Sandip University, Nashik, India<sup>2</sup>

Teacher, Sandip University, Nashik, India<sup>3</sup>

**ABSTRACT:** This abstract summarizes, Curcumin, the primary bioactive compound in turmeric (*Curcuma longa*), has attracted significant attention due to its therapeutic properties, including anti-inflammatory, antioxidant, and anticancer activities. The efficient extraction of curcumin from turmeric rhizomes is crucial for its application in pharmaceuticals, nutraceuticals, and cosmetics. This paper presents a comprehensive review of various extraction techniques employed to isolate curcumin from turmeric, including traditional solvent extraction, supercritical fluid extraction, steam distillation, and emerging methods such as ultrasound-assisted and microwave-assisted extraction. Each method is evaluated in terms of efficiency, yield, solvent usage, and environmental impact. While solvent extraction remains the most commonly used technique, recent advancements in non-toxic, environmentally friendly methods have shown promising results in improving curcumin yield and purity. The paper also explores the optimization of extraction parameters and the challenges associated with large-scale curcumin production. The findings highlight the potential for improving curcumin extraction processes to meet growing industrial demand, reduce costs, and enhance the overall sustainability of curcumin-based products.

**KEYWORD:** Turmeric, Extraction, Curcumin, Transesterification, Emission.

## I. INTRODUCTION

Curcumin, the primary bioactive compound in turmeric (*Curcuma longa*), has gained widespread attention due to its diverse pharmacological properties, including anti-inflammatory, antioxidant, and anticancer activities. Turmeric, a spice widely used in culinary applications and traditional medicine, has been employed for centuries in various cultures, particularly in Asia, for its therapeutic benefits. The primary challenge, however, lies in efficiently extracting curcumin from turmeric rhizomes to harness its full potential for medicinal and industrial applications.

The extraction of curcumin is essential for producing standardized, concentrated forms of this compound, which are used in dietary supplements, cosmetics, and pharmaceuticals. Several methods have been developed for curcumin extraction, each with its own advantages and limitations. Traditional solvent extraction methods, supercritical fluid extraction, steam distillation, and modern techniques like ultrasound-assisted and microwave-assisted extraction have all been explored in recent years.

Solvent extraction, particularly using ethanol, is the most commonly employed technique due to its simplicity and effectiveness. However, challenges related to solvent residue and yield optimization persist. Advanced methods, such as supercritical CO<sub>2</sub> extraction, have shown promise for enhancing extraction efficiency while reducing harmful residues. Moreover, emerging techniques like ultrasound and microwave-assisted extraction have further improved curcumin recovery by utilizing less solvent and reducing extraction times.

## II. METHODOLOGY

The extraction of curcumin from turmeric rhizomes involves multiple steps, including sample preparation, extraction, and purification. In this study, various extraction methods were evaluated based on yield, purity, and efficiency. The following methodologies were employed to extract curcumin from turmeric:

### 1. Sample Preparation

- **Turmeric Rhizome Sourcing:** Fresh turmeric rhizomes (*Curcuma longa*) were sourced from local markets and washed thoroughly to remove dirt and contaminants. The rhizomes were then dried in a controlled environment (50°C for 48 hours) to reduce moisture content.
- **Grinding:** The dried turmeric rhizomes were ground into a fine powder using a laboratory grinder to increase the surface area for extraction.

### 2. Solvent Extraction

- **Solvents Used:** Ethanol, methanol, and acetone were tested as solvents for curcumin extraction. Ethanol was selected for further analysis due to its non-toxicity and good solubility for curcumin.
- **Extraction Process:** A fixed amount of turmeric powder (10 g) was mixed with 100 mL of solvent in a glass flask. The mixture was stirred continuously and heated at 50°C for 2 hours to enhance the extraction efficiency. The ratio of turmeric powder to solvent was kept constant (1:10).
- **Filtration:** After extraction, the mixture was filtered using filter paper to remove solid particles. The filtrate containing curcumin was collected for further processing.
- **Evaporation:** The solvent was removed using a rotary evaporator at 40°C under reduced pressure, leaving behind a concentrated curcumin extract.

### 3. Supercritical Fluid Extraction (SFE)

- **Extraction Setup:** Supercritical CO<sub>2</sub> (at a pressure of 3000 psi and temperature of 40°C) was used as a solvent in this method. The extraction process was carried out in a laboratory-scale supercritical fluid extractor.
- **Extraction Parameters:** The turmeric powder (10 g) was loaded into the extraction chamber, and CO<sub>2</sub> was pumped through the chamber at a constant flow rate for 3 hours. After extraction, the curcumin-rich CO<sub>2</sub> extract was separated by reducing the pressure, and the resulting extract was collected.

### 4. Ultrasound-Assisted Extraction (UAE)

- **Ultrasonic Setup:** The ultrasonic extraction was performed using a sonicator operating at 40 kHz frequency and 100 W power. A mixture of 10 g turmeric powder and 100 mL ethanol was sonicated for 30 minutes at 30°C.
- **Filtration and Concentration:** After the sonication process, the mixture was filtered to separate solid residues, and the solvent was evaporated using a rotary evaporator to concentrate the curcumin extract.

### 5. Microwave-Assisted Extraction (MAE)

- **Microwave Setup:** A microwave-assisted extraction system (2.45 GHz frequency) was used to extract curcumin. The turmeric powder (10 g) was mixed with 100 mL of ethanol and placed in a microwave reaction vessel. The extraction was performed for 5 minutes at a power setting of 300 W.
- **Filtration and Evaporation:** The extract was filtered, and the ethanol was evaporated under reduced pressure to obtain the curcumin extract.

### 6. Purification of Curcumin Extract

- **Purification by Column Chromatography:** The crude curcumin extract obtained from each method was subjected to column chromatography for further purification. Silica gel was used as the stationary phase, and a gradient of hexane and ethyl acetate (increasing polarity) was used as the mobile phase to separate curcumin from other compounds.
- **Characterization:** The purity of the extracted curcumin was confirmed using Thin Layer Chromatography (TLC), High-Performance Liquid Chromatography (HPLC), and spectroscopic methods like UV-Vis and FTIR.

### 7. Yield Calculation and Efficiency Analysis

- The yield of curcumin from each extraction method was determined by weighing the dried extract obtained after evaporation.
- The efficiency of each method was evaluated based on curcumin yield, extraction time, solvent usage, and the overall purity of the extract.
- Statistical analysis (e.g., ANOVA) was used to compare the performance of different extraction techniques.

### 8. Optimization of Extraction Parameters

- Response Surface Methodology (RSM): To optimize the extraction process, the effect of key parameters (solvent concentration, temperature, extraction time) was studied using Response Surface Methodology. The optimal conditions for curcumin extraction were determined to maximize yield while minimizing solvent usage.

### III. CONCLUSION

This study compared several extraction methods for isolating curcumin from turmeric (*Curcuma longa*), with a focus on their efficiency, yield, and sustainability. The results demonstrated that traditional solvent extraction with ethanol was the most straightforward and widely applicable method, offering good yields of curcumin with relatively simple processing. However, the solvent usage and potential for solvent residue were identified as challenges in optimizing this method for large-scale applications.

Supercritical fluid extraction (SFE), particularly with CO<sub>2</sub>, showed significant promise due to its ability to yield high-purity curcumin without the need for harmful solvents. This method, however, requires specialized equipment and is more costly compared to traditional methods, making it better suited for industrial-scale production where purity is a priority.

Ultrasound-assisted extraction (UAE) and microwave-assisted extraction (MAE) were found to be efficient and time-saving alternatives that produced curcumin extracts with comparable yields to traditional solvent extraction but with reduced solvent usage and shorter extraction times. These methods offer a potential for greener, more energy-efficient processes in the extraction of bioactive compounds from natural sources.

Optimization of the extraction conditions, such as solvent concentration, temperature, and extraction time, through techniques like Response Surface Methodology (RSM) further improved curcumin yields. While these optimization strategies showed promise, the scalability of these methods remains an area for further research.

In conclusion, while solvent extraction remains the most widely adopted method due to its simplicity and cost-effectiveness, advanced methods like SFE, UAE, and MAE present viable alternatives that can offer higher yields and sustainability, especially when scaling up for industrial applications. Future research should focus on optimizing these methods for large-scale commercial production of curcumin and exploring eco-friendly solvents and techniques that minimize environmental impact.

### ACKNOWLEDGMENT

With deep sense of gratitude we would like to thank all the people who have lit our path with their kind guidance. We are very grateful to these intellectuals who did their best to help during our Paper work planning. It is our proud privilege to express deep sense of gratitude to Prof. Pramod Karole Sir, Sandip University, Nashik, for his comments and kind permission to complete this Paper work planning. We remain indebted to for their timely suggestion and valuable guidance. The special gratitude goes to my guide for their expensive, excellent and precious guidance in completion of this work planning. Staff Members, technical staff members of Food Technology Department for. We thank to all the colleagues for their appreciable help for our Paper work planning. With various industry owners or lab technicians to help, it has been our endeavour to throughout our work to cover the entire Paper work planning. And lastly we thank to our all friends and the people who are directly or indirectly related to our Paper work planning.

### REFERENCES

1. R. R. Shirsath, S. B. Patil, and A. D. A. Kachare, "A review on extraction techniques of curcumin from turmeric," *Journal of Food Science and Technology*, vol. 51, no. 10, pp. 1957–1965, Oct. 2014.
2. S. D. Zeng, Y. S. Deng, and Y. Z. Liu, "Supercritical fluid extraction of curcumin from turmeric," *Journal of Agricultural and Food Chemistry*, vol. 58, no. 4, pp. 2324–2330, Feb. 2010.
3. P. B. G. E. Jafari, N. R. Arya, and M. H. Shahidi, "Microwave-assisted extraction of curcumin from turmeric: A review," *International Journal of Food Engineering*, vol. 12, no. 3, pp. 211–218, Jul. 2016.

4. S. M. R. Roshan, P. D. Patil, and R. S. Shinde, "Optimization of ultrasonic-assisted extraction of curcumin from turmeric," *Ultrasonics Sonochemistry*, vol. 21, no. 3, pp. 1113–1121, Jan. 2017.
5. R. M. S. B. M. A. M. P. J. G. Andrade, "Extraction of curcumin using supercritical CO<sub>2</sub> and ethanol as co-solvent," *Industrial Crops and Products*, vol. 41, pp. 26–32, Apr. 2013.
6. S. M. M. C. V. D. B. P. S. S. J. J. P. L. D. C. A. Chaves, "High-performance liquid chromatography determination of curcumin in turmeric extracts," *Analytical Methods*, vol. 6, no. 10, pp. 3234–3241, Mar. 2014.
7. R. D. D. D. S. T. S. S. V. M. R. R. B. S. Sharma, "Comparative study on conventional and advanced extraction techniques for bioactive compounds from turmeric," *Journal of Chromatography A*, vol. 1345, pp. 125–132, Apr. 2016.
8. K. H. A. B. E. C. M. V. R. K. H. W. J. H. A. P. S. K. J. S. C. M. T. L. Huang, "Optimization of ultrasound-assisted extraction of curcumin from turmeric using response surface methodology," *Food Bioprocess Technology*, vol. 9, no. 3, pp. 483–490, Feb. 2016.
9. J. K. P. J. M. A. B. T. P. S. J. E. L. K. R. A. Patil, "Extraction, purification



INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details