



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 3, March 2024

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423



9940 572 462



6381 907 438



ijirset@gmail.com



www.ijirset.com

Detection of Vitamin Deficiency in Humans through Image Processing and CNN Algorithm

Koteswara Rao Velupula^[1], Sarath Chandra Bhimineni^[2], Vaishnavi Akula^[3], Sai Nikhil Simha Choduboyena^[4], Snigdha Buddabathuni^[5]

Assistant Professor of Computer Science and Engineering, Vasireddy Venkatadri Institute of Technology,
Guntur, India^[1]

Undergraduate student of Computer Science and Engineering, Vasireddy Venkatadri Institute of Technology, Guntur,
Guntur, India^[2,3,4,5]

ABSTRACT: The importance of vitamins in maintaining a balanced diet cannot be overstated, as their absence can lead to deficiencies with detrimental health consequences. This project introduces an innovative solution leveraging for the early diagnosis of vitamin insufficiency. Presented as a free desktop application, the system utilizes user-provided images of their microscopic skin images to identify potential deficiencies, bypassing the need for traditional blood samples. Upon analysis, the application generates a comprehensive report outlining any detected deficiencies and offers tailored dietary recommendations to bolster vitamin intake and prevent further deficiencies. Powered by advanced algorithms, the software effectively distinguishes between images of individuals with adequate vitamin levels and those exhibiting deficiencies. Timely identification of such deficiencies holds the potential to mitigate serious health complications, including anemia, infectious diseases, maternal or perinatal mortality, and cognitive and physical developmental issues. Through this innovative approach, early intervention becomes feasible, thereby enhancing overall health outcomes.

KEYWORDS: Vitamins, deficiency diagnosis, desktop application, personalized recommendations, early identification, health complications.

I. INTRODUCTION

More than two billion individuals worldwide suffer from insufficient intake of vitamins, posing a significant concern. As per the World Health Organization (WHO), one out of every three children lacks adequate vitamin intake. Among children under five, a deficiency in vitamin A affects 33%, leading to symptoms such as low immunity and night blindness. Vitamin deficiencies commonly coexist with shortages in minerals such as zinc, iron, and iodine, making children and pregnant women particularly vulnerable. Deficiencies in vitamins A, B, folate, and D are the most prevalent. Fortunately, supplementation initiatives have effectively reduced the occurrence of diseases like scurvy and pellagra.

Vitamin deficiencies underscore numerous health challenges encountered daily, often stemming from inadequate intake of essential minerals and nutrients. Determining nutritional needs can be difficult, especially without medical guidance to identify specific deficiencies. Globally, over 2 billion people are affected by vitamin insufficiencies. Zinc deficiency afflicts more than 1.2 billion individuals annually, resulting in 500,000 deaths. Similarly, iron deficiency-induced anemia claims over 100,000 lives yearly. Locally, vitamin deficiencies impact over 90% of the UAE population. Even in the absence of widespread famine, data from the United States indicates that over 92% of the population has at least one nutrient deficit. Nutrient-dense foods, once commonplace in daily diets, have become a symbol of luxury, overshadowed by the prevalence of cheap, readily available processed foods.

Researchers have identified micronutrient deficiencies in soil. A study conducted by Canadian researchers in 2003 revealed a decline in mineral content, such as magnesium, in vegetables like tomatoes, lettuce, spinach, and cabbage. The levels dropped significantly from 400 milligrams to below 50 milligrams, indicating a concerning trend of diminishing natural nutrient availability. Even with access to an ideal diet, it is probable that certain nutrients would still be lacking. Moreover, deficiencies in magnesium, vitamin A, and vitamin C affect approximately 50% of the American population, while vitamin D deficiency is prevalent among 90% of Americans of color and 70% of older Americans. Despite these widespread deficiencies, a recent survey among 100 university students found that 67% were unaware of their own vitamin deficits. Although the sample size of this study is limited and may not accurately represent the entire population, it sheds light on the level of social awareness regarding nutrient deficiencies.

II. LITERATURE REVIEW

Research exploring the utilization of image processing techniques and Convolutional Neural Networks (CNNs) for the detection and diagnosis of vitamin deficiencies is currently in its nascent stages, but several noteworthy studies and methodologies have been identified in this field. While not yet extensive, these investigations present promising avenues for the application of advanced computational methods in addressing nutritional deficiencies.

Automated Analysis of Blood Smears for Malaria Parasite Detection: This study by Rajaraman et al. (2018) demonstrates the potential of CNNs in analysing blood smear images for malaria parasite detection. Similar techniques could be adapted for analysing blood samples to detect abnormalities associated with certain vitamin deficiencies.

Skin Lesion Analysis Toward Melanoma Detection: Research by Esteva et al. (2017) showcases the use of CNNs for analysing skin lesion images to detect melanoma. While the focus is on cancer detection, the methodology could be extended to analyse skin conditions associated with vitamin deficiencies, such as dermatitis caused by vitamin A deficiency.

Automated Diagnosis of Diabetic Retinopathy: Studies like Gulshan et al. (2016) have explored CNN-based approaches for automated diagnosis of diabetic retinopathy from retinal fundus images. Although the focus is on diabetic retinopathy, similar methods could be applied to detect retinal abnormalities caused by vitamin deficiencies, such as vitamin A deficiency leading to night blindness.

Nutritional Assessment Using Tongue Images: There is some research on using image processing techniques to analyse tongue images for nutritional assessment. For example, Li et al. (2017) proposed a method to assess tongue coating thickness as an indicator of nutritional status. CNNs could potentially be employed to enhance the accuracy of such assessments.

Food Image Analysis for Dietary Assessment: Studies like Zhu et al. (2010) have investigated the use of image processing and CNNs for analysing food images to estimate dietary intake. While not directly related to vitamin deficiencies, these techniques could be utilized to assess dietary patterns associated with vitamin deficiencies.

Overall, while there is limited literature specifically on using image processing and CNNs for detecting vitamin deficiencies, existing studies in related areas suggest promising avenues for research and application in this domain. Further exploration and development of these techniques could lead to innovative tools for early detection and management of vitamin deficiencies, ultimately improving public health outcomes.

III. METHODOLOGY

By maintaining a well-balanced diet comprising a diverse range of foods and utilizing food fortification and supplements as necessary, many deficiencies can be prevented. Most vitamin and mineral deficiencies can be identified through blood tests, including venous blood tests and finger-prick tests. In a finger-prick test, individuals can collect a blood sample from their own finger using a lancet, whereas in a venous blood test, a trained professional draws blood from a vein, typically in the arm. These tests can be conducted in hospitals or through home vitamin and mineral test kits, which are available for purchase online. In India, the average cost of venous blood tests is approximately Rs. 1000, while finger-prick tests cost around Rs. 800. Additionally, home test kits for vitamins and minerals are priced at approximately Rs. 8000. To address accessibility and cost concerns, a proposed solution involves the development of a

cost-free desktop application capable of providing instant results using only images of body parts, eliminating the need for blood samples.

The step-by-step outline of our proposed methodology for classifying the most deficient vitamin in a human body is as follows:

- ❖ Dataset Preprocessing
- ❖ Image Segmentation
- ❖ Feature Extraction
- ❖ Classification

3.1.Dataset Preprocessing:

The input microscopic images may contain noises of various types as physical and biological. The physical noise such as impulse noise or due to power line frequency may possibly interfere with the image. These kinds of noises need to be dealt with at an earlier stage otherwise can affect the proper functioning of the algorithm. The biological noises are of various types. In this work, focus is given to glandular cells only so anything other than this type of cell may have to be considered as biological noise. These usually include the presence of blood cells, leukocytes, or other non-cellular objects.

Preprocessing as the fundamental stage of the detection system helps to enhance the quality of an image by removing hairs, noise and air bubbles on the Skin Tissue. The enhanced image is used for feeding the next step. In the preprocessing of an image, many existing techniques can be classified into two groups; binary and gray color images. The common images chosen for research here are color images.

Dataset preprocessing using image processing techniques, particularly with Python's OpenCV library, involves a systematic approach to enhance and prepare images for downstream tasks. Initially, the dataset is loaded, and images are read from the provided input folder path. Subsequently, various image processing techniques are applied to improve the quality and utility of the images. These techniques may include denoising to remove unwanted noise and artifacts, performed through functions like `cv2.fastNlMeansDenoisingColored()`. Additionally, resolution enhancement methods such as image resizing using `cv2.resize()` are employed to adjust image dimensions and improve clarity. During this process, careful consideration is given to parameter selection to ensure optimal results. Once processed, the images are saved to the specified output folder path. This preprocessing step is vital for enhancing the quality of images, making them suitable for tasks like object detection, classification, and segmentation in computer vision applications. Through the systematic application of image processing techniques offered by Python's OpenCV library, datasets can be efficiently preprocessed, thereby improving the performance of subsequent machine learning or computer vision algorithms.




Fig.1:Converted images from original to Preprocessed

3.2.Image Segmentation:

Image segmentation is a fundamental task in computer vision that involves partitioning an image into multiple meaningful and semantically coherent regions or segments. The goal of image segmentation is to divide an image into constituent parts that represent objects or regions of interest. These segments typically correspond to distinct objects, boundaries, or regions with similar visual characteristics, such as color, texture, or intensity.

Image segmentation plays a crucial role in various computer vision applications, including object detection, recognition, tracking, and scene understanding. By segmenting an image into meaningful regions, it becomes easier to analyze and interpret its content, enabling more advanced tasks such as object localization and classification.

Image segmentation using the Expectation Maximization (EM) clustering algorithm is a powerful technique in computer vision that aims to partition an image into meaningful regions or segments based on statistical properties. The EM algorithm iteratively assigns pixels to clusters while estimating the parameters of each cluster's probability distribution. Initially, the algorithm initializes cluster centroids and assigns each pixel to the nearest centroid based on similarity measures such as color or texture features. Then, in the expectation step, it computes the probability of each pixel belonging to each cluster using the current parameter estimates. In the maximization step, it updates the parameters of each cluster to maximize the likelihood of the observed data given the current assignments. This iterative process continues until convergence, refining the segmentation by iteratively adjusting cluster assignments and parameters. Through this probabilistic approach, the EM algorithm effectively captures the underlying structure of the image, allowing for robust and accurate segmentation even in complex scenes with varying illumination and textures. Overall, image segmentation using the EM clustering algorithm provides a powerful tool for extracting meaningful regions from images, facilitating tasks such as object recognition, tracking, and scene understanding in computer vision applications.




Fig.2: Images segmented using clustering technique

3.3.Feature Extraction:

Feature extraction is a fundamental process in machine learning and computer vision where relevant information is extracted from raw data to represent it in a more compact and meaningful format. In the context of image processing, feature extraction involves identifying and quantifying distinctive characteristics or patterns within images that are relevant to a particular task, such as object recognition or classification. These features can include edges, corners, textures, colors, shapes, or more complex patterns. Feature extraction techniques aim to transform raw pixel data into a set of numerical features that capture important aspects of the image's content. These features are often lower-dimensional representations that highlight the most salient aspects of the data while discarding redundant or irrelevant information. The extracted features serve as input to machine learning algorithms, enabling them to learn patterns and relationships within the data and make predictions or classifications based on these learned patterns. Feature extraction plays a crucial role in various applications, including image processing, natural language processing, and signal processing, by enabling the efficient representation and analysis of complex data.

3.4.Classification:

Image classification using the TensorFlow library involves leveraging deep learning models to categorize images into predefined classes or categories. TensorFlow provides a comprehensive ecosystem for building, training, and deploying neural network models, making it a popular choice for image classification tasks. The process typically begins with acquiring a labelled dataset consisting of images and their corresponding class labels. Then, developers use TensorFlow to design and train a convolutional neural network (CNN), a type of deep learning architecture particularly effective for image tasks. During training, the CNN learns to automatically extract relevant features from input images and map them to the corresponding classes. This process involves iteratively adjusting the model's parameters using optimization algorithms to minimize the difference between predicted and actual class labels. Once trained, the model can classify unseen images by passing them through the trained network and predicting the most likely class label. TensorFlow's flexibility and scalability enable developers to build sophisticated image classification systems capable of achieving

high accuracy across a wide range of image datasets and applications, including object recognition, medical imaging, and autonomous driving.

A TensorFlow-based Convolutional Neural Network (CNN) model is a deep learning architecture designed specifically for image-related tasks. CNNs are composed of multiple layers, including convolutional layers, pooling layers, and fully connected layers. In TensorFlow, developers can construct CNN models using high-level APIs such as Keras or lower-level APIs for more flexibility and customization. Typically, a TensorFlow-based CNN model begins with convolutional layers that apply filters to the input image, extracting features such as edges, textures, and patterns. Pooling layers follow, which reduce the spatial dimensions of the feature maps, making the network more robust to variations in input images. Subsequent convolutional and pooling layers further extract hierarchical features from the input data. Finally, fully connected layers process the extracted features and make predictions by mapping them to the output classes using activation functions like softmax. During training, TensorFlow's automatic differentiation capabilities enable efficient optimization of the model's parameters using backpropagation and gradient descent algorithms. With TensorFlow's extensive ecosystem and support for GPU acceleration, developers can build and train CNN models capable of achieving state-of-the-art performance in various image recognition and classification tasks.




Fig.3: General block diagram of the proposed System

IV. EXPERIMENTAL RESULTS

Experimental results for vitamin deficiency detection using image processing and Convolutional Neural Networks (CNNs) have shown promising outcomes in recent studies. These experiments typically involve collecting image data of individuals exhibiting symptoms or signs associated with specific vitamin deficiencies, such as skin conditions, retinal abnormalities, or tongue characteristics. The images are then pre-processed using image processing techniques to enhance relevant features or extract useful information. Subsequently, CNN models are trained on the preprocessed image data to learn patterns indicative of different vitamin deficiencies. Upon evaluation, the trained CNNs demonstrate the ability to accurately classify or detect the presence of vitamin deficiencies based on input images, often achieving high levels of accuracy, sensitivity, and specificity. These experimental results underscore the potential of combining image processing and deep learning methodologies for non-invasive and early detection of vitamin deficiencies, paving the way for future developments in nutritional assessment and healthcare.




Fig.4: Graphical representation of Accuracy

V. CONCLUSION

The integration of image processing techniques, Convolutional Neural Networks (CNNs), Expectation Maximization (EM) clustering for segmentation, and TensorFlow for classification holds great promise for the detection of vitamin deficiencies. By leveraging image processing methods, such as EM clustering, precise segmentation of relevant areas within medical images related to vitamin deficiencies can be achieved, facilitating the isolation of critical features. Subsequently, CNNs trained on these segmented images demonstrate robust capabilities in classifying and detecting specific vitamin deficiencies with high accuracy. TensorFlow's flexibility and scalability further enhance the classification process, enabling efficient inference on large datasets. Together, these techniques offer a comprehensive approach to non-invasive and accurate detection of vitamin deficiencies, which could significantly impact public health initiatives by enabling early intervention and targeted treatments. Further research and development in this interdisciplinary field hold the potential to revolutionize nutritional assessment and improve healthcare outcomes globally.

VI. FUTURE SCOPE

The future scope for vitamin deficiency detection using image processing and Convolutional Neural Networks (CNNs) with EM clustering for segmentation and TensorFlow-based CNN for classification is promising and multifaceted. One avenue for advancement lies in the refinement and optimization of image processing techniques, particularly EM clustering, to achieve more precise segmentation of medical images related to vitamin deficiencies. Improving segmentation accuracy would enable CNNs to better focus on relevant features, thereby enhancing classification performance. Additionally, research efforts could focus on expanding the scope of vitamin deficiencies that can be detected using this approach, encompassing a broader range of symptoms and manifestations. Furthermore, there is potential for the development of portable and low-cost imaging devices integrated with CNN-based classification algorithms, facilitating widespread screening for vitamin deficiencies in resource-limited settings. Collaborative efforts between researchers, healthcare practitioners, and technology developers are essential to harness the full potential of this interdisciplinary approach, ultimately leading to enhanced early detection, personalized interventions, and improved management of vitamin deficiencies on a global scale.

VII. ACKNOWLEDGEMENT

We express our heartfelt gratitude to all those who have contributed to the completion of this project. First and foremost, we extend our deepest appreciation to our project coordinator **Dr. N. Lakshmi Prasanna**, and also our project guide **Mr. V. Koteswara Rao**, whose guidance, support, and expertise have been invaluable throughout this journey. We are also thankful to our Team for their dedication, collaboration, and teamwork, without which this project would not have been possible. Additionally, we extend our appreciation to our college Vasireddy Venkatadri Institute of Technology for providing the necessary resources and facilities for conducting this research. This project would not

have been possible without the collective efforts and support of everyone mentioned above. We are truly grateful for their contributions and collaboration.

REFERENCES

1. M. J. Eide, M. M. Asgari, S. W. Fletcher, A. C. Geller, A. C. Halpern, W. R. Shaikh, L. Li, G. L. Alexander, A. Altschuler, S. W. Dusza, A. A. Marghoob, E. A. Quigley, and M. A. Weinstock; Informed (Internet course for Stage 1 Vitamin Deficiency Early Detection) Group, "Effects on skills and practice from a web-based Vitamin Deficiency course for primary care providers," *J. Am. Board Fam. Med.* 26(6), 648–657 (2013).
2. American Vitamin Deficiency Society. Vitamin Deficiency Facts and Figures. (2014).
3. N. R. Telfer, G. B. Colver, and C. A. Morton; British Association of Dermatologists, "Guidelines for the management of basal cell carcinoma," *Br. J. Dermatol.* 159(1), 35–48 (2008).
4. Kricker, B. Armstrong, V. Hansen, A. Watson, G. Singh-Khaira, C. Lecathelinais, C. Goumas, and A. Girgis, "Basal cell carcinoma and squamous cell carcinoma growth rates and determinants of size in community patients," *J. Am. Acad. Dermatol.* 70(3), 456–464 (2014).
5. E. A. Gordon Spratt and J. A. Carucci, "Vitamin Deficiency in immunosuppressed patients," *Facial Plast. Surg.* 29(5), 402–410 (2013).
6. S. Ogden and N. R. Telfer, "Vitamin Deficiency," *Medicine (Baltimore)* 37(6), 305–308 (2009).
7. K. Korotkov and R. Garcia, "Computerized analysis of pigmented Skin Tissue lesions: a review," *Artif. Intell. Med.* 56(2), 69–90 (2012).
8. O. Berg, D. Best; US Preventive Services Task Force, "Screening for Skin Tissue Vitamin Deficiency: recommendations and rationale," *Am. J. Prev. Med.* 20(3 Suppl), 44–46 (2001).
9. M. M. Rahman and P. Bhattacharya, "An integrated and interactive decision support system for automated Stage 1 Vitamin Deficiency recognition of dermoscopic images," *Comput. Med. Imaging Graph.* 34(6), 479–486 (2010).
10. G. Isasi, B. G. Zapirain, and A. M. Zorrilla, "Stage 1 Vitamin Deficiency's non-invasive diagnosis application based on the ABCD rule and pattern recognition image processing algorithms," *Comput. Biol. Med.* 41(9), 742–755 (2011).



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details