



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 4, April 2025

Comparative Analysis of Bracing System using STAAD.Pro Software

**Mahesh Chiman Choudhary, Yash Baban Nale, Kundan Sunil Kumawat, Kiran Kerba Galande,
Prof. Ankita Mali**

Diploma Student, Department of Civil Engineering, JSPM Polytechnic College, Hadapsar, Maharashtra, India

Diploma Student, Department of Civil Engineering, JSPM Polytechnic College, Hadapsar, Maharashtra, India

Diploma Student, Department of Civil Engineering, JSPM Polytechnic College, Hadapsar, Maharashtra, India

Diploma Student, Department of Civil Engineering, JSPM Polytechnic College, Hadapsar, Maharashtra, India

Assistant Professor, Department of Civil Engineering, JSPM Polytechnic College, Hadapsar, Maharashtra, India

ABSTRACT: The increasing frequency of earthquakes and their devastating impact on structures necessitate effective seismic-resistant designs, particularly for multi-storey buildings. Tall buildings, while essential for modern infrastructure, face challenges in earthquake resistance due to lateral forces that compromise their stability. Steel bracing systems have proven to be an effective solution for enhancing the seismic performance of reinforced concrete (RC) buildings by improving lateral resistance and structural stiffness. This study evaluates the seismic behavior of G+4 RCC framed structures under Seismic Zone IV using STAAD.Pro V8i with the Response Spectrum Method. Different bracing configurations, including X-bracing, diagonal bracing, Y-bracing, and K-bracing, are analyzed for their impact on base shear, storey drift, storey displacement, and bending moment. Results indicate that X-bracing offers the highest structural stiffness and significantly reduces lateral displacements. The comparative analysis highlights that braced frames are more efficient than unbraced structures, providing enhanced resistance to seismic forces. Among various configurations, X-bracing proves to be the most effective in RCC Structure due to its superior load distribution and stiffness enhancement. The findings contribute to the development of cost-effective and efficient seismic-resistant designs for high-rise buildings in earthquake-prone regions

KEYWORDS: Structural Analysis, Bracing Systems, STAAD.Pro, X-Bracing, V-Bracing, Diagonal Bracing, Inverted V-Bracing

I. INTRODUCTION

In the field of structural engineering, the stability and performance of buildings under lateral loads such as wind and earthquakes are of paramount importance. Bracing systems play a critical role in enhancing the lateral load resistance and overall stability of structures, particularly in multi-storey buildings. With the increasing demand for safer and more cost-effective structural designs, it becomes essential to evaluate and compare various bracing configurations to determine the most efficient solution for different design requirements.

This study focuses on a comparative analysis of five structural configurations: X-bracing, V-bracing, Diagonal bracing, Inverted V-bracing, and an unbraced frame. The analysis is conducted using STAAD.Pro, a widely used finite element analysis software in structural engineering. Each configuration is subjected to different loading conditions, including dead load, live load, wind load, and seismic load, to assess its performance in terms of displacement control and cost-effectiveness.

By evaluating key parameters such as lateral displacement, structural behavior under dynamic loads, and material consumption, this research aims to identify the most efficient bracing system for improving structural performance. The results of this study provide valuable insights for engineers and designers in selecting suitable bracing systems that balance strength, stability, and economic feasibility.

II. LITERATURE SURVEY

A significant amount of research has been conducted to investigate the impact of bracing systems on the seismic and wind performance of buildings. Bracing systems are widely recognized as one of the most effective methods for enhancing the lateral stiffness and strength of steel and reinforced concrete frames.

Chandurkar and Pajgade (2013) studied the seismic performance of multi-storey buildings using different types of bracings. Their research revealed that steel bracing significantly reduces lateral displacement and improves overall structural performance, particularly under seismic loads.

Rai and Goel (2004) explored the effectiveness of concentric and eccentric bracing systems in resisting lateral loads. Their results indicated that concentric bracing systems, such as X and V types, are more efficient in minimizing storey drift and improving stability.

Patel et al. (2015) analyzed various bracing patterns in multistorey steel frames using ETABS and concluded that diagonal bracing provides superior lateral stiffness and is more cost-effective compared to other types.

Saha and Roy (2017) conducted a comparative study between braced and unbraced structures using STAAD.Pro. They reported that braced frames exhibit significantly lower displacement under lateral loads, confirming the importance of selecting appropriate bracing for seismic regions.

Kumar and Sudhakar (2020) examined the performance of inverted V and K-bracing in steel structures. Their findings highlighted the advantages of inverted V-bracing in distributing loads more uniformly and reducing bending moments in columns.


These studies collectively emphasize the necessity of incorporating appropriate bracing systems in structural design, particularly in high-risk seismic and wind zones. However, limited research has focused on a detailed comparative evaluation of multiple bracing configurations in a unified framework, especially using STAAD.Pro as an analysis tool. This study aims to bridge this gap by systematically analyzing and comparing X-bracing, V-bracing, diagonal bracing, inverted V-bracing, and unbraced frames under varying loading conditions, with a focus on both performance and cost.

III. METHODOLOGY

The primary objective of this project is to evaluate the effectiveness of different bracing systems in improving the seismic performance of a G+4 (Ground + 4 floors) structure located in Earthquake Zone 4. The analysis is performed using STAAD.Pro, a widely accepted structural analysis software. The methodology followed in this study is divided into the following steps :-

1. Structural Model Description

- A G+4 structure was selected for analysis, with each storey having a uniform height of 3 meters.
- The structural framing system consists of beams and columns with the following cross-sections:
 - a) Beams: 230 mm × 230 mm
 - b) Columns: 230 mm × 300 mm
- The plan and elevation of the building were kept consistent for all models to ensure fair comparison.
- All members were modeled as prismatic sections, assuming rigid floor diaphragms and fixed supports at the base.



2. Bracing Configurations


Five structural configurations were modeled:

- **Model 1:** Unbraced Frame (used as the control model)
- **Model 2:** X-Bracing
- **Model 3:** V-Bracing
- **Model 4:** Diagonal Bracing
- **Model 5:** Inverted V-Bracing

3. Load Application

The following loads were applied to all structural models as per Indian Standard Codes:

- **Dead Load (DL):** Applied as uniform area load of 3 kN/m², representing the self-weight of structural components.
- **Live Load (LL):** Applied as uniform area load of 2 kN/m², representing furniture, occupancy, and other variable loads.
- **Floor Finish Load (FF):** Applied as 1 kN/m² to account for tiling, plastering, and additional floor materials.
- **Seismic Load:**
 - Considered as per IS 1893 (Part 1): 2016
 - Zone Factor (Z): 0.24 (for Zone 4)




4. Structural Analysis in STAAD.Pro

- Each model was analyzed using STAAD.Pro's analysis engine.
- All loads were defined in the load case manager, and appropriate load combinations were generated as per IS 456 and IS 1893.
- The structure was meshed and analyzed to determine:
- Maximum Lateral Displacement.

5. Performance Evaluation Parameters


After running the analysis, the following output parameters were extracted and compared:

- **Displacement:** Lateral deflection at the top storey (critical in seismic design)




Unbraced Structure


X-Bracing



Diagonal Bracing



Inverted V-Bracing



V-Bracing

IV. RESULTS

Bracing System	Displacement	Cost	Openings
X-Bracing	(0.0010) Low	High	Limited
V-Bracing	(0.0046) Moderate	Moderate	Some Restrictions
Inverted V-Bracing	(0.0040) Moderate	Moderate	Some Restrictions
Diagonal-Bracing	(0.0080) High	Low	More Flexible
Without Bracing	(0.030) Very High	Very Low	Most Flexible

V. CONCLUSION

Based on the comparative analysis conducted using STAAD.Pro, it is evident that the implementation of bracing systems significantly enhances the structural performance of the building by reducing displacement under seismic loads.

Among the five configurations studied—X-bracing, V-bracing, Diagonal bracing, Inverted V-bracing, and an Unbraced frame—Diagonal and X-bracing proved to be the most effective in minimizing lateral displacement, thereby offering superior structural stability. While all braced models outperformed the unbraced frame in terms of displacement and performance, the cost analysis revealed that certain bracing systems, particularly Diagonal bracing, provide a more favorable balance between material usage and structural efficiency.

REFERENCES

1. STAAD.Pro Software. (2020). STAAD.Pro User's Manual. Bentley Systems, Incorporated.
2. American Concrete Institute. (2019). ACI 318-19: Building Code Requirements for Structural Concrete. American Concrete Institute.
3. American Society of Civil Engineers. (2019). ASCE 7-19: Minimum Design Loads for Buildings and Other Structures. American Society of Civil Engineers.
4. International Code Council. (2018). International Building Code (IBC). International Code Council.
5. American Institute of Steel Construction. (2016). AISC 360-16: Specification for Structural Steel Buildings. American Institute of Steel Construction.
6. Chopra, A. K. (2017). Dynamics of Structures: Theory and Applications to Earthquake Engineering. Prentice Hall.
7. Clough, R. W., & Penzien, J. (1993). Dynamics of Structures. McGraw-Hill.
8. Hariharan, S. (2017). Structural Analysis and Design of Tall Buildings: Steel and Composite Construction. Springer.
9. Kim, J. H. (2018). Structural Analysis and Design of Buildings: A Practical Guide. CRC Press.
10. McCormac, J. C. (2017). Structural Steel Design: A Practical Approach. Pearson.
11. ASCE. (2017). ASCE/SEI 41-17: Seismic Evaluation and Retrofit of Existing Buildings. American Society of Civil Engineers.
12. ATC. (2018). ATC-58: Development of Next-Generation Performance-Based Seismic Design Guidelines. Applied Technology Council.
13. BSSC. (2018). BSSC 2018: NEHRP Recommended Provisions for Seismic Regulations for New Buildings and Other Structures. Building Seismic Safety Council.
14. EN 1993-1-1. (2005). Eurocode 3: Design of Steel Structures - Part 1-1: General Rules and Rules for Buildings. European Committee for Standardization.
15. EN 1994-1-1. (2004). Eurocode 4: Design of Composite Steel and Concrete Structures - Part 1-1: General Rules and Rules for Buildings. European Committee for Standardization.
16. REFERENCES – For load (IS 875-1987)
For concrete (IS 456-2000)



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details