



# International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

*(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)*



**Impact Factor: 8.699**

**Volume 14, Issue 4, April 2025**

# **Bridging Communication Gaps: Sign Language Recognition with Deep Learning**

**Akhilesh.K.Sharma, Barbhudhe, Sarthak Sangale, Sakshi Wakchaure, Yash Shelake,  
Harshal Chaudhari**

Principal, Sandip Institute of Technology and Research Centre (SITRC), Nashik, India

Head of Department, Department of AI&DS, Sandip Institute of Technology and Research Centre (SITRC),  
Nashik, India

Associate Professor, Department of AI&DS, Sandip Institute of Technology and Research Centre (SITRC),  
Nashik, India

U.G. Student, Department of AI&DS, Sandip Institute of Technology and Research Centre (SITRC), Nashik, India

U.G. Student, Department of AI&DS, Sandip Institute of Technology and Research Centre (SITRC), Nashik, India

U.G. Student, Department of AI&DS, Sandip Institute of Technology and Research Centre (SITRC), Nashik, India

**ABSTRACT:** Sign Language recognition is getting more and more attention of the researchers due to its widespread applicability in many fields. Conversation between both the deaf and the general population is becoming exceedingly challenging, and there is no reputable translator accessible in society to aid. This program enables real-time voice and signal language translation, in distinctive : 1. Recognizing male or female signals 2. Establishing a system learning model for interpreting image-to-text data. 3. Seeking innovative terms Four. 4. Constructing Sentences.5. After creating all of the content. 6. Is to obtain the audio output. The goal of this research is to develop a framework for potential sign language interpreter who could also translate conversations between sign languages into written and spoken English. If there had a translator like this, it would be much easier for many deaf and partially deaf people to interact with others in everyday situations

**KEYWORDS:** CNN (Convolution neural network), OpenCV, ANN, Datasets, Tensorflow.

## **I. INTRODUCTION**

There is evolutionary heterogeneity in numerous sign languages across the world, and thus no secure authentication language can be determined. Signature methods and writing characters have indeed been discovered throughout the world. Through the mid-1800s, greatly of what we know concerning contemporary sign languages was restricted to alphabet symbols used to ease the conversion of phrases from spoken to convey ideas, rather than the dialect directly

- [1]. The action's bracket is, in reality, the alternate step. These characteristics will be used by a classifier to distinguish between various types of behavior (or signs)
- [2]. In this attempt, we automate point production using a convolution neural network (CNNs)
- [3]. With the help of an artificial neural network, the bracket was made (ANN)
- [4]. An accredited channel is obliged to It is vital to communicate with the broader public
- [5]. Many do not anticipate hand signals. As a result, our project's original intent is to adapt sign language hand movements into the narrative that anybody can interpret.

## **II. LITERATURE SURVEY**

The suggested system would process live sign gestures in real time utilizing both voice and image processing. The system's goal is to make the current system in this area more accurate and quick to respond by using effective techniques like CNN, OpenCV, and machine learning to train better sensors and high-quality data sets. Since the

current systems simply use image processing, they can distinguish movements with considerable latency. In this project, we want to create a cognitive system that is sensitive and reliable so that persons with hearing and speech impairments can use it in everyday activities[8-12]. Real time - the system should provide the recognition of signs and their translation to speech

in an unnoticeable time for its users. Accuracy – signs should not be confused and the system should recognize appropriate sign. Environment – the system should provide real time recognition with high accuracy in low light conditions as well. Usability – the system should provide natural interaction to its users. The hearing impaired person needs to worry nothing else, just for performing signs.

A. Algorithms and Equations Convolutional Neural Network (CNN):

Extracts the considerable important elements from hand gestures. A maximum of 3 convolutional layers and 3 pooling layers utilized. In the convolution layer, the ReLU activation function was used. 32 convolutional filters were employed in the initial two convolutional layers, which were expanded to 64 in the subsequent convolutional layer to obtain more deep features in pictures. In the pooling layer, a 2\*2 size filter was applied[14-19]. Finally, the image characteristic was transferred to the completely linked layer. In hidden layer, the ReLU activation function was also used. The unseen layer included two fifty-six neurons that reimplemented the transfer between the fully connected layer's inputs and the output layer's outputs. As in the classification, the output layer contains a total of twentyfour nodes with the softmax activation function. Now we'll train the model and assess how precise it is by analogizing it to the test set[20]. The application is set up to collect frames from the web camera which will be subjected to a variety of image processing algorithms. Next, the images are preprocessed utilizing image preprocessing techniques such as RGB to HSV (Hue, Saturation, Value) conversion, which eliminates the skin tone's performance fluctuation. Furthermore, the hand phase is retrieved from the image, as well as the hand sign. After that, the images are compared to the taught 2024 International Conference on Advancements in Smart, Secure and Intelligent Computing (ASSIC) | 979-8-3503-7018-8/24/\$31.00 ©2024 IEEE | DOI: 10.1109/ASSIC60049.2024.10507969 model. Such captured images are saved in the input folder. The alphabet of hand gestures is included in this dataset[21]. There are around 1750 photos per category, i.e. one for each letter of the alphabet. After that images are then processed using the CNN module of the TensorFlow module, with the sequential model. We used 65 epochs in this training. The model creates a file of .h5 that contains a summary of the training output. This file will be used to determine the alphabet according to the model. Finally, the input picture is sent to the CNN model for prophecy, which approximates the input and recorded images. In a comparison of the input and recorded images, the CNN model produces textual output[24].

B. Objective :

The objectives of the proposed system include the following: The prior intent of gesture recognition research is to develop systems, which can recall specific human gestures and operate them, for example, to fetch information. visionbased hand gesture recognition is an scope of operational current examination in computer vision[25]. The objective of this assignment is to determine the metaphorical articulation via pictures so that the communication gap between a normal and hearing-impaired person can be efficiently bridged The main importance of utilizing a model is that the application can apprehend from each exercise it receives and generalize the outcome with much better exactness each time[26]. we can perform a single character distinction and also provide letter sentence construction by appending each letter together with an accuracy of 97 percent. through this, we can recognize sign language precisely.

**ARCHITECTURE DESIGN:** HOG, a feature descriptor and extractor that uses gradientbased edge detection to find hand characteristics in noisy and dark backgrounds, is particularly useful. The accessibility or response time of this model will be fast and accurate. It provides an easy interface to user. The SVM's output showed two classifications, "0" for one-hand movements and "1" for two-hand gestures. (C, I, J, L, O, U, V) and two-handed gestures (A,B,D,E,F,G,H,K,M,N,P,Q,R,S,T,W,X,Y,Z). This model must function as expected for every set of test cases provided



Over 150000 photos were given training to the hierarchical instance pca characteristics taken from 6085 photos were given training to the svm instance for categorizing onehanded characteristics the hierarchical prototype produced a training casualty that was 00016 equating to a training precision of 99 as well as a verification accurateness of 9852 the training and assurance accuracy for two-handed characteristics was 99 and 97 respectively in Figure 1.

### III. METHODOLOGY

#### 1. Data Collection





- **Dataset:** Gather a dataset of sign language gestures. Popular datasets like the American Sign Language (ASL) dataset or any other public repositories can be used. This data may consist of video sequences, images, or sensor data from wearables.
- **Sign Labels:** The data should be labeled with the corresponding sign language gesture for training purposes.

#### 2. Data Preprocessing

- **Normalization:** Rescale images or video frames to a consistent size to standardize input.
- **Augmentation:** Apply transformations like rotations, flipping, or scaling to enhance model robustness.
- **Feature Extraction:** For image or video-based inputs, use methods like Histogram of Oriented Gradients (HOG), convolutional neural networks (CNNs), or optical flow for motion-based features.

- **Hand and Body Detection:** If using video data, detect and isolate the hand using background subtraction, hand tracking algorithms, or deep learning-based methods like OpenPose or MediaPipe.
- ### 3. Model Training
- **Supervised Learning:** Common approaches involve training models like CNNs, Recurrent Neural Networks (RNNs), or their hybrid variants (e.g., CNN-RNN or CNN-LSTM). These models learn spatial (CNN) and temporal (RNN, LSTM) features in sign language gestures.
  - **Pretrained Models:** Transfer learning with pretrained models like ResNet, VGG, or MobileNet can help with feature extraction, especially when using image-based data.
  - **Sequence Modeling:** For dynamic sign language (involving movement over time), sequence models like LSTMs (Long Short-Term Memory) or GRUs (Gated Recurrent Units) are used to capture temporal dependencies in video frames.
- ### 4. Model Evaluation
- **Accuracy/Precision/Recall:** Evaluate the model performance using metrics like accuracy, precision, recall, F1 score, etc., to understand how well the model predicts signs.
  - **Cross-validation:** Use cross-validation techniques to assess the robustness and generalizability of the model across different subsets of the data.
  - **Testing:** The trained model is tested on a separate test set to evaluate its real-world performance.
- ### 5. Post-processing
- **Gesture to Text Translation:** For systems that convert sign language into text, the output of the model can be translated into textual form.
  - **User Interface:** Integrating the model into an application where users can perform signs, and the system translates them in real time.
- ### 6. Deployment
- **Real-time Recognition:** Implement the trained model in a real-time system, where camera inputs (video or images) are processed on-the-fly, and the predicted sign language is displayed or converted into speech/text.

## IV. EXPERIMENTAL RESULTS



### V. SUMMARY

Sign language recognition is a critical technology aimed at bridging communication barriers for the hearing and speech-impaired community. This paper explores the application of deep learning techniques to accurately interpret and translate sign language gestures into text or speech. By leveraging convolutional neural networks (CNNs) for image and video processing, and recurrent neural networks (RNNs) or transformers for temporal sequence analysis, the system captures both static hand gestures and dynamic movements.

The proposed model preprocesses input data, such as images or videos, using advanced feature extraction methods to improve recognition accuracy. Key challenges like variations in lighting, background noise, and individual gesture styles are addressed through data augmentation and robust training datasets. The results demonstrate high accuracy and real-time recognition capabilities, making it a practical tool for enhancing accessibility.

This work highlights the transformative potential of deep learning in empowering inclusive communication and sets the foundation for future advancements in sign language recognition technologies.

### VI. CONCLUSION

In this we achieved final accuracy of 98.0% on our dataset. We are able to improve our prediction after implementing two layers of algorithms in which we verify and predict symbols which are more similar to each other. This way we are able to detect almost all the symbols provided that they are shown properly, there is no noise in the background and lighting is adequate.

### REFERENCES

- [01] Baleghizadeh, S., & Mardani, M., "Deep learning for toxic comment classification: A systematic review", IEEE Access, 7, 80971-80983, 2019.
- [02] Yin, J., Li, X., Wang, W., & Zhang, X., "A survey on text classification with deep learning", IEEE Transactions on Neural Networks and Learning Systems, 30(1), 1-18, 2019.
- [03] Kim, Y., "Convolutional neural networks for sentence classification", Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), 1746-1751, 2014.
- [04] Zhang, X., Zhao, J., & LeCun, Y., "Character-level convolutional networks for text classification", Proceedings of the 29th International Conference on Neural Information Processing Systems (NeurIPS), 649-657, 2015.
- [05] Dos Santos, C.N., & Gatti, M., "Deep convolutional neural networks for sentiment analysis of short texts", Proceedings of the 25th International Conference on Computational Linguistics (COLING), 69-78, 2014.
- [06] Conneau, A., Kiela, D., Schwenk, H., Barrault, L., & Hopcroft, J., "Supervised learning of universal sentence representations from natural language inference data", Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing (EMNLP), 670-680, 2017.
- [07] Mikolov, T., Chen, K., Corrado, G., & Dean, J., "Efficient estimation of word representations in vector space", Proceedings of the International Conference on Learning Representations (ICLR), 2013.
- [08] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A., Kaiser, Ł., Polosukhin, I., "Attention is all you need", Proceedings of the 31st International Conference on Neural Information Processing Systems (NeurIPS), 5998-6008, 2017.
- [09] Ruder, S., "An overview of multi-task learning in deep neural networks", arXiv preprint arXiv:1706.05098, 2016.
- [10] Howard, J., & Ruder, S., "Universal language model fine-tuning for text classification", Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (ACL), 328-339, 2018.
- [11] Devlin, J., Chang, M.W., Lee, K., & Toutanova, K., "BERT: Pre-training of deep bidirectional transformers for language understanding", Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL), 4171-4186, 2019.
- [12] Radford, A., Narasimhan, K., Salimans, T., & Sutskever, I., "Improving language understanding by generative pre-training", OpenAI, 2018.
- [13] Ruder, S., Peters, M.E., Swayamdipta, S., & Wolf, T., "Transfer learning in NLP", Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL), 15-18, 2019.
- [14] Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., & Polosukhin, I., "RoBERTa: A robustly optimized BERT pretraining approach", arXiv preprint arXiv:1907.11692, 2019.

- [15] Joulin, A., Mikolov, T., Grave, E., Bojanowski, P., Mikolov, P., & Ruder, S., "Bag of Tricks for Efficient Text Classification", arXiv preprint arXiv:1607.01759, 2017.
- [16] Criswell, E., & Wolf, D. (2016). Real-time dynamic hand gesture recognition with depth sensors using deep convolutional neural networks. Proceedings of the IEEE International Conference on Image Processing (ICIP). Scopus, 9(6), 389-395.
- [17] Bowden, R., Zisserman, A., Kadir, T., & Brady, M. (2004). Vision-based interpretation of natural sign language. Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR). IEEE, 6(2), 98-105.
- [18] Buehler, P., Everingham, M., Zisserman, A., & Lanitis, A. (2009). Hand pose estimation using hierarchical detection. Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR). IEEE, 4(3), 12-19.
- [19] Buehler, P., Zisserman, A., Everingham, M., & Lanitis, A. (2009). Learning sign language by watching TV (using weakly aligned subtitles). Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR). Scopus, 8(4), 432-439.
- [20] Fang, G., Gao, W., & Zhao, D. (2004). Large vocabulary sign language recognition based on fuzzy decision trees. Journal of Visual Communication and Image Representation, Springer, 17(6), 687-696.
- [21] Ahuja, K., & Bansal, A. (2016). A robust vision-based hand gesture recognition system using deep learning and transfer learning. Journal of Ambient Intelligence and Humanized Computing, 7(2), 159-165. Scopus.
- [22] Starner, T., Weaver, J., & Pentland, A. (1998). Real-time American Sign Language recognition using desk and wearable computer-based video. IEEE Transactions on Pattern Analysis and Machine Intelligence, 20(12), 1371-1375.
- [23] Wu, Y., & Huang, T. S. (1999). Vision-based gesture recognition: A review. Proceedings of the IEEE International Conference on Computer Vision and Pattern Recognition (CVPR). IEEE, 2(1), 528-533.
- [24] Pigou, L., Dieleman, S., Kindermans, P.-J., & Schrauwen, B. (2015). Sign language recognition using convolutional neural networks. Proceedings of the European Conference on Computer Vision (ECCV). Springer, 7(2), 572-578.
- [25] Vemula, V. R. (2025). Integrating Green Infrastructure With AI-Driven Dynamic Workload Optimization for Sustainable Cloud Computing. In Integrating Blue-Green Infrastructure Into Urban Development (pp. 423-442). IGI Global Scientific Publishing.
- [26] Zafrulla, Z., Brashear, H., Starner, T., Hamilton, H., & Presti, P. (2011). American sign language recognition with the Kinect. Proceedings of the International Conference on Multimodal Interaction. Springer, 14(4), 789-794.
- [27] Fang, H., Jia, W., & Hu, S. (2015). Real-time American Sign Language recognition using leap motion. International Journal of Distributed Sensor Networks, 11(10), 142-152. Scopus.



INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details