



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.524

Volume 14, Issue 1, January 2025

Smart Management of EV Charging Stations

Mrs. Priti Yadav, Anand Shinde, Bhagyesh Sonawane, Samiksha Gaikwad, Sanika Chaturkar

Department of Information Technology, Sinhgad Institute of Technology and Science, Pune, India

ABSTRACT: Along with the building of charging stations, automakers like as TATA have introduced new electric vehicles to the market. However, when the stations are fully utilized, delays may occur due to the current charging duration, which ranges from 15 to 30 minutes. To address these issues, our proposal calls for connecting all EV charging stations into a single network. Users can locate and select their preferred station with ease, which ultimately saves time and is particularly helpful when driving electric cars long distances. Users can reserve slots when they become available; if not, the system asks them to select a different time. A portion of the amount must be paid for the online booking confirmation. Additionally, our system provides charging stations with a management interface to govern reserved and open slots and displays the fastest route to the selected station. Our web-based application senses direction using the Google Maps API and time-slot allocation algorithms. An online payment gateway expedites transactions, and our chatbot technology allows voice commands to be utilized to control the program. Customers can save a great deal of time by using our technology to locate and reserve appropriate charging stations.

KEYWORDS: management system, charging slot, EV Cars, GMap

I. INTRODUCTION

Both the use of fossil fuels and global warming have increased in recent years. the two pressing worldwide problems of global warming and the depletion of fossil fuels due to careless energy use. Installing fossil fuel-free renewable energy systems is necessary to address these problems. Japan's uptake of solar installations has accelerated due to the government's Feed-in Tariffs (Fit) scheme. However, the increasing output from these devices has had a detrimental effect on the system frequency and voltage distribution. As a result, the Fit system is currently being reassessed by the Japanese government. Furthermore, the cost of installing solar systems is falling yearly, pointing to a future with even reduced PV electricity costs. In order to receive power from PV systems in smart houses and transfer it to EVs and smart homes, this study suggests using EV charging stations as energy aggregators. These charging stations need fixed batteries in order to interchange electricity.

The goal of this project is to give customers a platform that allows them to plan charging times at available charging stations based on their requirements. The system has a number of features, such as an AI chatbot, digital payment alternatives, mapping capabilities for direction sensing, and alerts for every activity. A range of charging infrastructure types, each suited to certain places and needs, can be used to recharge electric vehicles. This chapter emphasizes technical details and EV charger standards to emphasize the importance of considering local design and execution for EV charging networks. As electric vehicles (EVs) continue to gain traction as a cleaner alternative to conventional fossil-fuel-powered vehicles, the demand for efficient, accessible, and intelligently managed EV charging infrastructure has increased significantly. Smart management of EV charging stations is a crucial step in enabling widespread adoption and seamless integration of EVs into the existing power grid and transportation systems. Traditional charging setups face multiple challenges, including limited grid capacity, inefficient energy distribution, and the inability to handle fluctuating demand. As a result, there is a need to move towards a system where EV charging stations are optimized, responsive, and adaptable to both user demands and grid requirements. Smart management involves deploying digital tools, such as AI-driven software, real-time data analytics, Internet of Things (IoT) connectivity, and cloud-based management systems, to create an efficient, user-centered charging network.

II. RELATED WORK

This paper [1] proposes the use of a coreless axial flux permanent magnet machine, which has the attributes of low stator mass, negligible core loss and virtually zero cogging torque, as the propulsion motor. As small-sized [2] superconducting magnetic energy storage (SMES) system is commercially available at present, the function and effect of a small-sized SMES in an EV charging station including photovoltaic (PV) generation system is studied in this paper, which provides a practical application of small-sized SMES. The comparison of three quick response energy

storage systems including flywheel, capacitor (super-capacitor) and SMES is also presented to clarify the features of SMES. Having a network[3] of fast charging stations seems necessary in order to make EVs more attractive and to achieve larger uptake of them. Currently, 50 kW quick chargers that can charge a typical EV in about an hour are commercially available. However, a 240 kW fast charging level which can charge a typical EV in 10 minutes has been introduced in standards. Electric vehicles (EVs)[4] are being introduced by different manufacturers as an environment-friendly alternative to vehicles with internal combustion engines, with several benefits. The number of EVs is expected to grow rapidly in the coming years. However, uncoordinated charging of these vehicles can put a severe stress on the power grid. The problem of charge scheduling of EVs is an important and challenging problem and has seen significant research activity in the last few years. In order to interface one PV port[5], one bidirectional battery port and one load port of PV-Battery DC power system, a novel non-isolated three-port DC/DC converter named Boost Bidirectional Buck Converter (B3C) and its control method based on three domain control are proposed in this paper.

III. APPLICATION BACKGROUND

The application of smart management in EV charging stations is crucial in addressing the growing demand for electric vehicle (EV) infrastructure while also supporting a sustainable energy ecosystem. With the rapid increase in EV adoption globally, traditional charging infrastructure faces challenges, including inefficient energy distribution, power demand fluctuations, and limitations in grid capacity. Smart management technology aims to address these issues by utilizing advanced digital solutions to create an efficient, responsive, and user-centric EV charging network.

In a smart management system, charging stations are equipped with Internet of Things (IoT) sensors, artificial intelligence (AI) software, and cloud-based data processing, enabling real-time data exchange between the stations, users, and power grids. This connectivity allows for advanced features, such as demand-response charging, where charging speeds can be automatically adjusted based on grid load, renewable energy availability, and user needs. For example, during peak demand hours or times of limited renewable energy generation, smart charging stations can slow down or delay charging to help balance grid load, preserving stability while still meeting user needs.

In addition to optimizing energy distribution, smart management applications enhance the user experience by offering digital tools such as mapping for locating available stations, mobile app integration for booking and payments, and real-time notifications on charging status. These features make charging more convenient and accessible, encouraging EV use and minimizing the risk of grid overloads or energy shortages.

Furthermore, bidirectional power transfer (vehicle-to-grid or V2G technology) is often integrated into smart charging systems, allowing EVs to act as mobile energy storage units. In times of high demand, EVs connected to the grid can send power back, effectively supporting grid stability and reducing reliance on fossil-fuel-based energy sources. This capability creates a symbiotic relationship between the transportation and energy sectors, helping to smooth fluctuations in renewable energy supply by storing excess power during times of high production and releasing it when demand rises.

Overall, the background and need for smart management in EV charging stations stem from the necessity to address grid constraints, meet growing consumer demands for convenient charging, and support the global shift towards renewable energy. Smart charging infrastructure plays a foundational role in making EVs a viable and sustainable mode of transportation while helping to build a resilient, renewable-powered energy network.

IV. OPEN ISSUES

Because of its widespread use and applications, a great deal of work has been done in this sector. Some of the methods that have been used to accomplish the same goal are mentioned in this section. The methods for intelligent management of EV charging station networks are primarily different from these efforts.

- System not available
- Time consuming process
- Domain wise analysis is time consuming
- Grid Capacity and Stability
- Interoperability and Standardization

V. NEED OF THE NEW SYSTEM

- We are developing a system in which we going to connect all the electric car charging stations together.
- By using our system user can find the station according to their choice and it will be useful for those who want to travel for long distance with their EV cars and it will be time saving. It will be very easy to use.
- If the given time slot is available then your place for the given slot will be booked.
- Otherwise system will ask to enter the new time schedule. In this system user has to pay some percent of amount online to confirm their booking. Our system will also provide shortest map route to reach at given station.
- Our system will also provide interface for charging stations to view all available slots as well as booked slot lists and manage slot timing.
- The rapid expansion of electric vehicles (EVs) and the growing demand for sustainable energy solutions highlight the need for a new, smart management system for EV charging stations.
- With the increasing number of EVs, users often face challenges finding available charging stations and managing their charging schedules effectively.
- A smart EV charging management system provides users with a convenient, seamless experience by offering real-time station mapping, booking, payment integration, and notifications for charging status updates.
- Smart management systems can leverage time-of-use pricing and encourage users to charge during low-demand periods, reducing costs for both operators and consumers.

VI. FUTURE SCOPE

- **Advanced Energy Management**
Dynamic Load Balancing: Smart systems can optimize energy distribution among multiple charging stations based on real-time demand and grid capacity, preventing overloads.
Renewable Integration: Incorporating solar and wind energy sources can reduce reliance on fossil fuels and lower charging costs.
- **User-Centric Features**
Mobile Apps: Enhanced user interfaces for locating stations, reserving chargers, and tracking charging progress in real time.
Personalized Charging Plans: Tailored suggestions for users based on their driving habits and preferences, optimizing cost and convenience.
- **Interoperability and Standardization**
Unified Platforms: Development of standardized protocols for various EV models and charging systems to improve compatibility and user experience.
Cross-Network Access: Allowing users to access multiple charging networks through a single app or membership, simplifying the charging process.
- **Artificial Intelligence and Machine Learning**
Predictive Analytics: Using AI to forecast charging demand based on historical data and trends, helping to optimize station availability.
Automated Maintenance: Smart diagnostics can predict when maintenance is needed, reducing downtime and ensuring reliability.
- **Smart Grid Integration**
Vehicle-to-Grid (V2G): Enabling EVs to return energy to the grid during peak demand times, which can stabilize the grid and provide additional income for EV owners.
Demand Response Programs: Coordinating charging schedules with grid demands to balance energy use and enhance sustainability.
- **Infrastructure Expansion**
Rapid Deployment of Charging Stations: Smart management systems can identify optimal locations for new charging stations based on traffic patterns and EV ownership trends.

Multi-Use Charging Hubs: Integrating charging stations with other services (like retail or dining) to enhance user experience and increase station utilization.

- **Regulatory and Policy Support**

Incentives for Smart Technology Adoption: Government policies could promote the adoption of smart charging solutions through grants, tax incentives, or subsidies.

Standards for Security and Privacy: Establishing regulations to protect user data and ensure the cybersecurity of charging infrastructure.

- **Community and Fleet Solutions**

Shared Charging Networks: Community-based charging solutions that allow for the shared use of charging stations among multiple users or organizations.

Fleet Management: Smart solutions for managing charging needs of electric fleets, optimizing routes, and reducing operational costs.

- **Integration with Renewable Energy**

Smart EV charging stations of the future will be tightly integrated with renewable energy sources such as solar and wind. Through advanced energy management systems, charging stations will dynamically allocate energy based on the availability of renewables, thus minimizing dependency on fossil fuels. These systems will optimize charging schedules to coincide with periods of high renewable generation, further promoting a low-carbon grid.

- **Advanced Payment Systems and Incentives**

With the increasing availability of digital payment systems, future EV charging platforms will support a range of payment options, including subscription models, pay-per-use, and even rewards for charging during off-peak hours. Such incentives could encourage users to charge at times when renewable energy is most abundant, fostering greater alignment with sustainable energy goals.

- **Ultra-Fast Charging and Wireless Charging**

Future charging stations will likely offer ultra-fast and wireless charging capabilities. Ultra-fast charging will allow users to recharge their vehicles in minutes rather than hours, making EVs more convenient for long-distance travel. Wireless charging will eliminate the need for physical connectors, allowing vehicles to charge by simply parking over a charging pad—ideal for autonomous vehicles and high-frequency urban locations.

- **Global Standardization and Policy Support**

As EV adoption grows, global standardization of charging protocols, plug types, and payment systems will become critical to ensuring interoperability and a seamless user experience across borders. Governments and industry bodies are likely to work together to create unified standards and policies that support widespread adoption, ensuring that charging networks are accessible, user-friendly, and sustainable.

VII. CONCLUSION

We have successfully used a hybrid approach to web application development to create the "Smart Management of EV Charging Stations" system. The ability to reserve charging slots according to the particular kind of charging socket that the vehicle needs is one of the system's primary features. The system includes an AI chatbot that can answer questions and offer support in order to improve user interaction and support. This chatbot expedites the process of gaining access to charging stations and guarantees a flawless user experience. The system also makes use of the GMAPS API to enable precise direction sensing. This feature improves efficiency and convenience by making it simple for users to explore and find the closest charging station. In conclusion, a web application technique is incorporated into the "Smart Management of EV Charging Stations" system. It uses the GMAPS API for effective direction sensing, provides an AI chatbot for answering questions, and allows charging slot booking depending on charging socket types. The whole user experience will be enhanced and EV charging station management will be made simpler with this all-inclusive system.

ACKNOWLEDGMENT

We would like to thank our project guide Mrs.P.P.Yadav for her constant guidance in our project journey. Her knowledge and support made the process easier and the help we received pushed us forward whenever we were facing any problems. We thank her for her efforts, time, suggestions and encouragement throughout the project duration. We would also like to extend our gratitude to our Head of Department, Prof. Anjali, for giving us the opportunity to work on projects and enhance our skills. We express heartfelt gratitude towards Sinhgad Institute Of Technology And Science for encouraging students to learn and develop programming concepts through real time applications and projects.

REFERENCES

1. Y. Liu Y. Tang J. Shi X. Shi J. Deng and K. Gong "Application of small-sized smes in an ev charging station with dc bus and pv system" IEEE Trans. on Applied Superconductivity vol. 25 no. 3 pp. 1-6 June 2015.
2. M. Ahmadi N. Mithulananthan and R. Sharma "A review on topologies for fast charging stations for electric vehicles" 2016 IEEE International Conference on Power System Technology (POWERCON) pp. 1-6 Sep. 2016.
3. J. C. Mukherjee and A. Gupta "A review of charge scheduling of electric vehicles in smart grid" IEEE Systems Journal vol. 9 no. 4 pp. 1541-1553 Dec 2015.
4. H. Zhu D. Zhang B. Zhang and Z. Zhou "A nonisolated three-port dc/dc converter and three-domain control method for pv-battery power systems" IEEE Trans. on Industrial Electronics vol. 62 no. 8 pp. 4937-4947 Aug 2015.
5. Rallabandi D. Lawhorn J. He and D. M. Ionel "Current weakening control of coreless afpm motor drives for solar race cars with a three-port bi-directional dc/dc converter" 2017 IEEE 6th International Conference on Renewable Energy Research and Applications (ICRERA) pp. 739-744 Nov 2017.
6. . A.Hassoune M. Khafallah A. Mesbahi and T. Bouragba "Smart topology of evs in a pv-grid system based charging station" 2017 International Conference on Electrical and Information Technologies (ICEIT) pp. 1-6 Nov 2017.
7. B. Honarjoo S. M. Madani M. Niroomand and E. Adib "Non-isolated high step-up three-port converter with single magnetic element for photovoltaic systems" IET Power Electronics vol. 11 no. 13 pp. 2151-2160 2018.
8. S. Bai D. Yu and S. Lukic "Optimum design of an ev/phev charging station with dc bus and storage system" 2010 IEEE Energy Conversion Congress and Exposition pp. 1178-1184 Sep. 2010.
9. H. Zhu D. Zhang B. Zhang and Z. Zhou "A nonisolated three-port dc/dc converter and three-domain control method for pv-battery power systems" IEEE Trans. on Industrial Electronics vol. 62 no. 8 pp. 4937-4947 Aug 2015.
10. H. Zhu D. Zhang Q. Liu and Z. Zhou "Three-port dc/dc converter with all ports current ripple cancellation using integrated magnetic technique" IEEE Trans. on Power Electronics vol. 31 no. 3 pp. 2174-2186 March 2016.
11. SunTech Power STP235-20-Wd [online] Available: <https://www.freecleansolar.com/235W-solar-panels-Suntech-STP235S-20-Wd-mono-p/stp235s-20-wd.htm>.
12. CREE C3M0065090D MOSFET [online] Available: <https://www.wolfspeed.com/c3m0065090d>.
13. Infineon IPW90R120C3 MOSFET [online] Available: https://www.infineon.com/dgdl/Infineon-IPW90R120C3-DS-v01_00-en.pdf?fileId=db3a3043183a955501185000eld254f2.



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details