

ISSN(O): 2319-8753

ISSN(P): 2347-6710



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 3, March 2025





www.ijirset.com | A Monthly, Peer Reviewed & Refereed Journal | e-ISSN: 2319-8753 | p-ISSN: 2347-6710 |

Volume 14, Issue 3, March 2025

|DOI: 10.15680/IJIRSET.2025.1403105|

AI Driven Waste Conversion to Clean Energy

Dr. Rekha P S¹, Pavan Kumar R², Darshan D³, Rakshith Gowda R⁴

Associate Professor, Department of Electrical & Electronics Engineering, SJBIT, Bengaluru, Karnataka, India¹ U.G. Student, Department of Electrical & Electronics Engineering, SJBIT, Bengaluru, Karnataka, India^{2,3,4}

ABSTRACT: The project "Generating Electricity by Using Waste Materials" focuses on addressing two pressing global concerns: waste management and energy generation. By utilizing waste materials such as plastic, rubber, and garbage, the system converts thermal energy into electrical energy through a heating panel. This innovative approach not only reduces landfill waste but also promotes the use of renewable energy sources. The system integrates automation into waste management, incorporating features like an automatic trash bin that detects when it's full and transfers the waste to a furnace for processing. Real-time monitoring of generated electricity is achieved using a multimeter, ensuring efficiency and reliability. Supplemented by solar panels, the system maximizes energy generation while reducing environmental impact, providing a sustainable and eco-friendly solution to energy challenges. By combining advanced components such as Arduino Uno, cooling sensors, and carbon collecting plates, the project exemplifies an interdisciplinary approach. It demonstrates the practical application of engineering and programming (C language) to tackle environmental challenges, paving the way for cleaner energy production and a more sustainable future

KEYWORDS: Renewable energy, Automatic dustbin, heating panel, ultrasonic sensor, battery, led bulb.

I. INTRODUCTION

The world faces two critical challenges today: the growing demand for energy and the increasing accumulation of unmanaged waste. The relentless rise in global energy consumption has placed an immense burden on traditional energy sources, primarily fossil fuels. These non-renewable resources are not only depleting rapidly but also significantly contributing to environmental degradation through greenhouse gas emissions. On the other hand, waste management has become a daunting task, with millions of tons of waste generated annually, much of which ends up in landfills or the oceans, polluting the environment and harming ecosystems. In this context, the concept of converting waste into energy presents a compelling solution. Waste-to-energy systems offer a dual benefit: they mitigate waste disposal challenges while generating renewable energy. Such systems effectively utilize the latent energy stored in waste materials, transforming what is considered a liability into a valuable resource. By doing so, they reduce landfill dependency and contribute to the global push for cleaner, more sustainable energy solutions.

This project, titled "Generating Electricity by Using Waste Materials," is an innovative approach to addressing these pressing issues. The system focuses on converting waste materials such as plastic, rubber, and garbage into electricity using thermal energy. A heating panel and furnace facilitate the energy conversion process, while automated features ensure efficient waste handling and processing. Real-time monitoring and supplementary energy from solar panels further enhance the system's performance, making it a robust and sustainable solution. By integrating modern technologies such as Arduino Uno and C programming, this project exemplifies the potential of interdisciplinary engineering. The system demonstrates how electronics, automation, and renewable energy technologies can converge to create a functional and impactful solution. Such innovations are crucial for fostering sustainable development and addressing global challenges related to energy and waste management. In summary, the project aims to provide a scalable, eco-friendly, and cost-effective model for waste-to-energy conversion. It underscores the importance of adopting sustainable practices to combat environmental issues while meeting the growing demand for energy. By leveraging waste as a resource and incorporating renewable energy sources, the system represents a step forward in achieving a greener, cleaner future.






www.ijirset.com | A Monthly, Peer Reviewed & Refereed Journal | e-ISSN: 2319-8753 | p-ISSN: 2347-6710 |

Volume 14, Issue 3, March 2025

|DOI: 10.15680/IJIRSET.2025.1403105|

Block diagram



WORKING:

The sensors or deployed or incorporated to a dustbin and placed above the zaar box when the dustbin detects this and triggers a servomotor to open the bottom of the dustbin. The waste materials falls directly into the zaar box once the waste materials are in the zaar box, the materials catch fire automatically. The burning waste generates heat and that heat is transferred to a heating panel inside the zaar box this panel converts heat into electricity. Once the electricity generation is stable the powers the led bulb

COMPONENT SPECIFICATION

Arduino Uno

The Arduino Uno is a microcontroller board based on the ATmega328. It has 14 digital input/output pins, 6analoginputs,16 MHz ceramic resonator, USB connection, power jack, an ICSP header, and a reset button. It contains everything essential to support the microcontroller.

1. Microcontroller: ATmega328P

2. Operating Voltage: 5V3. Input Voltage: 7-12V

Solar Panels

Solar panels provide a supplementary source of energy, harnessing sunlight to generate electricity. This feature enhances the system's sustainability by reducing dependency on waste

5v1-channelrelay

In this project, a 5V 1-channel relay module is used to automate the ignition of waste in the furnace. The relay, controlled by the Arduino, connects the power from four lithium-ion batteries to a pencil, which acts as the ignition source. The graphite core of the pencil heats up due to electrical resistance when current flows through it, generating enough heat to create a controlled fire.

1. Operating Voltage: 5V

Relay Type: Single Pole Single Throw (SPST)
Contact Rating: 10A/250V AC, 10A/30V DC

4. Trigger Voltage: 2.5-5V5. Trigger Current: 5-10Ma





www.ijirset.com | A Monthly, Peer Reviewed & Refereed Journal | e-ISSN: 2319-8753 | p-ISSN: 2347-6710 |

Volume 14, Issue 3, March 2025

|DOI: 10.15680/IJIRSET.2025.1403105|

Battery

The battery stores the electricity generated by the system, providing a stable power supply for later use. This feature is particularly important for ensuring continuous energy availability during periods when waste combustion or solar energy generation is not possible.

The algorithm automatically generates mask image without user interaction that contains only text regions to be inpainted.

1.1 PROJECTPREPERATION&DEMONSTRATION



Procurement of components required

The pictures above demonstrate the beginning of our project where we procured the initial components for our project. Then we planned on how to arrange the components for work. Though this was a prototype which showcased our idea on how the project works, we planned on making the better furnace size. After making the connection, we planned that the dustbin is positioned directly above the zaar box. Then all the necessary electronic components were connected. We made sure that the proper output was met and completed the connections by programming the Arduino



PrototypeModel1

The above model (Model 1) is the prototype that we planned and the model (Model 2) below is the working one which shows the actual output or outcome of our project electricity generation from waste materials.





www.ijirset.com | A Monthly, Peer Reviewed & Refereed Journal | e-ISSN: 2319-8753 | p-ISSN: 2347-6710 |

Volume 14, Issue 3, March 2025

|DOI: 10.15680/IJIRSET.2025.1403105|



PrototypeModel2

The output is generated using waste materials

II. RESULT

The system successfully converts waste materials into electrical energy with minimal environmental impact. Real-time monitoring validates the output efficiency, and the integration of solar panels supplements the overall energy generation.

III. CONCLUSION

The project successfully demonstrates that waste materials can be a viable resource for energy generation. By integrating automation and renewable energy sources, it reduces environmental impact and promotes sustainability.

Through efficient design and implementation, the system achieves its objectives of reducing waste, generating electricity, and fostering eco- friendly practices. It serves as a model for innovative approaches to waste management and renewable energy solutions.

REFERENCES

- 1.M. Faccio, A. Persona, and G. Zanin, "Waste collection multi objective model with real time traceability data," Waste Manage., vol. 31, no. 12, pp. 2391–2405, Dec. 2011
- 2.S. Navghane, M. Killedar, and D. V. Rohokale, "IoT based smart garbage and waste collection bin," Int. J. Adv. Res. Electron. Commun. Eng., vol. 5,= no. 5, pp. 1576–1578, 2016
- 3.S. Kathirvale, M. N. M. Yunus, K. Sopian, and A. H. Samsuddin, "Energy potential from municipal solid waste in Malaysia," Renew. Energy, vol. 29, no. 4, pp. 559–567, Apr. 2004.
- 4. Sosunova and J. Porras, "IoT-enabled smart waste management systems for smart cities: A systematic review," IEEE Access, vol. 10, pp. 73326–73363, 2022











INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY







📵 9940 572 462 💿 6381 907 438 🔀 ijirset@gmail.com

